

Master Garden Products.

1-800-574-7248

Willow Fencing Care and Setup

Note: This is only our suggested method of setting up our Willow rolled fences. You may do it in any way you want. This is just a suggestion to help.

Our Willow rolled fences come in bundles for ease of transport. Once unrolled, these fences can be installed along a pre-existing fence or as a standalone fence with proper post and frame supports.

It is necessary to have a rigid structure to support most rolled fences like the bamboo rolled fence, reed fence, willow rolled fence or the heather fence when used as a fence. If it is being applied to an existing wooden fence which provides a flat vertical plane surface, the rolled fence can be held to the existing fence with galvanized wire or staples applied with a staple gun. Galvanized or stainless staples are recommended. If the existing fence is a chain link fence and the fabric of the fence is on the side to receive the reed, the material can be wired through the vertical fence materials to the chain link with galvanized wire. The wiring should be done about every 4 or 5 inches at top bottom and middle. We recommend and prefer using galvanized wire to tie the rolled fences whenever possible. **IMPORTANT NOTE:** When tying or stapling, all the rolled fences with wire line should be tied or stapled on the existing wire that are weaving them. This will blend the galvanized wire and staples to the existing wire and firmly hold the fences' structure.



Thank you for your business!

Any Questions? Call us at: **1-800-574-7248**

