



# NO-DIG EDGING KIT EASY TO INSTALL



## INSTALLATION INSTRUCTIONS

Always use proper safety precautions when cutting and spiking edging. Protective eyewear and gloves are recommended during installation.



**1** Clear the installation area of loose soil and debris. Place edging on the cleared surface with anchoring tabs flat on the soil.



**2** Pound anchoring spikes through tabs to secure the edging. Typical installations require one spike every 2-3 feet.



**3** Backfill to the top of the edging with mulch, rock, or other ground cover. Assure tabs are completely covered by bedding material.

## HELPFUL TIPS & INFORMATION

### Installation:

Certain conditions and landscape designs will require additional spikes, which are sold separately in stores and online.

Use a rubber mallet to pound spikes into the ground. Pound spikes only to the top of the edging tab. Too much tension on tabs can result in wavy edging.

Cut edging at the midpoint between the anchoring tabs using hand snips or a fine tooth saw.

### Preparation:

Soil must be level. Assure no debris is under the edging tabs. Compact soil can reduce spike movement and frost heave.

To use with weed fabric, install according to product directions. Install edging over the fabric. Spikes will easily pierce fabric.

Allow the edging to relax in the sun prior to installation and pull tightly between anchoring points. Doing so can reduce undesirable waves in straight installations.

## USING THE CONNECTOR

A specially designed connector is included with your Vigoro No-Dig Edging purchase. Use this connector to adjoin cut edging ends for a clean finish to your landscape project.

**1** Lay out edging along bed design prior to spiking tabs. Leave a 1-inch gap between edging ends.

**2** Secure each edging piece 2-3 tabs from the cut ends. Do not spike the end tabs closest to the connector.

**3** Slide the connector over the 1-inch gap and spike through the connector tab. Backfill with groundcover.

