

DEWALT®

GAS GENERATOR FEATURES

SPECIFICATIONS DXGNR7000

- 1 PREMIUM DeWALT ENGINE**
- 2 LOW-OIL LEVEL SHUTDOWN**
automatically safeguards engine from damage
- 3 HARDENED 1 1/4" STEEL TUBE CRADLE**
for added durability and strength
- 4 FOLD-DOWN/LOCKING HANDLE**
for sturdy portability and compact storage
- 5 WATTAGE METER**
gives instant feedback on how much power is being used
- 6 SMART RUNTIME METER**
shows fuel level and time remaining at current power level
- 7 HOUR METER**
tracks maintenance intervals
- 8 COVERED OUTLETS**
for protection from the elements and rugged working conditions
- 9 ELECTRIC START**
(battery included) provides hassle-free start-up
- 10 IDLE CONTROL**
conserves fuel and reduces noise on the job site
- 11 NEVER FLAT, DURABLE WHEELS**
for maximum portability and durability



GUARANTEED TOUGH.®

GAS GENERATORS



SPECIFICATIONS

Model No.	DXGNR7000 EPA/50 State	DXGNR7000 CSA	DXGNR5700 EPA/50 State	DXGNR5700 CSA
Rated Watts	7000 Watts	7000 Watts	5700 Watts	5700 Watts
Surge Watts	8750 Watts	8750 Watts	7125 Watts	7125 Watts
Engine	420cc	420cc	389cc	389cc
Oil Alert	Yes	Yes	Yes	Yes
USDA-Qualified Spark Arrestor/Muffler	Yes	Yes	Yes	Yes
Fuel Tank Capacity	7.5 Gallons	7.5 Gallons	6.7 Gallons	6.7 Gallons
Fuel Gauge	Yes	Yes	Yes	Yes
Run Time @ 50% Load	10.5 Hours	10.5 Hours	10.5 Hours	10.5 Hours
Unit Dimensions - L x W x H	27.2" x 27.4" x 28.5"	27.2" x 27.4" x 28.5"	27.2" x 27" x 25.7"	27.2" x 27" x 25.7"
Assembled Weight (Dry)	192 lbs. (87.1 kg)	199 lbs. (90.3 kg)	172 lbs. (78.0 kg)	172 lbs. (78.0 kg)
UPC	696471619331	696471002904	696471003109	696471002010
Starting Function	Recoil/Electric Start	Recoil/Electric Start	Recoil Start	Recoil Start

PREMIUM CONTROL PANEL



Includes Smart Runtime Meter, Hour Meter and covered outlets for protection from the elements and rugged working conditions. *DXGNR7000 models only



GREAT FOR CONTRACTORS



- (2) 5-20R GFCI Duplex, 120V
- (1) L14-30R, 120/240V



- (2) 5-20R GFCI Duplex, 120V
- (1) L14-30R, 120/240V



- (2) 5-20R GFCI Duplex, 120V
- (1) L14-30R, 120/240V



- (2) 5-20R GFCI Duplex, 120V
- (1) L14-30R, 120/240V

GUARANTEED TOUGH.®

0203530 REV. A 03/2017
 ©2017 DEWALT. DEWALT®, GUARANTEED TOUGH® and the yellow and black color scheme are trademarks of the DEWALT® Industrial Tool Co., used under license. All rights reserved.

Generac Power Systems, Inc.
 S45 W29290 Hwy. 59, Waukesha, WI 53189
generac.com 888-431-6871