

# Rough Opening Measurement Guide

## Adjustable Frame Commercial Door Kits

---

### Drywall Application *Stud Opening*

Height (in.) Width (in.)

VSDFDEX3680EL	81	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3680ER	81	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3684EL	85	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3684ER	85	37 <sup>5</sup> / <sub>8</sub>

### Masonry Application *Rough Opening*

Height (in.) Width (in.)

VSDFDEX3680EL	82 <sup>1</sup> / <sub>8</sub>	40 <sup>3</sup> / <sub>8</sub>
VSDFDEX3680ER	82 <sup>1</sup> / <sub>8</sub>	40 <sup>3</sup> / <sub>8</sub>
VSDFDEX3684EL	86 <sup>1</sup> / <sub>8</sub>	40 <sup>3</sup> / <sub>8</sub>
VSDFDEX3684ER	86 <sup>1</sup> / <sub>8</sub>	40 <sup>3</sup> / <sub>8</sub>

### Masonry Application *Stud Opening*

Height (in.) Width (in.)

VSDFDEX3680EL	81	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3680ER	81	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3684EL	85	37 <sup>5</sup> / <sub>8</sub>
VSDFDEX3684ER	85	37 <sup>5</sup> / <sub>8</sub>

*\*Please refer to the installation guide for more information*