

Technical Data Sheet

Product Description – SlipDoctors Deck Grip is a non-yellowing, waterbased acrylic sealer for concrete and other surfaces. This versatile coating is easy to apply and results in a barefoot-friendly, clear, semi-gloss finish that is chemical resistant, UV resistant and highly durable. The included Additive must be mixed with Deck Grip at time of application to provide increased surface traction and effective anti-slip protection. Deck Grip is the perfect solution to treat slippery pool decks, stone or concrete decks and natural stone surfaces where anti-slip protection is desired.

SlipDoctors Deck Grip

Special Features

- Interior & Exterior Use
- Barefoot Friendly
- Increases Traction
- UV & Chemical Resistant
- Chlorine Resistant
- Non-Yellowing
- Fast & Easy Application

Suggested Uses

- Commercial and Residential
- Stamped, Sealed & Stained Concrete Surfaces
- Driveways
- Patios
- Swimming Pool Areas
- Concrete & Stone Decks

Product Characteristics and Benefits

Surfaces	Stamped, sealed and stained concrete, sealed tile and natural stone
Color	Liquid milky white, dries clear with semi-gloss finish
Mode of Application	3/8" nap roller
Size	1 gallon, 5 gallon pail
Application Temperature	Surface, air and product temperature above 40°F (4°C) and at least 5°F (2°C) above the dew point
Recoat Time	2-4 hours
Light Traffic	6-12 hours
Normal Traffic	24 hours
Water Resistant	Yes, but cannot be continuously submerged.
Stain Resistant	Yes
Product Type	Water-based Acrylic Sealer
Coverage	300-600 sq. ft./gallon, coverage will vary due to surface porosity
Storage	Store in dry area at ambient room temperature of 72°F (22°C); Do Not Freeze.
Shelf Life	2 years in original unopened container; 1 year, opened container
Warranty	2 years
Removal	Xylene or Paint Thinner
Disposal	Dispose of container and unused contents in accordance with local, state, and federal regulations.

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before using.

Safety Precautions:

- Use in a well-ventilated area.
- If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Hotline at 1-800-424-LEAD or www.epa.gov/lead for more information.

Optional Safety Equipment:

- Chemical-resistant gloves
- Eye protection
- Mask

Surface Preparation:

Surface preparation varies by surface. Please see chart below for specific surface preparation instructions.

Application Instructions:

- MIXING:** Pour one gallon of Deck Grip into a separate container. Open the bottle of the included Deck Grip Additive and pour entire contents into the gallon of Deck Grip. Mix thoroughly for even distribution. NOTE: Mixture should be stirred frequently during application to ensure consistent Additive distribution. Do not thin.
- APPLICATION:** The Deck Grip mixture should be applied by rolling. Use the included 3/8" nap roller to evenly coat the surface. Avoid puddling in low areas. If puddles occur, roll them out immediately. Applying two thin coats is recommended rather than one thick coat. Wait 2-4 hours between coats. Roll second coat at a right angle to first coat. Dry times: Allow 6-12 hours for foot traffic and 24 hours for wheel traffic.
- CLEAN-UP:** While the Deck Grip mixture is still wet, application equipment can be cleaned with soap and water.

Maintenance:

- CLEANING:** Use a light pressure rinsing. For best results to remove oily deposits or other foreign matter, clean with a pH-neutral cleaner and scrub lightly with a soft bristle desk brush. Avoid alcohol-based cleaners.
- REMOVAL:** Use xylene or paint thinner to remove Deck Grip from the surface.

Surface Preparation

Surface Type	Surface Preparation
All Surfaces	All substrates must be clean, dry and free of dust, dirt, oil, grease, soil, soap residue, wax, flaking paint and other soluble contaminants. Do not use alcohol-based cleaners.
Painted Surfaces	Deck Grip cannot be applied over painted surfaces. All paint must be removed before application.
Sealed Surfaces	Chipped or flaking surfaces should be sanded or scuffed to a sound surface. If sealed surface is sound, lightly sand with 400 grit sandpaper to promote adhesion. Scrub and clean surface with pH-neutral cleaner. Rinse thoroughly and allow to dry before application.
Uncoated Concrete	New concrete should be allowed to cure for 30 days before application of any coating. If there is any doubt about the dryness of the concrete, conduct a test by placing a weighted rubber mat, plastic sheet or other nonporous material on the surface for 24 hours. Check the underside of the mat and concrete for signs of moisture. The concrete will be darker if damp. If moisture is found, allow additional dry time (10-14 days) and repeat test. If moisture persists, the concrete surface cannot be coated.
Unsealed Tiles & Natural Stone	Clean surface using pH-neutral cleaner or power-wash, rinse and allow to dry thoroughly before application. For best adhesion, surface can be lightly sanded with 400 grit sandpaper or etched using SlipDoctors Stone Grip.
Wood & Composite Wood	Deck Grip cannot be applied to wood or composite wood.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.

Deck Grip Safety Data Sheet can be found at www.slipdoctors.com.

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or support@slipdoctors.com.

Office Hours: Monday - Friday from 8:00 am - 5:00 pm CST

Warranty & Disclaimer

WARRANTY: All properly installed SlipDoctors products are guaranteed to increase the coefficient of friction of your surface for two (2) years (provided surface preparation and cleaning procedures are followed and no contaminants are present). If at any time during the warranty period the treated surface should lose its coefficient of friction, SlipDoctors shall at its option replace any product that proves defective. This warranty applies only to the product itself. Neither the Seller nor the Manufacturer shall be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the product. Before using, Buyer shall determine the suitability of the product for the intended use, and the Buyer assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by Seller and Buyer. Buyer assumes all risks and responsibility associated with disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents. Please visit www.slipdoctors.com to find further warranty information. KEEP OUT OF REACH OF CHILDREN.