

BEHR PREMIUM PLUS® Interior/Exterior Hi-Gloss Enamel Paint & Primer◊

No. 8150 ULTRA PURE WHITE®
No. 8153 Deep Base
No. 8154 Medium Base

- Glass-Like, Durable Finish
- Dirt & Grime Wipe Clean
- Tough, Stain Resistant Sheen
- Maximum Moisture Resistance
- Outstanding Hide
- 100% Acrylic
- Mildew Resistant Finish
- For High-Use Surfaces
- Lifetime Limited Warranty*

◊ A primer coat may be needed on some surfaces. See back label for details.

1 Hr Dry Time
2 Hr Recoat Time

250 – 400 Sq. Ft.
Coverage per Gallon

Soap & Water
Clean-Up

Protect
from Freezing

FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

For high-use surfaces. Ideal for Kitchens, Bathrooms, Cabinets, Shutters, Doors, Furniture, Garage Doors, Windows and Trim.

PREPARATION

Use on previously painted or primed Interior or Exterior surfaces. All surfaces should be properly prepared and cleaned. Remove loose paint and chalk. Wash off dirt and grease with detergent, rinse and allow to dry. Remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. Etch galvanized metal and rinse thoroughly. Allow new stucco, plaster and masonry to cure for 30 days before painting.

PRIME

Use BEHR PREMIUM PLUS® Paint as a primer over properly prepared coated or uncoated surfaces. For stain-blocking, or over oil-based or glossy interior surfaces, use a product such as BEHR® Kitchen, Bath & Trim Stain-Blocking Primer & Sealer No. 75. For stain-blocking, painting over woods with tannins, or over oil-based or glossy exterior surfaces, use a product such as BEHR® Multi-Surface Primer & Sealer No. 436.For best results, prime all metal surfaces before painting.

APPLICATION

Apply when air and surface temperatures are between 50–90°F (10–32°C). Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. Use a high quality 3/8–1/2" nap roller cover, nylon/polyester brush or airless sprayer (.015–.019" spray tip, 60 mesh filter). Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon. Certain colors may require more than one coat for complete hide. Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time. After 2 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent for interior applications and after 4 weeks for exterior applications. Dry paint film is mildew resistant. When applying to vinyl, color choice must be the same color or lighter than the existing color. **Do not use on floors**.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, expert project advice, and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

GREENGUARD GOLD

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **To obtain warranty service, call 1-800-854-0133.** Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-854-0133 Ext. 2 (U.S.A. only).

This product can expose you to chemicals including ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID**: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY**

BEHR

©2023 Behr Paint Company
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. < 50 g/L • REV. 10/23