

Garden Hose Washer Installation Guide

1. Package Contents

- 16 black garden hose washers with 4 small outer pieces;
- 16 red heavy-duty thermoplastic rubber washers with excellent sealing performance, packaged in a bag for convenient transportation.

2. Dimension Details

- Inner diameter of black washers: 5/8 inch / 16 mm;
- Inner diameter of red washers: 13 mm;
- Outer diameter of all hose washers: 1 inch / 25 mm;
- Thickness of all hose washers: 1/8 inch / 3 mm.

3. Material & Compatibility

These rubber washers are made of high-quality rubber, featuring durability, resistance to deformation and scratches. They are suitable for all standard 3/4-inch garden hose fittings.

4. Installation Steps

Step 1: Turn off the water controller to cut off the water supply.

Step 2: Rotate the faucet to detach the old washer from the garden hose fitting.

Step 3: Take out the appropriate new washer (black or red according to your needs) and install it into the fitting.

Step 4: Reattach the faucet by rotating it back to the original position.

5. Product Advantages

- Easy to install: No professional tools required, and the whole replacement process can be completed quickly.
- Effective leak repair: Perfectly replaces old or damaged washers, fixing water leakage at the faucet connection.

- Reliable sealing performance: The high-quality rubber material ensures tight sealing and long-term use.

6. Notes

- Ensure the water supply is completely turned off before installation to avoid water splashing.
- Choose the correct washer (matching inner diameter) for your garden hose fitting to ensure optimal sealing effect.
- Store unused washers in a dry and cool place to maintain their performance.