

# Installation Guide

## Installation & Operating Instructions

For your safety and to ensure proper operation, please read these instructions before installing and using your 2-Way Hose Splitter.

**Important Safety Notice** Always ensure the main water source is turned OFF before attempting to connect or disconnect any fittings. Do not overtighten connections. Hand-tightening is typically sufficient. Check all connections for leaks after installation and periodically during use.

## Tools Required

No tools are required for standard installation.

An adjustable wrench or pliers may be used for initial tightening if a connection is loose, but use with caution to avoid damaging the fittings.

## Installation Steps

### Step 1: Connect to Water Source

Turn the water faucet to the OFF position. Remove any existing hose or attachment. Screw the female 3/4" GHT thread (the larger opening with internal threads) on the base of the splitter clockwise onto your outdoor faucet spigot. Tighten securely by hand.

### Step 2: Attach Hoses to Quick-Connect Outlets

Ensure the independent shutoff valves on the splitter are in the OFF (closed) position. Push your garden hose ends onto the male quick-connect fittings on the two outlets. You will hear a faint "click" when the hose is securely locked in place. To disconnect, pull the collared sleeve on the quick-connect back towards the splitter body and gently pull the hose free.

### Step 3: Adjust and Position

The splitter body features a 360° rotatable design. Adjust its position to best suit your hose routing needs and to provide easy access to the shutoff handles.

### Step 4: Operate and Test

Slowly turn on the main water faucet. Open one shutoff valve on the splitter by turning the extended stainless steel handle counter-clockwise. Observe the connection points for any leaks. Repeat for the second outlet. If a minor leak occurs at the faucet connection, turn off the water and slightly tighten the connection.