

Contiene Xileno y Etilbenceno. El producto es nocivo si se inhala o se absorbe a través de la piel. Causa irritación en los ojos, la piel, la nariz y la garganta. Puede afectar el cerebro y el sistema nervioso y causar mareos, dolor de cabeza o náuseas. La inhalación prolongada de vapor puede tener como resultado daños físicos severos. Exposición repetida y prolongada a disolventes puede causar daño permanente a los riñones, el hígado, el corazón, el y el sistema nervioso. No respire los vapores. Utilice solamente con ventilación adecuada. Cerciórese de que exista entrada de aire fresco. Evite el contacto con la piel y con los ojos. No lo ingiero. Utilice guantes de goma y gafas de seguridad. El vapor puede hacer explosión. Mantenga alejado de fuentes de calor, chispas, flamas, luces piloto y otras fuentes de encendido durante su uso y hasta que los vapores hayan desaparecido. No fume. **PRIMEROS AUXILIOS:** PIEL: Lávese bien. OJOS: Enjuague inmediatamente c/abundante cantidad de agua. INHALACION: Trasládese al aire libre. INGESTION: NO INDUZCA EL VOMITO. Busque atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame al centro de control de envenenamientos al 1-800-222-1222. Consulte la Hoja de datos de seguridad (SDS, por sus siglas en inglés) para obtener información adicional. Para obtener una SDS, póngase en contacto con su proveedor o visite dap.com. **MANTENGA ALEJADO DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo

WARRANTY: DAP will provide replacement product or refund sales price if product fails to perform when used as directed within one year of purchase. Call 1-888-DAP-TIPS with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

QUESTIONS?/¿PREGUNTAS? Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.

DAP Products Inc.,
Baltimore, MD, 21224

Made in the USA for DAP Products Inc. with U.S. & globally sourced materials.
dap.com

GUTTERS • ROOFS • FLASHING • SIDING • WINDOWS • DOORS

ULTRACLEAR



Flexible All Purpose Waterproof Sealant



Stays Crystal Clear/ Non-Yellowing

CLEARER THAN SILICONE

- Ultra Flexible & Crackproof Even in Cold Weather
- Immediate Water Ready- Won't Wash Out
- Strong Multi-Surface Adhesion
- Cured Sealant is Mildew Resistant
- Paintable
- Interior/Exterior

DANGER! FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED.
Read side panel carefully for other cautions.

¡PELIGRO! LÍQUIDO Y VAPOR INFLAMABLES. NOCIVO O MORTAL SI LO TRAGA. Lea atentamente las precauciones en el panel del reverso.

10.1 fl oz (300 mL)

DAP® ULTRA CLEAR FLEXIBLE SEALANT is a premium all purpose, ultra elastic, ultra clear sealant for sealing & patching a wide variety of surfaces & projects. Use it to seal out air, water & moisture for a durable, 100% waterproof & weatherproof seal. Stays flexible & crackproof even in cold weather. Sealant does not yellow & is clearer than silicone. Tack free in 10 minutes & cures completely in 7 days. **USE FOR SEALING:** Windows, Doors, Siding, Trim, Gutters, Flashing, Roof Penetrations, Shingles, Eaves, Ducts, Vents, Skylights, Sinks, Showers, Tubs, Countertops. **ADHERES TO:** Asphalt, Wood, Fiber Cement, Vinyl, Metal, Glass, Fiberglass, Plexiglas®, Lexan®, PVC, ABS, Formica®, Ceramic, Concrete, Brick, Tile, Stone, Stucco

FOR BEST RESULTS: Apply in temperatures above 20°F. Not for continuous underwater use. Do not use on polystyrene products or plastics. Joint size should not exceed 3/8" wide by 3/8" deep. If joint depth exceeds 3/8", use backer rod material. Store unused container away from extreme heat/cold.

INSTRUCTIONS: 1. Remove old caulk, dirt, oily residue, frost & loose material from surface. 2. Trim nozzle at 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load cartridge into caulk gun. 5. Fill crack or gap with sealant. 6. Smooth bead with finishing tool if necessary before sealant skins over (approx. 5-10 min). 7. Clean excess uncured sealant from surface & tools with mineral spirits. Scrape or cut away excess cured sealant. Wash hands & skin only with soap & water. 8. Allow at least 24 hours before painting with latex paint only. Allow longer time in cool/humid climate conditions.

COVERAGE: 55 linear feet at 3/16" diameter bead size.

Contains Xylene and Ethylbenzene. Harmful if inhaled or absorbed through skin. Causes eye, skin, nose and throat irritation. May affect the brain and nervous system causing dizziness, headache or nausea. Prolonged vapor inhalation may result in severe physical injuries. Repeated and prolonged overexposure to solvents may cause kidney, liver, heart and permanent brain and nervous system damage. Do not breathe vapors. Use only with adequate ventilation. Ensure fresh entry. Avoid skin and eye contact. Do not ingest. Wear rubber gloves and safety glasses. Vapor may ignite explosively. Keep away from heat, sparks, flames, pilot lights and other sources of ignition. Do not smoke. **FIRST AID: SKIN:** Wash thoroughly. **EYE:** Flood with large quantities of water. **INHALATION:** Remove to fresh air. **INGESTION: DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **For emergencies,** call poison control center at 1-800-222-1222. See SDS for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer & Reproductive Harm
— www.P65warnings.ca.gov.

NCCS Calif. ARB VOC <1.5 wt /wt% (<296 g/L)