



## BEHR® WATER-BASED PRE STAIN WOOD CONDITIONER

No. B2080 Series

Clear

- Prepares Wood Surfaces for Water-Based Staining
- Excellent Penetration
- Helps Promote Even Staining



Prep Before Use



1 Coat Application



Spread Rate:  
100 Sq. Ft. / Qt.



Clean-Up:  
Soap & Water

### READY TO USE. PROTECT FROM FREEZING.

**WHERE TO USE:** Properly prepared interior bare or stripped wood surfaces prior to applying BEHR® Water-Based Wood Stain.

### SURFACE PREPARATION† (Proper surface preparation is required)

- Before applying BEHR Pre-Stain Wood Conditioner to bare or stripped wood surfaces, sand wood surfaces (with #180-220 grit sandpaper) in the direction of grain to the desired smoothness. Remove all dust from the surface with a tack cloth.

Note: BEHR Water-Based Pre-Stain Wood Conditioner is not recommended for use with oil-based stains. For oil-based stains, pretreat wood with BEHR Oil-Based Pre-Stain Wood Conditioner.

### APPLICATION (The following steps are recommended for best results.)

- Stir thoroughly before using. Do not shake or thin.
- Use a nylon or nylon/polyester brush or a saturated clean cloth and apply liberally to all areas of the wood surface including edges.
- Allow to penetrate between 5-10 minutes, and then wipe off any noticeable excess with a clean, dry cloth.
- Apply BEHR Water-Based Wood Stain or BEHR Water-Based Stain & Poly In One. Follow all label instructions.
- Allow Pre-Stain to dry for up to 20 minutes before applying Wood Stain.
- Sand lightly prior to staining to remove grain raise.

### DRY TIME

- Dries in 20 minutes.

### DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service

### LIMITED WARRANTY

- Visit [behr.com/warranty](http://behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

† **WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

⚠ **WARNING** Cancer and Reproductive Harm –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**CAUTION IRRITANT CONTAINS: ISOTHIAZOLONE. MAY CAUSE AN ALLERGIC SKIN REACTION AND EYE, SKIN, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.**

**PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. (C.O.V.) <275 g/L • REV. 7/19