



Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name Heavy-Duty Baseboard Stripper
Product code ZUBASE18
Date of issue 10/07/09 **Supersedes**

Emergency Telephone Numbers

For MSDS Information:
 Compliance Services 404-352-1680

For Medical Emergency
 (877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
 CHEMTREC: (800) 424-9300 - All Calls Recorded
 In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

DANGER !

CAUSES EYE BURNS. CAUSES SKIN IRRITATION. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN.
 CONTENTS UNDER PRESSURE.

*Hazard Determination System (HDS): Health, Flammability, Reactivity



NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

- Eyes** Causes eye burns. Direct contact with the eyes can cause irreversible damage, including blindness.
- Skin** Causes skin irritation. Harmful if absorbed through the skin. Prolonged exposure may result in skin burns and ulcerations. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.
- Inhalation** Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.
- Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Repeated or prolonged exposure to spray or mist may produce respiratory tract irritation, leading to frequent attacks of bronchial infection. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Contains material which may cause damage to the following organs: blood, kidneys, lungs, the reproductive system, liver, central nervous system (CNS).

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	10 - 20
MONOETHANOLAMINE; 2-aminoethanol; MEA	141-43-5	5 - 15
ETHYLENE GLYCOL; 1,2-ethandiol; glycol; ethylene dihydrate	107-21-1	1 - 10
HYDROCARBON PROPELLANT; blend of propane & isobutane	75-28-5; 74-98-6	1 - 10

Section 4. First Aid Measures

- Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
- Skin Contact** Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Get medical attention if irritation develops.
- Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point Closed cup: >93.33°C (>200°F)

Flammable Limits Not available.

Flammability Non-flammable. (CSMA Method)

Fire hazard CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Fire-Fighting Procedures Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash contaminated clothing before reusing. Wash thoroughly after handling.

Storage CONTENTS UNDER PRESSURE. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Product name

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve

MONOETHANOLAMINE; 2-aminoethanol; MEA

HYDROCARBON PROPELLANT; blend of propane & isobutane

ETHYLENE GLYCOL; 1,2-ethandiol; glycol; ethylene dihydrat

Exposure limits

ACGIH TLV (United States).

TWA: 20 ppm 8 hour(s). Form:

OSHA PEL (United States). Skin

TWA: 50 ppm 8 hour(s). Form:

OSHA PEL / ACGIH TLV (United States).

TWA: 3 ppm 8 hour(s).

OSHA /ACGIH (United States).

STEL: 6 ppm 15 minute(s).

ACGIH TLV / OSHA PEL (United States). Notes: Propane

TWA: 1000 ppm 8 hour(s).

ACGIH TLV (United States).

TWA: 50 ppm 8 hour(s).

Personal Protective Equipment (PPE)

Eyes Splash goggles.

Body Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.



Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.]

pH Not determined.

Boiling Point 98.3°C (208.9°F)

Specific Gravity 0.996

Solubility Easily soluble in the following materials: cold water and hot water.

Color Clear. Colorless.

Odor Solvent. [Slight]

Vapor Pressure Not determined.

Vapor Density Not determined.

Evaporation Rate <1 (Water = 1)

VOC (Consumer) 331 (g/l). 2.77 lbs/gal (33.4%)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂), oxides of nitrogen

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethylene Glycol Monobutyl Ether	LD50 Dermal	Rabbit	680 mg/kg	-
	LD50 Oral	Rat	1746 mg/kg	-
	LC50 Inhalation Vapor	Rat	450 ppm	4 hours
Monoethanolamine	LD50 Dermal	Rabbit	>1000 mg/kg	-
	LD50 Oral	Rat	1720 mg/kg	-
Ethylene Glycol	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	4000 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Consumer commodity ORM-D			
TDG Classification					
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

Ethylene Glycol Monobutyl Ether
Ethylene Glycol

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: Ethylene Glycol (RQ 5000 lbs)

Clean Air Act (CAA) 112 regulated toxic substances: Ethylene Glycol

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Canada**WHMIS (Canada)**

Class A: Compressed gas.
Class D-2B: Material causing other toxic effects (Toxic).

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.