



# WD-40 SPECIALIST® GEL LUBE

## PRODUCT DESCRIPTION

WD-40 Specialist Gel Lube No-Drip Formula offers 12x longer-lasting lubrication when compared to WD-40® Multi-Use Product.\* It has been designed for superior protection that resists water and displaces moisture to prevent rust for up to one year.\*\* This gel goes on thick and stays where you spray, making it ideal for use on vertical surfaces and offers non-fling for moving parts such as gears, bearings, cables, chains, rollers and more. Once applied withstands temperature ranges from -100°F to 500°F. Safe on multiple surfaces including metals, plastic and rubber.

## PACKAGING



## APPLICATIONS

- Chains
- Cables
- Gears
- Rollers
- Bearings
- Vertical Surfaces
- Moving Parts

## FEATURES & BENEFITS

- No Drip
- No Mess
- Unique, Thick Gel Lubricant
- 12x Longer-Lasting Lubrication\*
- Prevents rust for up to 1 year\*\*
- 50-state VOC Compliant
- Effective in a temperature Ranges from -100°F to 500°F

## PHYSICAL & CHEMICAL PROPERTIES

<b>BOILING POINT (INITIAL):</b>	221-271°C (430-520°F)	<b>DENSITY:</b>	0.89g/mL
<b>SOLUBILITY IN WATER:</b>	Insoluble	<b>pH:</b>	Not Applicable
<b>VAPOR PRESSURE:</b>	Not established	<b>VAPOR DENSITY:</b>	>1
<b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b>	Not established	<b>VOC:</b>	24.5%
<b>FLASHPOINT:</b>	>69°C (-156°F)(CC ASTM D3828)	<b>APPEARANCE/ODOR:</b>	Light amber liquid with a mild petroleum odor.
		<b>FLAMMABLE LIMITS:</b>	LEL: 0.6% UEL: 8.0%

## PERFORMANCE RESULTS

### 4 BALL WEAR (ASTM D4172)

This test measures the wear protection of a fluid on a metal surface. A steel ball is pressed with force against three stationary steel balls and is rotated at 1200 rpm for 60 minutes. WD-40 Specialist® Gel Lube lives up to its name as it lubricates and protects the steel ball.

<b>WD-40 SPECIALIST® GEL LUBE</b>	.39 mm
<b>WD-40® MULTI-USE PRODUCT</b>	.60 mm

RESULTS SHOW DEPTH OF SCAR IN MILLIMETERS. LOWER IS BETTER.

## DIRECTIONS

SHAKE CAN WELL (20-25 Seconds) before EACH spray. Flip straw up for STREAM or down for SPRAY. Make sure there is a 4-6-inch distance between actuator tip and the surface to be sprayed. Apply an even coat.

\*Compared to WD-40® Multi-Use Product using independent lab test ASTM D-5620A.

\*\*Independent tests conducted in salt spray and humidity chamber. Results may vary depending on extreme conditions.



# WD-40 SPECIALIST<sup>®</sup> GEL LUBE

## PACKAGING SPECIFICATIONS

ORDER#	CASE# / GTIN#	ITEM# / UPC#	DESCRIPTION	INDIVIDUAL UNIT					CASE PACK					PALLET						
				APPROX WT (OZ)	DIMENSIONS (IN)			CUBE	CASE PACK	APPROX WT (LBS)	DIMENSIONS (IN)			CUBE	APPROX WT (LBS)	CASES/LAYER	LAYERS	TOTAL QTY	APPROX HT (IN)	CUBE
				WIDTH	DEPTH	HEIGHT				WIDTH	DEPTH	HEIGHT								
300103	1 00 79567 30010 3	0 79567 30010 6	10oz Gel Lube	1.04	2.598	2.598	8.66	0.033	6	6.60	5.56	8.12	9.25	0.24	1330	39	5	195	48.0	56.94

## STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

## DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate containers.

## SPECIAL USE WARNINGS

**CONTENTS ARE EXTREMELY FLAMMABLE:** Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. **ELECTRICITY CAN BURN A HOLE IN THE CAN AND CAUSE CONTENTS TO BURST INTO FLAMES.** To avoid serious burn injury, do not let **THE CAN** touch battery terminals, electrical connections on motors or appliances or any other source of electricity. **CONTENTS UNDER PRESSURE:** Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat or store above 120°F. Avoid eye contact. Avoid prolonged or repeated contact with skin and clothing. Avoid breathing vapors or spray mists. Use in well ventilated area. Wash thoroughly with soap and water after use. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:** CONTAINS PETROLEUM DISTILLATES AND PROPANE PROPELLANT

**Ingestion (Swallowed):** Do not induce vomiting unless directed to do so by medical personnel. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water for 15 minutes. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation persists, get medical attention.

**Inhalation (Breathing):** If irritation develops, discontinue use and move to fresh air. Get medical attention if irritation or other symptoms persist.

## REGULATORY INFORMATION

**U.S. Federal Regulations: CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA TITLE III: Hazard Category For Section 311/312:** Acute Health, Fire Hazard, Sudden Release of Pressure; **Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None; Section 302 Extremely Hazardous Substances (TPQ): None; **EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory; **Canadian WHMIS Classification:** Class B-5 (Flammable Aerosol), Class D-2-A (Very toxic material causing other chronic effects)

