



Performance Data Sheet

Refrigerator Water Filter Models: FMA-1, FMG-2, FMG-3, FML-1, FML-2, FMM-1, FMM-2, FMS-1, FMS-2, FMS-4, FMW-2, FMW-4

This system has been tested according to NSF/ANSI Standard 42, 53, 372, 401, P473 and CSA B483.1 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42, 53, 372, 401, P473 and CSA B483.1.

Contaminant	% of reduction	Influent Concentration	Max Allowable
CHLORINE	>97%	2.0 mg/L	1.0 mg/L
ALACHLOR**	>98%	0.050	0.001
Asbestos†	99.98%	189 MFL	99%
ATRAZINE**	>97%	0.100	0.003
BENZENE**	>99%	0.081	0.001
BISPHENOL†	99.1%	2.058 mg/L	<0.300mg/L
BROMODICHLOROMETHANE (TTHM)**	>99.8%	0.300	0.015
BROMOFORM (TTHM)**	>99.8%	0.300	0.015
CARBOFURAN (Furadan)**	>99%	0.19	0.001
CHLORO BENZENE (Monochlorobenzene)**	>99%	0.077	0.001
CHLOROPICRIN**	99%	0.015	0.0002
CHLOROFORM (TTHM)* (surrogate chemical)†	>99.8%	0.300	0.015
2, 4-D**	98%	0.110	0.0017
CYST (Giardi, Cryptosporidium; Entamoeba, Toxoplasma)†	>99.95%	MINIMUM 50,000/L	99.95% REDUCTION REQUIREMENT
Cryptosporidium (see CYST)†	>99.95%	MINIMUM 50,000/L	99.95% REDUCTION REQUIREMENT
DBCP (see Dibromochloropropane)**	>99%	0.052	0.00002
1,2-DCA (see 1,2-DICHLOROETHANE)**	95%	0.088	0.0048
1,1-DCE (see 1,1-DICHLOROETHYLENE)**	>99%	0.083	0.001
DIBROMOCHLOROMETHANE (TTHM; Chlorodibromomethane)**	>99.8%	0.300	0.015
DIBROMOCHLOROPROPANE (DBCP)**	>99%	0.052	0.00002
o-DICHLOROBENZENE (1,2 Dichlorobenzene)**	>99%	0.080	0.001
p-DICHLOROBENZENE (para-Dichlorobenzene)	>98%	0.040	0.001
1,2-DICHLOROETHANE (1,2-DCA)**	95%	0.088	0.0048
1,1-DICHLOROETHYLENE (1,1-DCE)**	>99%	0.083	0.001
CIS-1,2-DICHLOROETHYLENE**	>99%	0.170	0.0005
TRANS-1,2-DICHLOROETHYLENE**	>99%	0.086	0.001
1,2-DICHLOROPROPANE (Propylene Dichloride)**	>99%	0.080	0.001
CIS-1,3-DICHLOROPROPYLENE**	>99%	0.079	0.001
DINOSEB†	99%	0.170	0.0002
EDB (see ETHYLENE DIBROMIDE)**	>99%	0.044	0.00002
ENDRIN	99%	0.053	0.00059
Entamoeba (see CYSTS)†	99.95%	MINIMUM 50,000/L	99.95% REDUCTION REQUIREMENT
ESTRONE†	96.9%	0.1388 mg/L	<0.020 mg/L
ETHYLBENZENE**	>99%	0.088	0.001
ETHYLENE DIBROMIDE (EDB)**	>99%	0.044	0.00002
Furadan (see CARBOFURAN)**	>99%	0.19	0.001
Giardia Lambdia (see CYST)†	>99.95%	MINIMUM 50,000/L	99.95% REDUCTION REQUIREMENT
HALOACETONITRILES (HAN)**			
BROMOCHLOROACETONITRILE†	98%	0.022	0.0005
DIBROMOACETONITRILE†	98%	0.024	0.0006
HALOACETONITRILES (HAN)**			
DICHLOROACETONITRILE†	98%	0.0096	0.0002
TRICHLOROACETONITRILE†	98%	0.015	0.0003
HALOKETONES (HK):**			
1,1-DICHLORO-2-PROPANONE†	99%	0.0072	0.0001
1,1,1-TRICHLORO-2-PROPANONE†	96%	0.0082	0.0003
HEPTACHLOR**	>99%	0.25	0.00001
HEPTACHLOR EPOXIDE**	98%	0.0107	0.0002
HEXACHLOROBUTADIENE (Perchlorobutadiene)**	>98%	0.044	0.001
HEXACHLOROCYCLOPENTADIENE**	>99%	0.060	0.000002
IBUPROFEN†	96.7%	0.432 mg/L	<0.060 mg/L
LEAD (pH 6.5)†	>99.3%	0.15 +/- 10%	0.010
LEAD (pH 8.5)†	>99.3%	0.15 +/- 10%	0.010
LINDANE**	>99%	0.055	0.00001
METHOXYCHLOR**	>99%	0.050	0.00001
Methylbenzene (see TOLUENE)**	>99%	0.078	0.001
Mercury (pH 6.5)†	74.9%	0.0059	0.002
Mercury (pH 8.5)†	97.8%	0.0061	0.002
Monochlorobenzene (see CHLORO BENZENE)**	>99%	0.077	0.001
NAPROXEN†	95.3%	0.130 mg/L	<0.020 mg/L
NONYLPHENOL†	97.1%	2.058 mg/L	<0.200 mg/L
PCE (see Tetrachloroethylene)†	>96%	0.014	0.005
PENTACHLOROPHENOL**	>99%	0.096	0.001
Perchlorobutadiene (see HEXACHLOROBUTADIENE)**	>98%	0.044	0.001
PFOA†	98.0%	0.0005 mg/L	<0.00007 mg/L
PFOS†	98.0%	0.001 mg/L	<0.00007 mg/L
Phenitoin†	94.7%	0.2173 mg/L	<0.030 mg/L
Propylene Dichloride (see 1,2-DICHLOROPROPANE)**	>99%	0.080	0.001
SIMAZINE**	>97%	0.120	0.004
STYRENE (Vinylbenzene)**	>99%	0.150	0.0005
1,1,1-TCA (see 1,1,1-TRICHLOROETHANE)**	95%	0.084	0.0046
1,2,4-Trichlorobenzene	>99%	0.215	0.07
TCE (see TRICHLOROETHYLENE)**	>99%	0.180	0.0010
1,1,2,2-TETRACHLOROETHANE**	>99%	0.081	0.001
TOLUENE (Methylbenzene)**	>99%	0.078	0.001
TOXAPHENE†	>92.9%	0.015 +/- 10%	0.003
2,4,5-TP (Silvex)**	99%	0.270	0.0016
Toxoplasma (see CYST)†	>99.95%	MINIMUM 50,000/L	99.95% REDUCTION REQUIREMENT
TRIBROMOACETIC ACID**		0.042	0.001
1,1,1-TRICHLOROETHANE (1,1,1-TCA)**	95%	0.084	0.0046
1,1,2-TRICHLOROETHANE**	>99%	0.150	0.0005
TRICHLOROETHYLENE (TCE)**	>99%	0.180	0.0010
TRIHALOMETHANES (TTHM) (Chloroform; Bromoform; Bromodichloromethane; Dibromochloromethane)†	>99.8%	0.300	0.015
Unsym-Trichlorobenzene (see 1,2,4-TRICHLOROETHANE)**	>99%	0.160	0.0005
Vinylbenzene (see STYRENE)**	>99%	0.150	0.0005
XYLENES (TOTAL)**	>99%	0.070	0.001

*Not tested or certified by NSF International.

FILTER SPECIFICATIONS

Flow Rate:	0.5 gpm / 1.89 lpm
Operating Temperature:	33 - 100°F (0.6°C - 38°C)
Operating Pressure:	30 psi (207 kPa) - 100 psi (689 kPa)
Capacity:	300 gallons (1,136 L) or six months



Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of Chlorine taste and odor, Endrin, 1,2,4-Trichlorobenzene, P-Dichlorobenzene. Refer to performance data sheet for complete list of claims.



Certified by IAPMO R&T against NSF/ANSI Standards 42, 53, 372, 401, P473 & CSA B483.1 for the reduction of Chlorine taste and odor, Lead, Cyst, VOC's, Mercury, Asbestos, Pharmaceuticals (such as Naproxen, Ibuprofen and Phenitoin), BPA, PFOA/PFOS. Refer to Performance Data Sheet for complete list of claims.

The compounds under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'.

Limited Warranty: This filter hereunder shall be free from material defects in material and workmanship for a period of one (1) year from the date of purchase. To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and installations. This filter unit must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Protect from freezing. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. The system conforms to NSF/ANSI 42, 53, 372, 401, P473 and CSA B483.1 for the specific performance claims as verified and substantiated by test data. Conforms to NSF/ANSI 53 for VOC reduction. See above for individual contaminants and reduction performance. Note: Testing was performed under standard laboratory conditions, actual performance may vary.

System to be used with municipal or well water sources treated and tested on regular basis to ensure bacteriological safe quality. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. Manufactured by Aquamor, LLC, Temecula, CA.