



# Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Gorilla Epoxy - Resin

**Synonyms:** Epoxy Resin

### Intended Use of the Product

Epoxy

### Name, Address, and Telephone of the Responsible Party

#### **Company**

The Gorilla Glue Company

2101 E. Kemper Road

Cincinnati, Ohio 45241

513-271-3300

[www.gorillatough.com](http://www.gorillatough.com)

### Emergency Telephone Number

**Emergency number** : 1-800-420-7186 (Prosar)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**



#### **Signal Word (GHS-US)**

: Warning

#### **Hazard Statements (GHS-US)**

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements (GHS-US)**

: P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.



## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Other Hazards** Not available

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Bisphenol A-epichlorohydrin polymer	(CAS No) 25068-38-6	>= 60	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
(3-(2,3-Epoxypropoxy)propyl)trimethoxysilane	(CAS No) 2530-83-8	>= 0.1	Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Exposure may produce an allergic reaction. Causes skin irritation. Causes serious eye irritation.

**Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin Contact:** Causes skin irritation. Exposure may produce an allergic reaction.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Not available

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** None known.

### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.



## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018  
Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store away from incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Amines.

**Specific End Use(s)** Epoxy

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.



## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Translucent, Clear
Odor	: Not available
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: > 93 °C Closed Cup (199.40 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.1 – 1.2
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** None known.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified



## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Symptoms/Injuries After Skin Contact:** Exposure may produce an allergic reaction.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
(3-(2,3-Epoxypropoxy)propyl)trimethoxysilane (2530-83-8)	
LD50 Oral Rat	8025 mg/kg
LD50 Dermal Rabbit	4250 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Toxic to aquatic life with long lasting effects.

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LOEC (acute)	1 mg/l Daphnia magna
NOEC chronic crustacea	0.3 mg/l Daphnia magna
(3-(2,3-Epoxypropoxy)propyl)trimethoxysilane (2530-83-8)	
LC50 Fish 1	55 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	710 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	350 mg/l Exposure time: 96 h - Species: Pseudokirchnerella subcapitata)

**Persistence and Degradability** Not available

**Bioaccumulative Potential** Not available

**Mobility in Soil** Not available

**Other Adverse Effects** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

This product qualifies for the marine pollutant exceptions set by DOT 171.4(c)(2), IMDG 2.10.2.7 and IATA SP A197 and is not subject to the regulations by ground, vessel or air.

**In Accordance with TDG** Not regulated for transport

This product meets the specifications set forth by Special Provision 99.





## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: REGULATORY INFORMATION


### US Federal Regulations

<b>Gorilla Epoxy - Resin</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard
<b>Bisphenol A-epichlorohydrin polymer (25068-38-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>(3-(2,3-Epoxypropoxy)propyl)trimethoxysilane (2530-83-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### US State Regulations

<b>Epichlorohydrin (106-89-8)</b>	
U.S. - California - Proposition 65 – Cancer & Reproductive harm - Male	California Prop 65: ⚠️WARNING: Cancer and Reproductive Harm- <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Canadian Regulations

<b>Gorilla Epoxy - Resin</b>	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
<b>Bisphenol A-epichlorohydrin polymer (25068-38-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>(3-(2,3-Epoxypropoxy)propyl)trimethoxysilane (2530-83-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 03/14/2018
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H402	Harmful to aquatic life



## Safety Data Sheet - Gorilla Epoxy - Resin

Date Revised: 03/14/2018

Date Issued: 10/08/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H411	Toxic to aquatic life with long lasting effects
------	---

### Party Responsible for the Preparation of This Document

The Gorilla Glue Company

+1 513-271-3300

*The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.*

North America GHS US 2012 & WHMIS 2 GG



# Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Name:** Gorilla Epoxy - Hardener

**Synonyms:** Epoxy Hardener

### Intended Use of the Product

Epoxy

### Name, Address, and Telephone of the Responsible Party

#### **Company**

The Gorilla Glue Company

2101 E. Kemper Road

Cincinnati, Ohio 45241

513-271-3300

[www.gorillatough.com](http://www.gorillatough.com)

### Emergency Telephone Number

**Emergency number** : 1-800-420-7186 (Prosar)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Acute Tox. 4 (Oral) H302

Acute Tox. 4 (Dermal) H312

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Repr. 2 H361

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**

:



GHS05



GHS07



GHS08

#### **Signal Word (GHS-US)**

: Danger

#### **Hazard Statements (GHS-US)**

: H302+H312 - Harmful if swallowed or in contact with skin.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H361 - Suspected of damaging fertility or the unborn child.

#### **Precautionary Statements (GHS-US)**

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove





## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a poison center or doctor.  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

Keep away from children and animals.

**Note:** *Gorilla Epoxy* contains isophorondiamine CAS No. 2855-13-2 which, according to Annex 1, Table 3.2.3 of CLP carries the H314: corrosive classification. Product level dermal corrosivity testing for Gorilla Epoxy confirms the product is classified as a skin irritant rather than corrosive. Positive results in a valid and accepted skin corrosion test (Corrositex test) classifies the mixture as Non-corrosive utilizing multiple replicate samples indicating highly reproducible results. As a result, the health hazard and transport classification have been changed to reflect the Epoxy results: UN Non-Corrosive and not a GHS Category 1.

### Unknown Acute Toxicity (GHS-US)

60 - 100 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

60 - 100 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

60 - 100 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Isophorone diamine	(CAS No) 2855-13-2	7 - 13	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Bisphenol A	(CAS No) 80-05-7	0.1 - 1	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Diethylenetriamine	(CAS No) 111-40-0	0.1 - 1	Not Available
Tetraethylenepentamine	(CAS No) 112-57-2	0.1 - 1	Not Available

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Using proper respiratory protection, immediately move the exposed person to fresh air. Seek medical attention immediately.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.



## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021  
Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. Exposure may produce an allergic reaction. Causes skin irritation. May cause respiratory irritation.

**Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

**Skin Contact:** Exposure may produce an allergic reaction. Harmful in contact with skin. Causes skin irritation.

**Eye Contact:** Causes serious eye damage.

**Ingestion:** Harmful if swallowed.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### **Extinguishing Media**

**Suitable Extinguishing Media:** Carbon dioxide, dry powder, and foam. In cases of large scale fires, alcohol-resistant foams are preferred.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** None known.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Do not get in eyes, on skin, or on clothing.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### **Environmental Precautions**

Prevent entry to sewers and public waters.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.



## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store away from incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Specific End Use(s)** Epoxy

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Bisphenol A (80-05-7)		
Yukon	OEL Ceiling (mg/m <sup>3</sup> )	2.8 mg/m <sup>3</sup>
Yukon	OEL Ceiling (ppm)	0.05 ppm
Diethylenetriamine (111-40-0)		
United States	ACGIH TLV (absorbed through skin)	4.2 mg/m <sup>3</sup> , 8 hours TWA
United States	ACGIH TLV (absorbed through skin)	1 ppm, 8 hours TWA

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** When effective engineering controls are not feasible, appropriate respirators shall be used. Personal Protective Equipment must be selected by trained personnel, taking into account the type of hazardous materials it should protect from, the nature of the work, the expected exposure, and the facial characteristics of the wearers; proper fit is of paramount importance. Ensure the respiratory protection program meets the requirements of OSHA 29 CFR 1910.134.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Amber
Odor	: Not available
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: Not available



## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: > 93 °C Closed Cup (199.40 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.12
Specific Gravity	: 1.12
Solubility	: Insoluble in water.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** None known.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Oral: Harmful if swallowed. ATE (oral): 1,812 mg/kg

**Skin Corrosion/Irritation:** Causes skin irritation.

*Gorilla Epoxy* contains isophorondiamine CAS No. 2855-13-2 which, according to Annex 1, Table 3.2.3 of CLP carries the H314: corrosive classification. Product level dermal corrosivity testing for *Gorilla Epoxy* confirms the product is classified as a skin irritant rather than corrosive. Positive results in a valid and accepted skin corrosion test (Corrositex test) classifies the mixture as Non-corrosive utilizing multiple replicate samples indicating highly reproducible results. As a result, the health hazard and transport classification have been changed to reflect the Epoxy results: UN Non-Corrosive and not a GHS Category 1.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.



## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Symptoms/Injuries After Skin Contact:** Exposure may produce an allergic reaction. Harmful in contact with skin. Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage.

**Symptoms/Injuries After Ingestion:** Harmful if swallowed.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child.

### Information on Toxicological Effects - Ingredient(s)

#### **LD50 and LC50 Data:**

<b>Isophorone diamine (2855-13-2)</b>	
LD50 Oral Rat	1030 mg/kg
<b>Bisphenol A (80-05-7)</b>	
LD50 Oral Rat	2000 to 5000 mg/kg
LD50 Dermal Rabbit	6400 mg/kg
LC50 Inhalation Rat	> 170 mg/m3

## SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** Not classified

<b>Isophorone diamine (2855-13-2)</b>	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
<b>Bisphenol A (80-05-7)</b>	
LC50 Fish 1	3.6 (3.6 - 5.4) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	10.2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	4.0 - 5.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)

**Persistence and Degradability** Not available

### **Bioaccumulative Potential**

<b>Isophorone diamine (2855-13-2)</b>	
Log Pow	0.79 (at 23 °C)
<b>Bisphenol A (80-05-7)</b>	
BCF Fish 1	5.1 - 13.8
Log Pow	2.2

**Mobility in Soil** Not available

### **Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Sewage Disposal Recommendations:** Do not dispose of waste into sewer.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations





## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Gorilla Epoxy - Hardener</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard
<b>Isophorone diamine (2855-13-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Bisphenol A (80-05-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

### US State Regulations

<b>Bisphenol A (80-05-7)</b>	
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	California Prop 65: ⚠️WARNING: Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
<b>Isophorone diamine (2855-13-2)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>Bisphenol A (80-05-7)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

### Canadian Regulations

<b>Gorilla Epoxy - Hardener</b>	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Isophorone diamine (2855-13-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
<b>Bisphenol A (80-05-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.





## Safety Data Sheet - Gorilla Epoxy - Hardener

Date Revised: 06/23/2021

Date Issued: 06/12/2015

Version: 1.4

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 06/23/2021

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

### Party Responsible for the Preparation of This Document

The Gorilla Glue Company

+1 513-271-3300

*The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.*

North America GHS US 2012 & WHMIS 2 GG