

# SHC Mini-Tank Electric Water Heater

## Technical Data



Certified to ANSI/UL Std. 174  
Conforms to CAN/CSA Std. 22.2 No. 110

ISO 9001  
CERTIFIED

Model	SHC 2.5	SHC 4
Item number	233219	234046
Phase - 60/50 Hz	single	single
Voltage	120 v	120 v
Wattage	1300 w	1300 w
Amperage	11.3 A	11.3 A
Nominal water volume	2.65 gal / 10 l	4.0 gal / 15 l
Weight empty	15.9 lb / 7.2 kg	19.8 lb / 9.0 kg
Height	17 <sup>11</sup> / <sub>16</sub> " / 475 mm	19 <sup>3</sup> / <sub>4</sub> " / 501 mm
Width	11" / 280 mm	12 <sup>5</sup> / <sub>8</sub> " / 320 mm
Depth	10 <sup>5</sup> / <sub>8</sub> " / 270 mm	12 <sup>1</sup> / <sub>2</sub> " / 318 mm
Maximum operating pressure	150 psi / 10 bar	150 psi / 10 bar
Maximum adjustable temperature	140°F / 60°C	140°F / 60°C
Recovery time	18 minutes	27 minutes
Standby heat loss @ 131°F / 55°C	0.37 kWh / day	0.39 kWh / day
Water connections	black steel 1/2" NPT	black steel 1/2" NPT