



Luxury Vinyl Tile

SPECIFICATIONS

Classification:	ASTM F1700 Class III Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	20 mil (0.5 mm)
Wear Layer Coating:	Ceramic-Bead
Edge Treatment:	Square (SE)
Emboss:	Ribbed
Colors:	20
Installation Method:	Glue Down
Warranty:	30 Year Residential / 15 Year Commercial

SIZES 6"x 36" (15.24 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF \geq 0.45 watts/cm ² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^{MC}
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Materials:	No Heavy Metals; Non-Toluene Ink System	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
LEED Scoreboard:	LEED 2009 MRc2 Construction Waste Management MRc4 Recycled Content MRc5 Regional Materials IEQ 4.1 Low-Emitting Adhesives IEQ 4.3 Low-Emitting Materials Flooring	LEED v4 MRc2 Building Product Disclosure and Optimization – Environmental Product Declarations MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials MRc5 Construction and Demolition Waste Management IEQc2 Low-Emitting Materials
Third-party Certification:	NSF/ANSI-332 Gold	
Manufacturing:	ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	
Packaging:	Packaged in corrugated cardboard	



- For more information visit www.luxflooring.com.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.