

BEHR WEATHERSTRONG™ ADVANCED HYBRID SEALANT

Ideal for: Baseboards, Window Frames, Door Frames, Trim, Molding, Siding, Stairs, Skirtings, Window Sills, Corner Joints, Pipes and Vents

PRODUCT INFORMATION

- Use for sealing connection joints and for transitional seal between building materials.
- All-weather application; wet surface/in-rain application.
- Strong bond to difficult substrates.
- Weatherproof & waterproof.
- Paint-ready (brush/roll) in 1 hour; spray paint immediately
- Consistent flow/no air pops.
- Won't shine through or discolor paint.
- Watertight seal.
- Easy gunning and smooth tooling.
- Each 9.5 fl oz cartridge will cover 55 linear feet with a 3/16" bead.
- Reduced dirt pick-up.
- Easy water clean-up.
- Non-yellowing.
- Asphalt-compatible.
- For exterior/interior use.

DIRECTION FOR USE

All surfaces must be clean and free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, rust, loose material and all other foreign substances. Using proper safety precautions, cut the tip at a 45° angle to desired bead size. Apply with conventional hand or air-powered caulking equipment in a continuous operation with adequate pressure to fill the joint to the proper width and depth (do not overfill the joint). Gun sealant into void to provide a solid fill. Use backer rod for gaps larger than 1/2" x 1/2". Smooth the sealant before the skin forms using a dry tool with a concave profile. Do not use water or soapy water for this operation. Allow 1 hour for sealant skin to form before painting with a brush/roller, or spray paint immediately. Excess dried sealant must be cut or scraped away. Reseal cartridge for storage and reuse. Clean tools, equipment and excess uncured material with mineral spirits, solvent or cleaning wipes.

 **WARNING** Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION IRRITANT MAY IRRITATE EYES, SKIN, AND RESPIRATORY TRACT. CONTAINS LIMESTONE, N-[3-(TRIMETHOXSILYL) PROPYL]-1, 2-ETHANEDIAMINE, TIN, DIBUTYLBIS(2,4-PENTANEDIONATO-O,O')-, (OC-6-11)-, CRYSTALLINE SILICA AND TITANIUM DIOXIDE. METHANOL MAY FORM DURING CURING. Do not breathe fumes. Do not get in eyes, on skin or on clothing. Do not swallow. Handle with care. Use only in well-ventilated area or wear a respirator. Wear protective clothing including safety glasses and gloves. Wash thoroughly after handling. **FIRST AID:** If in eyes or on skin, rinse with water for at least 15 minutes. If on clothes, remove clothing. If inhaled, move person to fresh air. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

