

**FHPC082AB1**

**Available Colors : White**

**Version : 10/19**

**Portable Air Conditioner**

**8,000 BTU Portable Room Air Conditioner**



## Product Specifications

### Functions

|                            |     |
|----------------------------|-----|
| 24-Hour On/Off Timer       | Yes |
| Auto Fan                   | Yes |
| Auto Restart               | Yes |
| Continuous Drain Operation | Yes |
| Dry Mode                   | Yes |
| Low Voltage Start-up       | Yes |
| Sleep Mode                 | Yes |

### AC

|                        |                     |
|------------------------|---------------------|
| Air CFM (High)         | 223                 |
| Air CFM (Low)          | 194                 |
| Air CFM (Med)          | 205                 |
| Air Direction Control  | Swing               |
| Air Discharge          | Top of Unit         |
| Exhaust Hose           | Yes                 |
| Fan Speeds - Cool      | 3                   |
| Fan Speeds - Fan       | 3                   |
| Filter Access          | Rear Top of Unit    |
| Filter Check Indicator | Yes                 |
| Filter Type            | Anti-Bacterial Mesh |
| Motor RPM (High)       | 680                 |
| Motor RPM (Low)        | 560                 |
| Motor RPM (Med)        | 610                 |
| Noise Level dB (High)  | 52                  |
| Noise Level dB (Low)   | 49                  |
| Noise Level dB (Med)   | 51                  |
| Window Slider Kit      | Yes                 |

### Electrical Specifications

|                   |            |
|-------------------|------------|
| Amps (Cool)       | 8.3        |
| Plug Type         | LCDI 5-15P |
| Power Cord Length | 6'         |
| Voltage Rating    | 115        |
| Watts (Cool)      | 930        |

### Performance

|                                   |           |
|-----------------------------------|-----------|
| BTU (Cool)                        | 8000      |
| Combined Energy Efficiency Ratio  | 6.3       |
| Cool Area (Sq. Ft.)               | Up to 350 |
| DOE Rating                        | Yes       |
| Dehumidification - Pints per Day  | 60        |
| Dehumidification - Pints per Hour | 2.5       |
| Energy Efficiency Ratio           | 9.1       |

### Certifications & Approvals

|            |     |
|------------|-----|
| ETL Listed | Yes |
| ISTA 6     | Yes |

### Controls

|                |            |
|----------------|------------|
| Control Type   | Electronic |
| Remote Control | Yes        |

### Dimensions

|        |       |
|--------|-------|
| Depth  | 13.87 |
| Height | 27.9  |
| Width  | 16.7  |

### Accessories

|                    |                   |
|--------------------|-------------------|
| Included Accessory | Window Slider Kit |
|--------------------|-------------------|

### General Specifications

|                         |           |
|-------------------------|-----------|
| Prop 65 Label           | Yes       |
| Refrigerant Type        | R410a     |
| Stack Height            | 4         |
| 40 HQ Stuffing Quantity | 419       |
| Warranty - Labor        | 1 yr Full |
| Warranty - Parts        | 1 yr Full |

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com](http://frigidaire.com) / [frigidaire.ca](http://frigidaire.ca). Specifications subject to change. Accessories information available on the web at [frigidaire.com](http://frigidaire.com) / [frigidaire.ca](http://frigidaire.ca)