

DuPont™ Tyvek® Roof Protector™

Strong and Lightweight Synthetic Roofing Underlayment



FEATURES/BENEFITS

Description

DuPont™ Tyvek® Roof Protector™ – with its four-layer construction providing excellent strength, grip and water-resistance – is the ideal engineered synthetic underlayment for steep slope roofing applications under asphalt shingles or metal panel roof materials, brought to you by the trusted name in total building envelope solutions.

Tyvek® Roof Protector™ is tough and tear-resistant, laying flat and staying flat for easier installation and better coverage per roll. Its high strength to weight ratio, slip-resistant surface and lightweight durability offers peace of mind to professional builders and homeowners alike.

Available Sizes

Tyvek® Roof Protector™ is available in 10 square rolls: 42" x 286'/1.1m x 87.2m (93.0m²)

Ease of Use

Tyvek® Roof Protector™ preserves the roof deck during installation, minimizing tearing at fastener points as a result of its excellent strength and deck grip. Tyvek® Roof Protector™ comes with a number of features and benefits:

- Lightweight material lays flat, stays flat and repositions with ease
- Large roll provides maximum coverage for quick installation
- Features 2" chalk mark guide lines for easier shingle alignment
- Acts as an effective secondary moisture barrier
- Withstands up to 90 days of UV exposure and comes with a 20-year limited warranty
- Low flame spread with a class "A" fire rating per ASTM E108
- Florida Building Code approved and meets AC188 (Intertek CCRR-1062), ASTM D226 Types 1 & II, CAN/CSA A123.3, CAN/CSA A220.1

PROPERTIES

DuPont™ Tyvek® Roof Protector™ exhibits physical properties as indicated in Tables 1 and 2 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-800-488-9835 when additional guidance is required for writing specifications that include this product.

TABLE 1: Physical Properties for Tyvek® Roof Protector™

Test Method	Property	Typical Value	Units
ASTM D1777	Nominal Thickness (mm)	0.254	mm
ASTM D1777	Nominal Thickness (mils)	10	mils
ASTM D4869	Liquid water transmission	Pass	–
ASTM E96	Permeability (MVTR)	< 0.05	Perms
ASTM D751	Tensile strength (MD / CD)	MD: 102 CD: 90	lbf
ASTM D751	Elongation (MD / CD)	MD: 17 CD: 18	%
ASTM D4533	Tear strength (MD / CD)	MD: 25 CD: 40	lbf
ASTM E108	Fire rating	Class A	–
ICC-ES AC188	UV exposure	90	–
Thermal Cycling	Temperature range	-40–240 (-40–115)	°F (°C)
ICC-ES AC188, per Intertek CCR-1087 ASTM D226	Code approvals	Pass	–

TABLE 2: Specifications for Tyvek® Roof Protector™

Specifications	Typical Value	Units
Length per roll	286	ft
Width per roll	42	in
Weight per roll	20	lb
Roll size	42"x286' (10 square)	square
Rolls per pallet	49	–
Pallet weight	1,095	lb
Weight per square	2.04	lb
Warranty	20	years



**For more information visit us at
tyvek.com
or call 1-800-448-9835**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.