



# GREAT STUFF™ BIG GAP FILLER INSULATING FOAM SEALANT WITH QUICK STOP™ STRAW TECHNOLOGY

## CRACK DOWN ON ENERGY LOSS. IMPROVE COMFORT.



The average U.S. home has a half mile of gaps and cracks<sup>1</sup> where air and moisture can enter. Air sealing and insulating projects around the home can save homeowners up to 30% on home energy costs, according to the Residential Energy Services Network (RESNET).

Seal out energy loss and improve comfort with GREAT STUFF™ Big Gap Filler Insulating Foam Sealant with QUICK STOP™ Straw Technology.<sup>2</sup>

### Reduces air leaks and energy costs.

GREAT STUFF™ Big Gap Filler Insulating Foam Sealant is a ready-to-use, expanding polyurethane insulating foam sealant that fills, seals and insulates gaps up to 3 inches. This specially formulated sealant:

- fills, seals and insulates gaps up to 3 inches
- expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal
- helps improve energy efficiency by forming an airtight seal in gaps and cracks
- is a simple way to minimize unwanted air flow and reduce moisture condensation



GREAT STUFF™ Big Gap Filler is a polyurethane foam gap/crack filler for use all around the home.

<sup>1</sup>Source: www.energystar.gov

<sup>2</sup>Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

<sup>3</sup>Skin of cured foam can discolor if exposed to natural light. Paint or coat foam for best results.

<sup>4</sup>70°F ± 5°F and 50 ± 5% RH, 1 inch bead diameter, 6 inch length. Cure rate is dependant on temperature, humidity and size of foam bead.



## Now with NEW QUICK STOP™ Straw Technology

- Easy, stop-start product usage
- Less mess, less clean-up (saves time)
- Less wasted foam (increases efficiency)

### Features and benefits at a glance

- Fills, seals and insulates gaps up to 3 inches
- Ready-to-use (straw applicator)
- Forms a long-lasting weathertight seal to minimize drafts
- Forms airtight, water-resistant seal
- Interior/exterior use<sup>3</sup>
- Adheres to wood, metal, masonry, glass and most plastics
- Tack free in 5- 15 minutes<sup>4</sup>; Trims in one hour
- Cures rigid
- Paintable, stainable and sandable
- Cream colored foam
- All-direction dispensing
- UL Classified
- CCMC 13074-L

## Where to Use GREAT STUFF™ Big Gap Filler

Use GREAT STUFF™ Big Gap Filler Insulating Foam Sealant to seal gaps up to 3 inches to insulate around common areas of energy loss such as rim joist/sill plate, plumbing, HVAC, etc.



Electrical openings



Hard to reach corners



Sill plate



Pipe penetrations



Rim joist

### GREAT STUFF™ Big Gap Filler Insulating Foam Sealant is Cost Effective

- One 16 oz. can = up to 26 tubes of caulk\*

\*Calculated caulk equivalence based on 10.2 oz tubes of caulk.

## Greatness comes in many forms

Did you know that the average U.S. home has a 1/2 mile of gaps and cracks?\*\*\* Seal them with GREAT STUFF™ Insulating Foam Sealants.

Each GREAT STUFF™ Insulating Foam Sealant\* is specially formulated to seal gaps and cracks to block air, moisture and even pests. Our comprehensive line of ready-to-use sealants is a simple, inexpensive money-saving solution for any do-it-yourself homeowner.

- **GREAT STUFF™ Gaps & Cracks\*** — Foam sealant that expands to seal and insulate gaps up to one inch.
- **GREAT STUFF™ Window & Door\*** — Minimally expanding foam that seals between a window or door and its rough opening.
- **GREAT STUFF™ Fireblock\*** — Impedes spread of fire and smoke through service penetrations.\*\*\*
- **GREAT STUFF™ Big Gap Filler\*** — Foam sealant that expands to seal and insulate gaps up to three inches.
- **GREAT STUFF™ Pestblock\*** — Blocks pests out of the home by eliminating points of entry.



In the United States

**The Dow Chemical Company**  
**Dow Building Solutions**  
 200 Larkin Center  
 Midland, MI 48674

In Canada

**Dow Chemical Canada ULC**  
**Dow Building Solutions**  
 2400, 215 – 2 Street S.W.,  
 Calgary, Alberta T2P 1M4

For Technical Information:

**1-866-583-BLUE** (2583) (English)  
**1-800-363-6210** (French)

**dowgreatstuff.com**

**dowgreatstuff.ca**  
**dowbuildingsolutions.com**

For Sales Information:

**1-800-232-2436** (English)  
**1-800-565-1255** (French)

**NOTICE:** No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release The Dow Chemical Company of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

#### Dow Polyurethane Foam Insulation and Sealants

**CAUTION:** When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call Dow at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood-burning stoves, gas stoves and gas dryers, are properly vented to the outside. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

**GREAT STUFF™** Insulating Foam sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death. Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

\* Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

\*\* [www.energystar.gov](http://www.energystar.gov)

\*\*\* Intended for use in residential applications to maintain the continuity of an approved fire block material.

©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

Printed in the U.S.A.

Form No. 179-15218-0516 CDP  
 178-15114-0516 CDP