



Direct-To-Metal Interior/Exterior Semi-Gloss Paint

- Ideal for Metal Fences, Railings, Doors, Garage Doors and Other Properly Prepared Surfaces
- Excellent Adhesion
- Durable Hard Finish
- Corrosion & Rust Resistant
- Easy Water Clean-up

NO. 3200 White
NO. 3230 Deep Base
NO. 3220 Black



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
UL COM1GG
UL 2818



2 Coats Recommended
for Optimal Durability



Spread Rate:
350-400 Sq. Ft.



Dry Time:
1 Hr Dry to Touch
3 Hr Recoat



Clean-Up
Soap & Water

WHITE: READY TO USE OR ADD TINTING COLORANTS.

DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.

WHERE TO USE

Use on properly prepared and cleaned interior and exterior metal surfaces. Also suitable for properly prepared and primed new or previously painted drywall, wood, plaster, concrete, and masonry surfaces.

PREPARATION

(Proper surface preparation is required.) Remove dust, dirt, chalk, oil, grease, wax, polish, loose and peeling paint, and all other foreign substances. Remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces and repair imperfections. Bare metal must be coated the same day it is cleaned. Allow new stucco, plaster, and masonry to cure for 30 days before painting. All oil and alkyd surfaces should be primed prior to painting.

PRIME

- Self-priming on properly prepared metal surfaces. For optimal corrosion protection on ferrous metal surfaces, use a rust-inhibitive primer, such as BEHR Metal Primer No. 435.
- For stain-blocking or painting over woods with tannins, prime with a product such as BEHR Multi-Surface Stain-Blocking Primer & Sealer No. 436.
- For new concrete and masonry surfaces, prime with a product such as BEHR Multi-Surface Stain-Blocking Primer & Sealer No. 436.

***LIMITED WARRANTY** For one year from the date that the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.), Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date that the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.), Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warrant, negligence, strict liability, or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Paint Company Representative, call 1-800-854-0133.

APPLICATION

DO NOT THIN PRODUCT. Apply when air and surface temperatures are between 50-90°F. Do not use for exterior when precipitation is expected within 24 hours after project completion. Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. Use a high quality 1/4-3/8" nap roller cover, nylon/polyester brush or airless sprayer (.013-.017" spray tip, 60 mesh filter). Certain colors may require additional coats for complete hide. Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time. After 4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Do not use on floors.

DISPOSAL

For disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

For additional information, please refer to the Technical Data Sheet (TDS).

Visit behr.com for painting tips, expert project advice and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes. Do not breathe dusts, vapor, or spray mist. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.



©2024 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
VOC < 50 g/L • REV. 1/24