

70-198  
70-198-9

# Silicone Moisture Barrier Underlayment

## EASY FLOORING INSTALLATIONS

Recommended for staple and nail down installations of solid and engineered wood floors and floating LVT applications

## MOISTURE BARRIER

Reduces vapor flow without trapping moisture

## LESS MESS

Helps reduce dust and noise levels, clean to use

## FEATURES & BENEFITS

- Provides moisture barrier
- Suitable for use on radiant flooring
- No asphalt odor
- Clearly visible chalk lines
- No residue on hands or walls
- Free of Toxic Chemicals

**NOTE:** For use with wood subfloors only



ROBERTS® Silicone Moisture Barrier is an underlayment with a silicone coating that will not allow moisture to penetrate through to finished flooring planks. The smooth surface side allows installers to easily slide planks during install, allowing for a fast installation process.

The Silicone Moisture Barrier is made from repurposed paper that is environmentally safe and made of 100% recycled contents, and does not contain any toxic tar or tar-based materials found in some underlayments. The white paper will not leave black residue on hands or walls and allows for a more visible chalk line. In addition, it does not fall apart during installation like red rosin, kraft and wax papers can. Meets the perm ratings recommended by the Natural Wood Flooring Association.

Scan here for  
PRODUCT  
INFORMATION



## SPECIFICATIONS

ITEM #	70-198	70-198-9
UNIT OF MEASURE	1 each	1 case / 9 rolls
COVERAGE	200 sq. ft. / roll	200 sq. ft. / roll
WIDTH OF ROLL	31.5"	31.5"
LENGTH OF ROLL	76.25 ft. (915")	76.25 ft. (915")
THICKNESS	6 mil (0.006")	6 mil (0.006")