

RO-109



CLEAN AND PREP SOLUTION

TECHNICAL DATA

DESCRIPTION AND USES

Clean & Prep Solution is designed for use with the Rust-Oleum Pool Paint coatings. It is used to clean, degrease, and dissolve mineral deposits from the substrate and increasing porosity of concrete surfaces for optimal adhesion. Do not apply to concrete that has already been sealed or stained.

FEATURES

- VOC Compliant
- Suitable for painted surfaces
- Biodegradable, safe to use near plants and grass

PRODUCTS

<u>1-gallon</u>	Description	
270384	Clean & Pre	

ean & Prep Solution

PRODUCT APPLICATION

SURFACE PREPARATION

ALL SURFACES: After all surface repairs, power wash loose material from surface to ensure a clean, tight surface remains.

APPLICATION

FOR BARE CONCRETE, GUNITE, MARCITE OR PLASTER:

Mix 1 gallon Clean & Prep Solution with 2 gallons of water. Apply with a garden sprayer. Scrub thoroughly until foaming stops. Rinse thoroughly until all foam is completely gone. Cleans approximately 400 square feet per gallon.

FOR PAINTED SURFACES OR BARE FIBERGLASS: Mix 1

gallon Clean & Prep Solution with 5 gallons of water. Use a garden sprayer for even application of product. Be sure the heavily soiled areas such as the waterline, steps or regular foot paths on concrete decks are scrubbed well. Rinse the surface (3 times) with a strong stream of clean water, while scrubbing, to ensure complete removal of all material. Cleans approximately 600-800 square feet per gallon.

CLEAN UP

Clean all application tools with water immediately after use.

TECHNICAL DATA

RUST-OLEUM

CLEAN AND PREP SOLUTION

PHYSICAL PROPERTIES

Composition		Water, Phosphoric Acid and Surfactants
Weight	Per Gallon	10.3 lbs.
	Per Liter	1.23 kg
рН		1.5
Volatile Organic (less water and	c Compounds exempt solvents)	0 g/l
Storage		Do not store at temperatures below 50°F (10°C). Do not allow to freeze.
Shelf Life		2 years in unopened containers properly stored in a cool dry area.
Safety Information	Warning!	CONTAINS PHOSPHORIC ACID. USE ONLY WITH ADEQUATE VENTILATION. TO AVOID OVEREXPOSURE, OPEN WINDOWS AND DOORS OR USE OTHER MEANS TO ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IF YOU EXPERIENCE EYE WATERING, HEADACHES OR DIZZINES, INCREASE FRESH AIR OR WEAR RESPIRATORY PROTECTION (NIOSH/MESA TC23C OR EQUIVALENT) OR LEAVE AREA. AVOID CONTACT WITH EYES AND SKIN. WASH HANDS AFTER USING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR ADDITIONAL SAFETY INFORMATION.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com/industrial Form: CS1768 Rev.: 091613