



Safe-T-Deck®

What is it:

- Acrylic Latex Safety Paint
- Skid resistant
- Waterbased
- Easy application
- Ready to use - no mixing required
- Water clean up
- 6 color variants and is tintable

What Does it do:

- Preserves and protects
- Increases the strength of surface through adhesion
- Seals out moisture and renews the old surface.
- Up to 300% Elastomeric

Where to Use:

- Decks
- Roof Decks
- Stairways
- Walkways
- Wheelchair Ramps
- Porches & Patios
- Concrete
- Wood
- Boat Decks

Finally, waterproofing that really works!



We are a green manufacturer of premium grade, elastomeric coatings and paints for waterproofing roofs, walls, decks, basements, and many other surfaces. We are experts with over 27 years of experience in waterproofing. Our impervious coatings are the highest quality. All products are waterbase, water clean up and contain no petroleum.



AMES® **Elastomeric**
SAFE-T-DECK®

USEFUL FOR:

- **Roof Decks**
- **Stairs**
- **Decks**
- **Ramps**
- **Wood**
- **Concrete**



**ACRYLIC SKID
RESISTANT
SAFETY PAINT**



Made with Pride in the USA

Manufactured by Ames Research Laboratories, Inc.
1891 16th St. SE Salem, OR 97302

Ames® Safe-T-Deck® is a trademark of Ames Research Laboratories, Inc. Copyright ©2018 by Ames Research Laboratories, Inc. All illustrations, photographs, diagrams and written content are property of Ames Research Laboratories, Inc. All Rights Reserved. 050318



1-888-345-0809

www.amesresearch.com

Do It Yourself in Three Easy Steps

To learn more application tips visit www.amesresearch.com



1. Surface Preparation

Read all label instructions before beginning. Always run a test patch first in an inconspicuous area to ensure that proper adhesion and drying occurs and the product works to your satisfaction. Do not proceed unless the product works totally to your satisfaction. Remove all loose paint, dirt, oil and grease leaving the surface clean and dry. All major cracks, joints and seams should be caulked with Ames® Blue Max® Trowel-Grade coating and filler. Do not use a silicone caulk. Make sure the surface is as smooth as possible.

2. Seam Tape Joint & Cracks

All surfaces with joints, cracks, flashings or where two unlike surfaces come together will require seam taping to provide additional strength and reinforcement. Ames® Peel & Stick™ adhesive seam tape (PS250, PS450, PS650) is easy to apply. Simply peel off the backing, place over the seam, and firmly press into place.

**NOTE: The Peel & Stick™ Seam Tape may show a slight bump and radiate through coating.*

3. Application

Apply one to three coats of Safe-T-Deck® as needed to properly seal the surface to a watertight system.

Maintenance: Life expectancy has been known to last five to ten years. One or more coats may be required annually over existing Safe-T-Deck® surfaces in high traffic areas and very damp areas depending on weather and wear. Inspect your deck annually. Recoat with Ames® products as needed.


Application Tools

Apply Safe-T-Deck with a 3-4 inch wide paint brush or a paint roller. Depending upon the project preparation work, Safe-T-Deck may require one of more or the following:



Estimated Coverage

Standard product coverage is one gallon per 100 sq. ft. per coat. Rough surfaces may require additional coating. Most decks will need two coats. Roof decks with roof fabric will need four coats to five gallons per 100 sq. ft. total.



Clean-Up, Storage, and Disposal

Clean tools and small spills with water. Store unused product in its original container, tightly sealed and protected from freezing. Dispose of this product in accordance with local, state, or federal requirements.

