

## In-Wall Timer - Heavy-Duty Mechanical In-Wall Timer - 20 A

Item IW700K / EAN-Code



### APPLICATIONS

- ▶ Entryway Lighting
- ▶ Deck Light Controls
- ▶ Landscape Light Controls
- ▶ Attic Fans
- ▶ Pumps
- ▶ Hallway Lighting
- ▶ Small Commercial Signage and Store Lighting

### TECHNICAL DATA

#### General

Application Compatibilities	Incandescent
	Fluorescent
	Compact Fluorescent
Warranty	1-year limited
Mechanism Type	Analog/Mechanical
UPC Code	078275143456
Description	Heavy-Duty Mechanical In-Wall Timer - 20 A
Model Number	IW700K
Brand	Intermatic
Harmonized Code	9107.00.8000
Country of Origin (Intermatic)	MEXICO

#### Electrical Specifications

Neutral Connection Required	True
Wiring Configurations	Single
Wiring Option	SPST (3) #14 AWG color coded
	SPDT (4) #14 AWG Color Coded
Input Voltages	120 VAC, 60 Hz
Switch Type	SPST

#### Material Specifications

Includes Wall Plate	False
Color	White
Shipping Weight (kg)	0.172
Shipping Weight (lbs)	0.38

#### Control Specifications

Minimum ON/OFF Times	20 min
Hold Mode Included	False
Maximum ON/OFF Operations	36
Operation Mode	24-hours

**Environmental Specifications**

Operating Humidity	0 to 95%, Non-condensing
Operating Temperature Min (°C)	-40
Operating Temperature Min (°F)	-40
Operating Temperature Max (°C)	82
Operating Temperature Max (°F)	180
California Proposition 65	DEHP

**Load Ratings**

Incandescent Load Ratings (Single-Gang)	1350 W, 120 VAC, 60 Hz
Resistive	20 A, 120 VAC, 60 Hz
Inductive	8 A, 120 VAC, 60 Hz
Motor	1 HP, 120 VAC, 60 Hz

**Standards and Certifications**

UL Certification	cULus
CSA Certification	cCSAus

**Dimensions**

Unit Carton Height (in)	3
Unit Carton Width (in)	3
Unit Carton Length (in)	4