




Premium Sheetgoods Adhesive



2001

• Non staining formula • Solvent free • Environmentally safe • Zero VOC calculated



ROBERTS® 2001 Premium Sheetgoods Adhesive is a synthetic non staining latex-based adhesive designed to adhere to allfelt-backed or mineral-backed sheetgoods. Roberts 2001 may be used over plywood of underlayment quality, and on-, above- and below-grade concrete sub-

floors. **ROBERTS 2001 IS NOT RECOMMENDED FOR SOLID VINYL-BACKED, LINOLEUM OR PERIMETER FLOORING. DO NOT USE WHEN INSTALLING FLOORING OVER CONCRETE EMITTING MOISTURE OF 3 LBS. OR MORE OR ALKALINE CONCRETE THAT MEASURES pH9 OR ABOVE.**

TYPICAL PROPERTIES:

Appearance: Beige Mastic

Base: Synthetic Latex

Non-volatiles: 65%

Consistency: Trowelable Mastic-Do Not Thin

Shelf-Life: One year minimum at 70°F

Flash Point: Non-flammable

Normal Open Time: Up to 20 minutes

Coating VOC: 0 Calculated VOC

Ventilation: Implement effective ventilation before, during and after installation by opening windows and doors for an adequate supply of fresh air. Consider using window fans and/or air movers to bring in fresh air and shorten curing time of the adhesive.

Before Installation:

Temperature:


- Roberts 2001 adhesive is freeze-thaw stable at 10°F (-12.2°C) or above and may be permanently damaged if stored below 10°F (-12.2°C).
- The Roberts 2001 adhesive and subfloor must be at least 65°F (18.3°C) or higher if recommended by the flooring manufacturer.

Floor Condition:

- The subfloor must be clean, dry and free of hydrostatic pressure, alkali, oil, moisture, dust, paint, grease, wax, cut-back adhesive and structurally sound.
- All substrate cracks, joints and uneven areas should be filled with a Roberts R-Krete 1440 floor patch. Allow floor patch to dry for 24 hrs. before applying the adhesive.

Coverage:

Floorcovering Type	Notch Size	Approx. Coverage
Felt- or Mineral-backed Sheetgoods	1/16 x 1/16 x 3/32 U (E1)	162-180 sq ft/gal



The above recommended trowel notches are merely suggestions and/or a starting point. Surface conditions and roughness of material backing will ultimately determine the coverage needed. It is the installer's responsibility to ensure 100% transfer of adhesive to the material backing, including recessed areas. Full coverage of the floor surface is also necessary.

During Installation:

Apply Adhesive:

- Layout flooring according to manufacturer's specifications. Installation instructions issued by sheetgoods manufacturer on underlayment, floor preparation and seam sealing must be followed.
- Apply Roberts 2001 adhesive evenly to the subfloor according to industry standards or as recommended by the flooring manufacturer using a Roberts (E1) trowel.

Install Flooring:

- Set the flooring into the adhesive while it is still wet, normally within 20 minutes after troweling. Adjust the flooring if necessary within this time. Lift a corner periodically to see if the adhesive is transferring 100% to the back of the flooring. If the adhesive is not transferring, apply additional adhesive.
- When high humidity exists, allow additional set time before lowering flooring into the adhesive.
- When it is necessary to seam sheetgoods, follow the flooring manufacturer's instructions for cutting and sealing.

Roll Flooring: Press and smooth flooring firmly into the adhesive with a Roberts 10-950 75 lb. roller or according to manufacturer's specifications.

- Refer to CRI 104-105 installation standards for additional information.



Premium Sheetgoods Adhesive



2001

• Non staining formula • Solvent free • Environmentally safe • Zero VOC calculated

After Installation:

Drying Time: Restrict foot traffic and moving of heavy objects for 24 hours. Do not expose to water (i.e. Cleaning) for 4-days. A longer curing time is required if temperatures are maintained lower than 65°F (18.3°C).

Clean Up: Wet adhesive can be cleaned from tools and flooring with warm soapy water. For dried adhesive, use Roberts 1912 Adhesive Cleaner sparingly with a clean white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

For additional installation instructions not included on this label, consult flooring manufacturer's recommendations.

Warranty: Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Any implied warranty of merchantability or fitness for particular use is limited to one year from date of purchase. Liability for any incidental or consequential damage or loss is specifically excluded at all times. If used for other than professional purposes, any implied warranty of merchantability or fitness for particular use is excluded.

First Aid:

Skin Contact: Remove fresh adhesive with warm water and soap. Consult physician if irritation develops.

Eye Contact: Flood with large quantities of water for 15 minutes. See physician if irritation develops.

Ingestion: Do not induce vomiting. If victim is conscious, give water to dilute. Contact a physician immediately.

KEEP OUT OF REACH OF CHILDREN.

Rated for commercial or residential use.

Refer to MSDS for more information.

Made in U.S.A.



Available in these sizes:

1 qt



1 gal



4 gal

