8 10191 03288 5

SO. CAL COMPLIANT
LOW VOC
<50 G/L

SCAN ME FOR VIDEO TUTORIAL

Classic COATINGS SYSTEMS®

TECH & DATA SHEETS
ClassicCoatingsSystems.com

WEAR EYE PROTECTION | WEAR FACE MASK | WEAR GLOVES

Classic Matte is a clear, water-based acrylic, single-component sealer. Its low VOC water-based formula ensures minimal environmental impact, while its high solids ensure robust performance and lasting protection. This versatile sealer is suitable for application on both vertical and horizontal surfaces, as well as interior and exterior areas in a wide range of climates. Functioning as an exceptional water-repellent and UV stabilizer, Classic Matte Sealer preserves surfaces without yellowing over time. Originally formulated for concrete restoration projects and pool deck coatings, it also serves as a reliable sand joint stabilizer when applied to properly prepared surfaces. Designed to deliver a low-maintenance, easily cleanable finish, Classic Matte Sealer is the ideal choice for those seeking durability and convenience. Its environmentally friendly composition ensures safe usage and effortless cleanup with just soap and water.

TYPICAL USES:

- Pool Decks & Patios
- Restoration Projects
- Architectural Toppings
- Spanish Tile
- Polymer-modified Cement Toppings
- Walkways
- Driveways
- Stucco
- Brick
- Stained Concrete
- Block Walls
- Natural Stone
- Pavers
- Masonry

LIMITATIONS:
Recommended application temperature is between 55° F and 95° F. Must be installed over a clean dry surface and must not contain moisture and efflorescence. Not freeze thaw and not for use underwater. If using high performance tires we recommend using a 2 part polyurethane sealer.

APPLICATION:
1) Prepare surface by thoroughly removing all foreign matter.
2) Mix well before use. Apply 1st coat with a brush, 3/8" nap roller, or pump sprayer. Sealer appears milky but dries clear. System thickness is 2-3 wet mils. per coat.
3) After 1- 2 hours, repeat step (2) for the 2nd coat.
4) A 3rd application may be required in high traffic areas.
Cure time at 77°F: Dry to touch in 30 minutes, allow light foot traffic after 12 hours, and full cure in 7 days.

UV STABLE
LOW SHEEN

FULL CURE IN
7 DAYS

MATTE WATER-BASED SEALER

ENHANCES COLOR + WATERPROOFS

FOR USE OVER:
BRICK • CONCRETE • FLAGSTONE
MASONRY • SLATE • *& MORE!*

COVERAGE: 300-400 sq. ft. per gallon (2 coats) depending on the condition of the surface and the method of application. Recommended application is 2 coats using a pump sprayer and back rolling with a 3/8" nap roller. 5 gallons will yield approximately 1500-2000 sq. ft. (2 coats) depending on the condition of the surface and the method of application.

NOTE: Over time, the sealer may wear down, particularly in areas with high traffic. It is advisable to reapply the sealer to areas where the sealer has worn down. Prior to use, test a small area of the surface to ensure the sealer is compatible.

WARNING: **SURFACE IS SLIPPERY WHEN WET. Keep out of reach of children and pets.** Prevent the sealer from draining into the street to help keep the oceans clean.

FIRST AID: Do not ingest. If ingested, seek medical attention immediately. Contact with eyes or skin may cause irritation. In case of contact, wash thoroughly with soap and water. If irritation occurs, seek medical attention. Always use gloves, safety goggles, and appropriate OSHA/NOSH approved respirator in areas with poor ventilation both indoors and outdoors. Refer to TDS and SDS for handling instructions.

Check out our YouTube channel for instructional "How To Apply" videos and find inspiration on our Instagram page!

@SimpleStains ***@ClassicCoatingSystems***

Classic Coatings Systems believes this information to be true to the best of our knowledge. Our products are of the highest quality and conform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied, is made to the effect of such use and no liability is assumed directly or indirectly from their use. Users are encouraged to conduct their own test prior to application.

California Proposition 65 Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

BATCH#

		HMIS HAZARD RATING
HEALTH SALUD	1	LEAST 0
FLAMMABILITY INFLAMABLE	0	SLIGHT. 1
PHYSICAL HAZARD PELIGRO FISICO	0	MODERATE 2
		HIGH. 3
		EXTREME. 4

BUY AMERICAN MADE . . . BECAUSE IT MATTERS

5 GAL. (119 LITERS) - COVERS APPROX. 1500-2000 SQ. FT.

CLASSIC COATINGS SYSTEMS • CORONA, CA 92878 • 951-279-2600