



Last Rev Date: 08/24/2015

Physical Properties

Appearance Black mastic	Flash Point 105°F min.	Solids By Weight 80%
Base Refined asphalt	Freezability Does not freeze	Specific Gravity @ 77° F (25°C) 1.12
Color Black	Maximum VOC 300 g/l	Weight Per Gallon 9.1-9.5 lbs (ASTM D-1475)
Consistency @ 77° F Soft, easily trowelable paste	Pliability @ 32° F No cracking or separation	

Approvals and Certifications

Meets or exceeds ASTM Specification D-4586, Type I and 100% wet surface adhesion as per ASTM D-3409
MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED - HE208 is in compliance TAS 121 with Miami-Dade Cty
NOA #12-0725.04

Description

HE208 - WET PATCH® ROOF LEAK REPAIR stops roof leaks in all temperatures and weather conditions - even in driving rain.

Usage

- Repair holes, cracks, and splits on composition, mineral surface cap sheet, asphalt coated, SBS modified, metal and masonry roofs.
- Seal leaks and openings around flashings, chimneys, vents, skylights, joints in metal edging, gutters, etc.

Coverage

12 1/2 sq. ft. per gallon applied 1/8" thick.

Surface Preparation

Clean dirt and loose material from surface. Remove embedded gravel and old roof cement that would interfere with a good bond. Remove rust and scale with wire brush.

Application

1. **APPLY** 1/8" to 1/4" thick with a trowel or putty knife. Work into hole and spread 2" to 4" beyond, feathering the edges.
2. **REINFORCE** with **HENRY 181** or **183 Repair Fabric** if hole is over 1/4" wide or 2" long.
3. **COVER** repair with a second layer of cement. For vertical surfaces in hot weather, use **#204 Plastic Roof Cement** or **#505 FlashMaster™ Flashing Cement**.

Precautions

DO NOT THIN. Do not heat container or store at temperatures greater than 110°F (43°C). When transporting, make sure the pail is secured and the lid is tight to prevent spills. **CLOSE AIR INTAKES ON ROOF UNTIL SOLVENTS DISSIPATE!** May not yield satisfactory results over some APP torch down membranes. Contact Henry and membrane manufacturer before use. Not recommended for use over gravel, rubber or PVC sheet roofing or wood shingles. To extend repair life, coat with a Henry Roof Coating after 30 days.

NOTE: Asphalt-based coatings form a water soluble residue as they weather. In areas without regular rainfall, the roof should be hosed off occasionally to prevent build-up and discoloration (removable with soap and water). Areas that pond water may accumulate more asphalt residue.

Cleanup

Clean tools with kerosene, paint thinner, or mineral spirits. Clean hands with waterless hand cleaner.

Caution

WARNING! Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Prevention: Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep containers tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid breathing mists and sprays. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection.

Response: In case of fire, use alcohol foam, carbon dioxide (CO₂) or dry chemical to extinguish. **IF ON SKIN:** Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs; Get medical advice or attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/containers in accordance with local/regional/national/international regulations. See safety data sheet for further details regarding the safe use of this product.

KEEP OUT OF REACH OF CHILDREN.

FOR EXTERIOR USE ONLY.

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, and/or birth defects, or other reproductive harm.

Product Sizes

10.1 / 10.3/ 11 OZ (0.86 lb)
GALLON (10.5 lb)

QUART (2.83 lb)
3.5 GALLON (42 lb)

4KG (9.48 lb)
5 GALLON (51 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will provide at no charge replacement product if the applicator proves, to our satisfaction, this product was defective within 7 years from purchase date of the product. We will consider this product defective if it does not perform its intended application provided it has been applied in accordance with our written instructions and used with Henry Repair Fabric. Proof of purchase must be provided for this warranty to be effective. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.** This limited warranty is in addition to and supplemented by the product warranty located on our website at: www.henry.com/warranty which also applies to this product.