



The D1100-2 series aluminum extension ladders are lightweight yet have a duty rating of 200 lbs. The TRACTION-TRED® D rungs are slip resistant. Spring-loaded locks operate smoothly for easy operation. Pivoting shoes with slip-resistant foot pads. Mar-resistant end caps help protect the surface ladder is leaning against. Exclusive ALFLO® rung joint means TWIST-PROOF® performance every time.

## Features

- Exclusive ALFLO® rung joint means TWIST-PROOF® performance
- 1-1/2in Slip-resistant TRACTION-TRED® D-rungs
- Durable extruded rung locks are spring loaded to operate smoothly
- Mar-resistant end caps
- Modified I-beam side rails to optimize strength and weight
- Pivoting shoe with slip-resistant pad

## Dimensions

Feature	Size
Rails Dimension	2-3/4 in
Flange Dimension	15/16 in
Rung Dimension	1-1/2 in
Fly Width	14-1/8 in

# Specifications

Feature	Size / Details
Size	16 ft
Reach Height	15 ft
Max Working Length	13 ft
Extended Length	13 ft
Approx. Closed Length	8 ft
Style	Multi Section
Load Capacity	200 lbs
Type	Type III Duty Rating
Performance Rating	
Material	Aluminum
Rung Type	D-Rung
Foot Material	Slip-resistant pad
Number of Sections	2
Base Width	16 in outside rails
Certifications	ANSI A14.2 (2007)
Approx. Cu. Ft. Per Unit	4.9
Approx. Shipping Wt. Lbs.	18.5
 Not equipped with rope and pulley	