

KEEP OUT OF REACH OF CHILDREN.

IN CASE OF EMERGENCY CALL: 1-800-255-3924

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND

INHALING THE CONTENTS MAY BE HARMFUL OR FATAL



FEATURES:

- Reduces Sliding Friction
- Dries in seconds
- Will not stain
- Eliminates squeaking
- Repels dirt & dust
- Resists corrosion & moisture
- Reduces wear

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov

AVERTISSEMENT: Cancer et Troubles de l'appareil reproducteur www.P65Warnings.ca.gov

APPLICATIONS:

Sliding Tracks, Locks & Hinges, Cutting Tools
Automotive, Bearing & Shafts, Saw Blades, Garden Tools

DIRECTIONS:

Shake Well. Apply to clean, dry surface. • Spray thin even coats. • Allow to cure several seconds. • Insert tip to reach confined areas.

PRECAUTIONS:

DANGER: EXTREMELY FLAMMABLE. Do not spray near sparks, heat, or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. **DO NOT SMOKE WHILE USING.** Turn off stoves, electric tools, appliances, and any other sources of ignition.

CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources. Exposure to temperatures above 120 deg. F. may cause can to burst with violence and cause injury. Do not puncture, incinerate, or place can in trash compactor. Care should be taken not to store aerosols in automobiles or trunks of automobiles when interior temperature may exceed 120 deg. F.

VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear properly fitted respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with skin and eyes. Refer to MSDS for complete safety and health information.

FIRST AID: In case of eye contact, flush thoroughly with plenty of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physicians. If swallowed, get medical assistance immediately.

NOTICE: Reports have associated repeated and prolonged occupational over exposures to solvents with permanent brain and nervous system damage.

Ingredients:

- Aliphatic Hydrocarbon CAS#110-54-3;
- Hydrocarbon Propellant CAS#68476-86-8;
- 2-propanol CAS#67-63-0; Aluminium Oxide,
- Fibrous CAS#1344-28-1

Distributed By:

PRIME-LINE

Redlands, CA

Website: rz-50.com

1-800-255-3505