



ProPink ComfortSeal™ Sill Gasket



Description

ProPink ComfortSeal™ Sill Gasket is a polyethylene foam gasket which provides resilient sealing in new and retrofit construction.

Features

- Minimizes air leakage
- Resists moisture
- Insect resistant
- Installs quickly and easily, with no special tools
- Long lasting and durable

Standards, Code Compliance

- Class A Fire Rating
- Does not support mold growth
- GreenGuard™ Certified

Applications

- Provide seal against air leakage, moisture and insect intrusion at the juncture of the foundation wall and sill plate
- Expansion joint material in poured concrete and concrete block slab and wall construction

Dimensions

Material		Product Size
Polyethylene Foam - Color: Pink	50 ft rolls	3-1/2", 5-1/2", 7-1/2" widths; 1/4" thick
Polyethylene Foam - Color: Black	50 ft rolls	3-1/2", 5-1/2", 7-1/2" widths; 3/16" thick

Technical Data*

Property	Test Method	Foam Sill Plate Material
Compressive Strength	ASTM D3575-93	2.7
Vertical Direction (psi)	Suffix D @ 25% / 50%	10.4
Compression Set (%)	ASTM D3575-93 Suffix B	29.4
Tear Resistance (lb/ft ²)	ASTM D3575-93	8.2
(@ Each Thickness)	Suffix T MD / CMD	11.5
Density Range lb/ft ³)	ASTM D3575-93	1.0-1.2
Water Absortion (lb/ft ²)	ASTM D3575-93 Suffix L	< 0,1
Water Vapor Transmission Rate	ASTM F-1249	0.089
GM / 100 in ² / 24 hr.	Method 3005 FED STD 101	0.089
Thermal Resistance R-Value @ initial thickness	ASTM C518-91	1 Layers
(HR-FT ² -°F/BTU)		0.68
Surface Resistivity	EIA STD. 541	1,0 x 10 ⁹ -

* The data presented for these products are for unconverted Ivex Protective Packaging polyethylene foam products. While values shown are typical of these products, they should not be construed as specification limits.

Installation Instructions

1. Smooth top surface of foundation wall to have minimal variation
2. Unroll Sill Gasket on top surface of foundation wall or fasten to bottom of sill plate on tilt-up wall sections with ridged side toward roughest surface
3. Overlap all end and perpendicular joints
4. Pierce Sill Gasket at anchor bolt locations
5. Set and anchor sill plate to foundation wall

Caution: ProPink ComfortSeal™ Sill Gasket is combustible and will ignite. The product may contain flammable vapors and should be stored in well ventilated areas. Do not expose the product to open flame during shipping, storage, installation or use.

Recommended Tools

- Safety glasses
- Cut resistant gloves
- Ladder
- Construction or hammer stapler
- 5/16" heavy duty staples
- Scissors or utility knife

This product should be installed in accordance with applicable building codes. Please refer to the Safety Data Sheet for more information.

Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high-quality products and services.

Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives. More information can be found at www.owenscorning.com.

Certifications and Sustainable Features

- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg



Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK®
www.owenscorning.com

Pub. No. 23514-H. Printed in U.S.A. February 2017.
THE PINK PANTHER™ & © 1964–2017 Metro-Goldwyn-Mayer Studios Inc.
All Rights Reserved. The color PINK is a registered trademark of Owens Corning.
© 2017 Owens Corning. All Rights Reserved.

