SAFETY DATA SHEET



1. Identification

Product identifier SHEETROCK® Brand Wall and Ceiling Spray Texture, Ready-Mixed

Other means of identification

SDS number 48000010002
Recommended use Interior use.

Recommended restrictionsUse in accordance with manufacturer's recommendations.

Manufacturer / Importer / Supplier / Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

Telephone 1-800-874-4968
Website www.usg.com
Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure (inhalation)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. May cause damage to organs (Lung) through prolonged or repeated exposure

by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not

Category 2 (Lung)

breathe dust.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	% < 65	
Limestone	1317-65-3		
Mica	12001-26-2		
Perlite	93763-70-3	< 10	
Attapulgite	12174-11-7	< 5	

Impurities

Chemical name	CAS number	
Crystalline silica (Quartz)	14808-60-7	< 2.5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is ≤ 2.3%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists.

Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Under normal conditions of intended use, this product is not expected to be a health risk. Dust may

irritate throat and respiratory system and cause coughing.

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire

Fire-fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	
Mica (CAS 12001-26-2)	TWA	20 mppcf	
Impurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
,		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	2 S		

Components	Туре	Value	Form
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Impurities	Туре	Value	Form
Crystalline silica (Quartz)	TWA	0.025 mg/m3	Respirable fraction.

(CAS 14808-60-7)

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable.
Perlite (CAS 93763-70-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Impurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Respiratory protection

It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin Hand protection

contact use suitable protective gloves.

Normal work clothing (long sleeved shirts and long pants) is recommended. Other

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use. None.

Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Solid. Physical state **Form** Paste. Color Off-white Low to no odor. Odor **Odor threshold** Not applicable. 8.5 - 10

Melting point/freezing point Not applicable. / 32 °F (0 °C) Initial boiling point and boiling 212 °F (100 °C)

range

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Vapor pressure Not available.

Vapor density Not available.

Relative density 1.5 - 1.7 (H2O=1)

Relative density Solubility(ies)

Solubility (water) Soluble in water.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity 300 - 840 Brabender units (20 °C)

Other information

Bulk density 12.5 - 14.2 lb/gal

VOC (Weight %) 1 g/l (Calculated by EPA Method 24)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition

products

Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause discomfort if swallowed.

Inhalation Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne

respirable crystalline silica can cause silicosis and/or lung cancer.

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Eye contact Airborne dust may cause mechanical eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity

Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization The product contains a small amount of sensitizing substance which may provoke an allergic

reaction among sensitive individuals after repeated contact.

For detailed information, see section 16.

Data does not suggest that this product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Repeated and prolonged exposures to high levels of respirable crystalline silica may cause Carcinogenicity

cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Attapulgite (CAS 12174-11-7) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Crystalline silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

May damage lung tissue through repeated and prolonged exposure to high levels of respirable

crystalline silica particles.

Aspiration hazard Not an aspiration hazard.

Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to Chronic effects

the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be

monitored and controlled.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

No data available. Mobility in soil Other adverse effects None expected.

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Dispose of in accordance with local regulations. Local disposal regulations

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Dispose of in accordance with local regulations. Contaminated packaging

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories**

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name **CAS** number **Threshold Threshold** Reportable Threshold quantity planning quantity planning quantity, planning quantity, lower value upper value

Vinyl acetate 5000 1000 lbs 108-05-4 Yes

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)

Limestone (CAS 1317-65-3) Mica (CAS 12001-26-2) Perlite (CAS 93763-70-3)

US. New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)

Limestone (CAS 1317-65-3) Mica (CAS 12001-26-2) Perlite (CAS 93763-70-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)

Limestone (CAS 1317-65-3) Mica (CAS 12001-26-2) Perlite (CAS 93763-70-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Attapulgite (CAS 12174-11-7)

Crystalline silica (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Nο

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 03-February-2014

Revision date 01 Version #

SHEETROCK® Brand Wall and Ceiling Spray Texture, Ready-Mixed 915540 Version #: 01 Revision date: - Issue date: 03-February-2014

Further information

Crystalline silica: Raw materials in this product may contain respirable crystalline silica. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Vinyl acetic monomer, formaldehyde and acetaldehyde: Trace amounts of vinyl acetate monomer and formaldehyde may be found in this product.

Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is below the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA Ratings



List of abbreviations References NFPA: National Fire Protection Association.

Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Products.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.