

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

SPECIALTY
CAMOUFLAGE SPRAYS

DESCRIPTION AND USES

A flat, non-reflective spray paint designed for use on wood, metal, and other surfaces to disguise or break up the outlines of items to blend in with different terrains. These durable paints are suitable for outdoor use and resist chipping, cracking, and peeling. Do not use on galvanized surfaces.

APPEARANCE

Flat

PRODUCTS

FINISHES

- 1916830 Black
- 1917830 Khaki
- 1918830 Earth Brown
- 1919830 Deep Forest Green
- 1920830 Army Green
- 263653 Sand

PAINTING CONDITIONS

SURFACE PREPARATION

ALL SURFACES: Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Mold and mildew must be cleaned with a chlorinated cleaner or bleach solution. Rinse with fresh water and allow to thoroughly dry.

STEEL: Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Use 7569838 Red Primer for sound rusted or clean metal before application of a finish coat.

PREVIOUSLY COATED: Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy surfaces should be scarified by sanding to create a surface profile. . Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. **LEAD IS TOXIC.** Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD pr log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply only when air and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85% to ensure proper drying. Use outdoors or in areas with good ventilation. Avoid spraying in very windy or dusty conditions. Cover surrounding area to protect from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 12-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying.

Apply a base coat of one color first. Then use leaves and twigs as stencils and lay them on the surface to make a random pattern. Then use three or more colors to paint stripes and patterns over the leaves and twigs. **Do not use near open flame.**

CLEAN-UP

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds. Clean up wet paint with xylene or mineral spirits. Throw away empty can in trash pick-up. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

SPECIALTY CAMOUFLAGE SPRAYS

PHYSICAL PROPERTIES

		SPECIALTY CAMOUFLAGE SPRAYS
Resin Type		Acrylic Modified Alkyd
Solvents		Acetone, Toluene, Xylene
Fill Weight		12 oz.
MIR		1.20 Max
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 6-7 sq. ft./can (0.54-0.63 m ² /can)
Dry Times at 70°F (21°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 24 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.