



GH-34

Paste for Unpasted Wallpaper

Clear, Strippable, Non-Staining Wallcovering Adhesive

Product Number(s): 209814, 209820

Base: Wheat starch

Product Information

General Properties: Ready-to-use adhesive for applying all types of wallcoverings, including English pulp papers, as well as commercial weight products.

- **Machinable**
- **Recommended for English-pulp paper**
- **Ideal for specialty wallcovering such as grasscloth and stringcloth**
- **Superior wet tack**
- **LEED compliant**

Recommended Uses: For paper-backed and heavyweight vinyls, mylars, naugahyde, heavy weight foils, burlaps and other synthetic fabrics weighing up to 34 oz.

NOT Recommended For: Application over oil/ alkyd primers or paints

Compatible Coatings: All ROMAN[®] primers

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Percent Solids: Approximately 16%

Coverage: Up to approx. 180 square feet per gallon

Viscosity: Approximately 90,000 cps

VOC (actual): 0.24% (\leq 1%)

VOC (regulatory): \leq 25 g/L

Drying Time: Drying time will vary depending on the temperature, ventilation and humidity of the room

Storage: Avoid freezing; keep in cool, dry place

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply a coat of adhesive with a pasting machine, brush or roller. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book according to the wallcovering manufacturer's instructions.

Clean-Up: Before the adhesive dries, remove any excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.