

Technical Data Sheet



Eclectic Products, Inc.
Manufacturing Facility
101 Dixie Mae Drive
Pineville, Louisiana
eclecticproducts.com
800.349.4667

**ISO 9001:2008
Compliant
Quality Management Systems**

Administration Office
Eugene, Oregon
eclecticproducts.com
800.693.4667



8.0 fl oz | 236.5 mL spray bottle



E6000[®] SPRAY ADHESIVE

No Odor, Interior / Exterior & Multi-Purpose

PRODUCT DESCRIPTION

E6000 Spray Adhesive is a permanent, multi-purpose latex-based spray applied adhesive without the toxic smells, fumes or unhealthy side effects. It works great for surface area applications and adhering/mounting lightweight materials.

WHERE TO USE / APPLICATIONS

SAFE & EASY	GREAT FOR	USE ON	DEPENDABLE
No Odor, Easy Water Clean-Up, No Harsh Chemicals.	Craft / Décor / Home Repairs Scrapbooking / Photos & Framing / Hobby / School Home Office & more!	Paper, Wood, Poster Board, Cardboard, Photos, Foil, Medium to Heavy-Weight Fabrics, Vinyl, Foam, Styrofoam [®] , Glass, Felt, Plastic, Rubber, Leather & Metals.	Strong, Translucent, Flexible, Permanent Bond. Photo-Safe. Resists Water, Bleed-Through & Yellowing.

FEATURES AND BENEFITS

NO ODOR FORMULA

NO toxic smells/fumes or unhealthy side effects from using E6000 Spray Adhesive. No more strong odor, headaches, coughing, dizziness, etc.

NO MESS & E-Z WATER CLEAN-UP

Clean-up is a breeze – Just use water. No more sticky mess.

MULTI-PURPOSE

Use for all kinds of projects! Anything from home repairs, to crafting, for hobby/school or office projects, to décor, scrapbooking, photos & framing, to scenery building and much more!

VERSATILE

Use on paper, wood, poster board, cardboard, photos, foil, medium to heavy-weight fabrics, vinyl, upholstery batting, foams, Styrofoam[®], glass, felt, plastic, rubber, leather, metals & more!

EXTREMELY STRONG

Lab testing results prove that E6000 Spray Adhesive forms a stronger bond on most materials used around the home, at work and by crafters.

DEPENDABLE

Strong, flexible, permanent bond. Resists water. Won't yellow. Can be used indoors or outdoors.

MORE FRIENDLY...

When used as recommended, this latex-based adhesive isn't harmful to people or the environment. The product contains VERY LOW VOCs, has NO harsh chemicals, is CARB compliant, requires NO Prop 65 warnings and uses no propellants or solvents. It is an OUTSTANDING solution for your spray adhesive needs.

PHOTO SAFE

The lignin-free formula has a low pH, making it great to use on photographs.

SUPER E-Z TO USE

Pumps out in a fine, even spray mist that is solvent & propellant-free.

RESISTS BLEED-THROUGH

Resists bleed-through – unless the consumer intentionally saturates the substrate for unique projects. Once dry, the adhesive helps form a barrier that helps protect material.

TRANSLUCENT

Dries to a translucent "color" that is virtually invisible when dry.

Technical Data Sheet



E6000[®] SPRAY ADHESIVE

No Odor, Interior / Exterior & Multi-Purpose



8.0 fl oz | 236.5 mL spray bottle

TECHNICAL INFORMATION

PHYSICAL & PERFORMANCE PROPERTIES

Technology:	Water-based formula	Coverage:	8.0 fl oz bottle – 50 sq ft @ 2 mils (0002”) film thickness; or 25 sq ft @ 4 mils (0.004”) film thickness
Color:	Translucent white	Application temperature:	Best applied between 50 – 130 °F / 10 – 54 °C
VOC:	4.00577%	Service temperature / heat resistance:	30 - 150 °F / -1 – 65 °C
Solvent:	None	Storage temperature:	Store above 40 °F / 4 °C
Flammable:	No	Dry time:	Varies by material and conditions
Density:	1.04 g/mL	Clean-up:	Warm to hot water
Viscosity:	<500 cps	Paintable:	Yes
pH:	4 - 5	Shelf life:	2 years — ASTM D-478301
Weight per gallon:	8.66 lbs/gal		
Chemical resistance:	None		
Water resistance:	Cured adhesive has good water resistance		
UV resistance:	Cured adhesive has adequate UV resistance		
Odor:	Odorless		
Flexible:	Yes		
Freeze/thaw stability:	Stable		

DIRECTIONS and APPLICATION NOTES

Always test a small area before full use.

- Step 1 Turn upside down and **SHAKE VIGOROUSLY** before using.
- Step 2 Protect surrounding area from overspray.
- Step 3 Point spray tip away from face.
- Step 4 Hold bottle 8-10 inches away from surface.
- Step 5 **PAPER, PHOTOS, CARDBOARD & FOIL:** Spray a thin, light coat to one surface. Join materials and continue to apply pressure periodically making sure to secure corners. Allow to dry 1-3 minutes.
POROUS MATERIALS (including foams and Styrofoam[™]): Spray a heavy coat to both surfaces to be joined. Mate surfaces together. Allow to dry.*
NON-POROUS MATERIALS: Spray a light coat to one surface. Mate surfaces together. Allow to dry.*
- Step 6 **IMPORTANT – CLEAN AFTER EACH USE:** To prevent clogging, remove and rinse nozzle/straw. Pump warm tap water through sprayer, until all adhesive is cleared out. Then dry, replace in the bottle, secure cap.
- Step 7 **KEEP FROM FREEZING**

*Maximum strength may not be reached for 1-5 hours. Styrofoam[®] may require an overnight cure. For technical assistance, call 800.767.4667.

HEALTH and SAFETY

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. MSDS is available on line at: eclecticproducts.com/msds/e6000_spray_english.pdf; to request an MSDS, please send an e-mail to msds@eclecticproducts.com or call 800.333.9826.



LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc., P.O. Box 4450, Pineville LA 71360 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.