

DESCRIPTION

ScentStop is bio-engineered to digest organic odors by eliminating the source, not by merely masking the odor. It contains enzymes and non-harmful living bacteria along with bioactive solubilizing agents developed to consume the source of the odors. Effectively eliminates odors caused by urine, feces, vomit, garbage, food odors and most other organically based odors.

DIRECTIONS

Safe for treating subfloors, baseboards, tack strips, walls, flooring and upholstery. Test in an inconspicuous area first. All excess moisture and debris should be removed prior to application. Apply ScentStop generously to the source of the odor and let dry. Repeat if necessary. Store at room temperature and do not allow product to freeze.

CLEANUP

ScentStop dries clear, so no surface cleanup is required. If a pump-type sprayer was used for application, rinse with clear water.

APPLICATION TOOLS & TECHNIQUES

A traditional pump sprayer should be used. If using an existing sprayer, insure it is contaminate-free. Residue from pesticides and other cleaning agents could interact with **ScentStop** and negate it's effectiveness. Saturate all areas of subfloor, focusing on odor-based stained areas. Existing flooring, grout lines, walls, upholstery and other water safe surfaces can be treated. If treating carpet, insure that carpet, pad and subfloor are all saturated in stained areas. Test in an inconspicuous area first. One gallon treats approximately 700 square feet.

SAFE TO USE AROUND PETS & CHILDREN



PERFORMANCE
ACCESSORIES

ScentStop
BIO-ENZYMATIC ODOR NEUTRALIZER

EFFECTIVELY ELIMINATES MOST
ORGANICALLY BASED ODORS IN
SUBFLOORS, BASEBOARDS, TACKSTRIPS,
WALLS, FLOORING AND UPHOLSTERY

NET CONTENTS: 1 US GALLON (3.78 L)

CAUTION

DO NOT take internally. If swallowed, **DO NOT** induce vomiting. Call a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

FIRE RATINGS

Meets NFPA Class A and UBC Class 1 as determined by ASTM E-84 and also passes the pill test.



WARRANTY

THIS PRODUCT IS MANUFACTURED ACCORDING TO EXACTING QUALITY CONTROL STANDARDS AND IS WARRANTED TO BE FREE FROM MANUFACTURING DEFECTS. DEFECTIVE MATERIAL CALLED TO OUR ATTENTION WITHIN ONE YEAR OF MANUFACTURE WILL BE REPLACED. NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE REGARDING THE PERFORMANCE OF THIS PRODUCT SINCE THE MANNER AND CONDITIONS OF APPLICATION ARE BEYOND OUR CONTROL.

FOR USE ON

- SUBFLOORS
- BASEBOARDS
- FLOORING
- TACKSTRIPS
- UPHOLSTERY
- WALLS

Manufactured for:
Performance Accessories
160 South Industrial Blvd.
Calhoun, GA 30701

Questions:
Performance Accessories
Technical Services
800-325-7062



SAFE TO USE AROUND PETS & CHILDREN



PERFORMANCE ACCESSORIES

ScentStop

BIO-ENZYMATIC ODOR NEUTRALIZER

EFFECTIVELY ELIMINATES MOST
ORGANICALLY BASED ODORS IN
SUBFLOORS, BASEBOARDS, TACKSTRIPS,
WALLS, FLOORING AND UPHOLSTERY

NET CONTENTS: 1 US GALLON (3.78 L)

DESCRIPTION

ScentStop is bio-engineered to digest organic odors by eliminating the source, not by merely masking the odor. It contains enzymes and non-harmful living bacteria along with bioactive solubilizing agents developed to consume the source of the odors. Effectively eliminates odors caused by urine, feces, vomit, garbage, food odors and most other organically based odors.

DIRECTIONS

Safe for treating subfloors, baseboards, tack strips, walls, flooring and upholstery. Test in an inconspicuous area first. All excess moisture and debris should be removed prior to application. Apply ScentStop generously to the source of the odor and let dry. Repeat if necessary. Store at room temperature and do not allow product to freeze.

CLEANUP

ScentStop dries clear, so no surface cleanup is required. If a pump-type sprayer was used for application, rinse with clear water.

APPLICATION TOOLS & TECHNIQUES

A traditional pump sprayer should be used. If using an existing sprayer, insure it is contaminate-free. Residue from pesticides and other cleaning agents could interact with **ScentStop** and negate it's effectiveness. Saturate all areas of subfloor, focusing on odor-based stained areas. Existing flooring, grout lines, walls, upholstery and other water safe surfaces can be treated. If treating carpet, insure that carpet, pad and subfloor are all saturated in stained areas. Test in an inconspicuous area first. One gallon treats approximately 700 square feet.

CAUTION

DO NOT take internally. If swallowed, **DO NOT** induce vomiting. Call a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

FIRE RATINGS

Meets NFPA Class A and UBC Class 1 as determined by ASTM E-84 and also passes the pill test.



WARRANTY

THIS PRODUCT IS MANUFACTURED ACCORDING TO EXACTING QUALITY CONTROL STANDARDS AND IS WARRANTED TO BE FREE FROM MANUFACTURING DEFECTS. DEFECTIVE MATERIAL CALLED TO OUR ATTENTION WITHIN ONE YEAR OF MANUFACTURE WILL BE REPLACED. NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE REGARDING THE PERFORMANCE OF THIS PRODUCT SINCE THE MANNER AND CONDITIONS OF APPLICATION ARE BEYOND OUR CONTROL.

FOR USE ON

- SUBFLOORS
- BASEBOARDS
- FLOORING
- TACKSTRIPS
- UPHOLSTERY
- WALLS

Manufactured for:
Performance Accessories
160 South Industrial Blvd.
Calhoun, GA 30701

Questions:
Performance Accessories
Technical Services
800-325-7062

