BEHR

SAFETY DATA SHEET

DRAFT VERSION

1. Identification

Product identifier BEHR Water-Based Spar Urethane Gloss

Other means of identification

Product code B8204

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp.

1801 E. St. Andrew Place Santa Ana. CA 92705

 Telephone
 714-545-7101

 Emergency telephone
 +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Sensitization, skin Category 1
Germ cell mutagenicity Category 1B
Carcinogenicity Category 2
Reproductive toxicity Category 1B

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May

cause genetic defects. Suspected of causing cancer. May damage the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist/vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective

clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical

advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

BEHR Water-Based Spar Urethane Gloss

SDS US

951112 Version #: 00 Revision date: Draft version. Issue date: Draft version.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Dipropylene glycol, monomethyl ether	34590-94-8	1 - 5
Triethylamine	121-44-8	1 - 3
2-Benzimidazole carbamic acid, methyl ester	10605-21-7	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-pi peridyl) Sebacate	41556-26-7	0.1 - 1
Diuron	330-54-1	0.1 - 1
Methyl 1,2,2,6,6-pentamethyl-4-piperid yl sebacate	82919-37-7	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2h-benzotriazol-2 -yl)-5-(1,1-dimethylethyl)-4-hyd roxyphenyl]-1-oxopropyl]ome ga[3-[3-(2h-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxy phenyl]-1-oxopropoxyl]-	104810-47-1	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2h-benzotriazol-2 -yl)-5-(1,1-dimethylethyl)-4-hyd roxyphenyl]-1-oxopropyl]ome gahydroxy-	104810-48-2	0.1 - 1

Composition comments

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media
Unsuitable extinguishing
media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

BEHR Water-Based Spar Urethane Gloss

wiove containers from the area if you can do so without risk.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Occupational exposure limits

Components	Туре	Value	
Dipropylene glycol, monomethyl ether (CAS 34590-94-8)	PEL	600 mg/m3	
		100 ppm	
Triethylamine (CAS 121-44-8)	PEL	100 mg/m3	
		25 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
Dipropylene glycol, monomethyl ether (CAS 34590-94-8)	STEL	150 ppm	
	TWA	100 ppm	
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Triethylamine (CAS 121-44-8)	STEL	1 ppm	
	TWA	0.5 ppm	
US. NIOSH: Pocket Guide to Chemica	l Hazards		
Components	Туре	Value	
Dipropylene glycol, monomethyl ether (CAS 34590-94-8)	STEL	900 mg/m3	
		150 ppm	
	TWA	600 mg/m3	
		100 ppm	

BEHR Water-Based Spar Urethane Gloss

SDS US

951112 Version #: 00 Revision date: Draft version. Issue date: Draft version.

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value

Diuron (CAS 330-54-1) TWA 10 mg/m3

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin. Triethylamine (CAS 121-44-8) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin. Triethylamine (CAS 121-44-8) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Light beige.
Odor Slight.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 45 - 70 (Seconds, #3 Zahn Cup)

Other information

Density8.47 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 51 g/l (including water)(Material) 161 g/l (excluding water)(Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristic

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

toxicological characteristics Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

Dipropylene glycol, monomethyl ether (CAS 34590-94-8)

Acute Dermal

LD50 Rabbit 10 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity Suspected of causing cancer.

BEHR Water-Based Spar Urethane Gloss
951112 Version #: 00 Revision date: Draft version. Issue date: Draft version.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity May damage the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential No data available. No data available. Mobility in soil No data available. Other adverse effects

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the **Disposal instructions**

material under controlled conditions in an approved incinerator.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN3082

Environmentally hazardous substance, liquid, n.o.s. (2-Benzimidazole carbamicacid, methyl **UN proper shipping name**

ester, Diuron)

Transport hazard class(es)

Class 9 Subsidiary risk Packing group Ш **Environmental hazards** Yes **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN3082 **UN** number

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Benzimidazole

carbamicacid, methyl ester, Diuron)

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group **Environmental hazards**

> Marine pollutant Yes

BEHR Water-Based Spar Urethane Gloss

EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Benzimidazole carbamic acid, methyl ester Listed.

(CAS 10605-21-7)

Diuron (CAS 330-54-1) Listed. Triethylamine (CAS 121-44-8) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Respiratory or skin sensitization

Germ cell mutagenicity Carcinogenicity Reproductive toxicity

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Triethylamine121-44-81 - 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Triethylamine (CAS 121-44-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

 $Contains\ component (s)\ regulated\ under\ the\ Safe\ Drinking\ Water\ Act.$

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Triethylamine (CAS 121-44-8) Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

Dipropylene glycol, monomethyl ether (CAS 34590-94-8)

Diuron (CAS 330-54-1)

Triethylamine (CAS 121-44-8)

US. New Jersey Worker and Community Right-to-Know Act

2-Benzimidazole carbamic acid, methyl ester (CAS 10605-21-7)

Dipropylene glycol, monomethyl ether (CAS 34590-94-8)

Diuron (CAS 330-54-1)

Triethylamine (CAS 121-44-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Dipropylene glycol, monomethyl ether (CAS 34590-94-8)

BEHR Water-Based Spar Urethane Gloss

SDS US

Diuron (CAS 330-54-1) Triethylamine (CAS 121-44-8)

US. Rhode Island RTK

Dipropylene glycol, monomethyl ether (CAS 34590-94-8) Diuron (CAS 330-54-1) Triethylamine (CAS 121-44-8)

16. Other information, including date of preparation or last revision

Issue date

Revision date

Draft version.

Version #

Draft version.

Draft version.

Health: 2*
Flammability: 0

Physical hazard: 0

List of abbreviations

DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

TWA: Time Weighted Average Value.

LD50: Lethal Dose, 50%.

References HSDB® - Hazardous Substances Data Bank

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR Water-Based Spar Urethane Gloss

SDS US

951112 Version #: 00 Revision date: Draft version. Issue date: Draft version.