



3095

HIGH-PERFORMANCE CARPET ADHESIVE Residential & Commercial



Powered by Microban® for superior mold and mildew protection.

1. DESCRIPTION

ROBERTS® 3095 HIGH-PERFORMANCE CARPET ADHESIVE is a commercial-grade, premium adhesive developed for the most demanding carpet installations, including broadloom carpet. ROBERTS 3095 is an excellent adhesive for direct or double-bond installation methods.

Features and Benefits

- High-solids content (70%-73%) for the most demanding carpet installations
- Fast grab and excellent for double-bond installations
- Moisture control up to 10 lbs. MVER and 90% RH
- Coverage up to 200 ft²/gal
- Commercial and residential use
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Commercial carpet

Residential carpet

Backings (smooth back & rough back)

Unitary

Actionbac®

Jute

Polypropylene

Polyurethane

Approved Substrates

Concrete

APA-rated plywood

Terrazzo

VCT (properly prepared)

For floorings and backings not listed, contact Technical Services at (706) 277-5294.

Recommended Trowel and Coverage Rate*

1/8" x 1/8" x 1/8" (3 mm x 3 mm x 3 mm) U Notch

Flooring: Carpet (polypropylene; woven)
Coverage: 65-75 ft²/per gallon (6-6.9 m²/per 3.78 L)

1/8" x 1/8" x 1/16" (3 mm x 3 mm x 1.5 mm) V Notch

Flooring: Carpet (polypropylene; woven)
Coverage: 90-110 ft²/per gallon (8.3-10.2 m²/per 3.78 L)

3/32" x 3/32" x 3/32" (2.3 mm x 2.3 mm x 2.3 mm) V Notch

Flooring: Carpet (non-woven; closed cell; Enhancer™)
Coverage: 100-200 ft²/per gallon (9.2-18.5 m²/per 3.78 L)

For natural fiber carpeting see additional table on pg 2.

** NOTE: The trowel notches referenced are those typically recommended for the type of flooring being installed, and are referenced as a guide. Coverage rates will vary depending on trowel type, substrate and installation conditions. Consult flooring manufacturer for their specific trowel recommendations.*



HIGH SOLIDS CONTENT
70-73%



SHELF LIFE
2 YEARS



LIFETIME
WARRANTY*

*Based on installation by an industry certified installer

Recommended Trowels for Installation of Natural Fiber Carpeting*

Method	Carpet Backing	Trowel Dimensions	Notch
Direct Glue Down	Smooth or Rough Back	1/8" x 1/8" x 1/8"	U

Method	Trowel Dimensions	Notch	
Double Glue Down	Between Floor & Cushion	1/16" x 1/16" x 1/16"	SQ
	Between Cushion & Carpet (Smooth Back)	1/8" x 1/16" x 1/8"	U
	Between Cushion & Carpet (Rough Back)	1/8" x 3/16" x 1/8"	U

*Per industry association guidelines

2. TECHNICAL DATA

Product Type:	SBR Latex
Color:	Beige
Odor:	Very mild, non-offensive, odorless when dry
Open Time:	Up to 20 minutes
Working Time:	Up to 40 minutes Setup time will vary slightly with temperature and porosity of substrate
Curing Time:	24 to 48 hours
Traffic:	Residential: 12 hours Commercial: 24 hours Rolling Loads: N/A
MVER:	10 lbs or less (ASTM F1869) / 90% RH or less (ASTM F2170)
pH:	Must not exceed 10
Shelf Life:	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
Storage:	Protect from freezing
VOC:	<1 g/L

3. INSTRUCTIONS

Limitations

- For interior installations only
- Do not use for luxury vinyl tile (LVT) or plank (LVP) or solid vinyl-backed products

Preparation

Subfloors must be structurally sound, dry, smooth, at ($\leq 3/16"$ within 10'), level and free of excess moisture/alkali and all contaminants (oil, debris, paint, sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring and its installation. All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Patching compounds must be suitable for the use application, cement-based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

This product is ready to use and does not require mixing. Maintain the same temperature and humidity during the life of the installation (between 65–95° F). Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Lift a corner periodically to ensure 100% coverage of adhesive to the flooring backing and the substrate to ensure a void-free bond. Spread adhesive uniformly. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the deepest recesses in the back of the flooring material. Place flooring into the adhesive while the adhesive is still fresh. The amount of time in which you have to place the flooring will vary with temperature and humidity.

Clean-up

Fresh adhesive – warm, soapy water on a clean cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

4. AVAILABILITY



4 G Plastic Pail	3095-4	075378309543
1 G Plastic Pail	3095-1	075378309512



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. **Lifetime Warranty applies only for installations performed by industry certified professional installers.**

Visit robertsconsolidated.com or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

H2024 12272



Roberts Consolidated Industries, Inc.
300 Cross Plains Blvd, Dalton, GA 30721
Customer Service: (866) 435-8665
Technical Support: (706) 277-5294
robertsconsolidated.com

