



SAFETY DATA SHEET

MATERIAL: LIKE-NU CONCRETE RESTORATION KIT

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT NAME: LIKE-NU CONCRETE RESTORATION KIT

SUPPLIER: LIKE-NU CONCRETE
26945 CABOT ROAD
SUITE 108
LAGUNA HILLS, CA 92653
WWW.LIKENUCONCRETE.COM

CONTACT: (949) 333-4230
INFO@LIKENUCONCRETE.COM

EMERGENCY: CALL AMBIPAR RESPONSE
1 (800) 633-8253

PRODUCT FORM: LIQUID / POWDER

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION

SKIN CORROSION/IRRITATION CATEGORY 1, 1A, 1B, 1C

SKIN IRRITATION CATEGORY 3

SENSITIZATION, SKIN CATEGORY 1, 1A, 1B

MAY BE HARMFUL IF INHALED CATEGORY 5

MAY CAUSE CANCER BY INHALATION CATEGORY 1,1A,1B

CAUSES SERIOUS EYE DAMAGE CATEGORY 1

RESPIRATORY IRRITATION CATEGORY 1,1A,1B, 3

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H315: CAUSES SKIN IRRITATION

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H333: ACUTE TOXICITY, INHALATION CATEGORY 5

H350I: CARCINOGENICITY

H318: SERIOUS EYE DAMAGE/EYE IRRITATION

H334: SENSITIZATION, RESPIRATORY

H335: SPECIFIC TARGET ORGAN TOXICITY;
SINGLE EXPOSURE; RESPIRATORY TRACT
IRRITATION.

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD

WARNING, DANGER

PRECAUTIONARY STATEMENTS

P203: OBTAIN, READ AND FOLLOW ALL SAFETY INSTRUCTIONS BEFORE USE.
 P262: DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING
 P263: AVOID CONTACT DURING PREGNANCY/WHILE NURSING
 P264: WASH HANDS AND CLOTHING THOROUGHLY AFTER HANDLING
 P265: DO NOT TOUCH EYES
 P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
 P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION/HEARING PROTECTION
 P301+P316 IF SWALLOWED: GET EMERGENCY MEDICAL HELP IMMEDIATELY
 P302+ P350: IF ON SKIN: GENTLY WASH WITH PLENTY OF SOAP AND WATER
 P333+P313 IF SKIN IRRITATION OR RASH OCCURS GET MEDICAL ADVICE/ATTENTION
 P305+P351+P338 IF IN EYES; RISE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING
 P304+P340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE BREATHING.
 P342+P316: IF EXPERIENCING RESPIRATORY SYMPTOMS: GET EMERGENCY MEDICAL HELP IMMEDIATELY
 P363 WASH CONTAMINATED CLOTHING BEFORE REUSE
 P403+P233 STORE IN A WELL-VENTILATED PLACE, KEEP CONTAINER TIGHTLY CLOSED
 P402: STORE IN A DRY PLACE,
 P404: STORE IN A CLOSED CONTAINER

OTHER HAZARDS

INHALATION CAN CAUSE SERIOUS, POTENTIALLY IRREVERSIBLE LUNG/RESPIRATORY TRACT TISSUE DAMAGE DUE TO CHEMICAL (CAUSTIC) BURNS, INCLUDING THIRD DEGREE BURNS. INDIVIDUALS WITH LUNG DISEASE (E.G. BRONCHITIS, EMPHYSEMA, COPD, PULMONARY DISEASE) OR SENSITIVITY TO HEXAVALENT CHROMIUM CAN BE AGGRAVATED BY EXPOSURE.

PHYSICAL HAZARDS

LIKE NU MANUFACTURING ACRYLIC SEALER BINDER IS A LIQUID SOLUTION THAT MAY CAUSE IRRITATION TO THE RESPIRATORY IF INHALED. IT MAY ALSO CAUSE IRRITATION TO THE EYES, SKIN, AND MUCOUS MEMBRANES UPON CONTACT. PROLONGED OR REPEATED EXPOSURE MAY LEAD TO DERMATITIS OR RESPIRATORY SENSITIZATION.

HEALTH HAZARDS

INHALATION OF THE SEALER BINDER MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT, INCLUDING COUGHING, SNEEZING, AND SHORTNESS OF BREATH. EYE CONTACT WITH THE SOLUTION MAY CAUSE IRRITATION, REDNESS, AND DISCOMFORT. SKIN CONTACT MAY RESULT IN IRRITATION REDNESS, AND DERMATITIS. INGESTION OF THE SEALER BINDER IS UNLIKELY UNDER NORMAL CONDITIONS OF USE BUT MAY CAUSE GASTROINTESTINAL IRRITATION IF INGESTED.

SIGNAL WORD

WARNING, DANGER

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

NAME	CAS NUMBER
Cement, Portland Chemicals	65997-15-1
Limestone	1317-65-3
Gypsum (Ca(SO4). 2H2O)	13397-24-5
Quartz	14808-60-7
Silica, Crystalline (general form)	Not Applicable
Calcium Oxide (CaO)	1305-78-8
Silicon Dioxide (SiO2)	14808-60-7
Trade Secret	Variable

SECTION 4: FIRST AIR MEASURES

INHALATION

REMOVE AFFECTED PERSON TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN IF TRAINED TO DO SO. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

SKIN CONTACT

WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

EYE CONTACT

FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES, HOLDING EYELIDS OPEN. SEEK MEDICAL ATTENTION IF IRRITATION OR REDNESS PERSISTS.

INGESTION

RINSE MOUTH WITH WATER. DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

MOST IMPORTANT SYMPTOMS AND EFFECTS BOTH ACUTE AND DELAYED**SYMPTOMS/INJURIES**

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE RESPIRATORY IRRITATION. SKIN SENSITIZATION. MAY CAUSE CANCER.

SYMPTOMS/INJURIES AFTER SKIN CONTACT CEMENT MAY CAUSE DRY SKIN, DISCOMFORT, IRRITATION, SEVERE BURNS, AND DERMATITIS. EXPOSURE OF SUFFICIENT DURATION TO WET CEMENT, OR TO DRY CEMENT ON MOIST AREAS OF THE BODY, CAN CAUSE SERIOUS, POTENTIALLY IRREVERSIBLE DAMAGE TO SKIN, EYE, RESPIRATORY AND DIGESTIVE TRACTS DUE TO CHEMICAL (CAUSTIC) BURNS, INCLUDING THIRD DEGREE BURNS. A SKIN EXPOSURE MAY BE HAZARDOUS EVEN IF THERE IS NO PAIN OR DISCOMFORT. CEMENT IS CAPABLE OF CAUSING DERMATITIS BY IRRITATION AND ALLERGY. SKIN AFFECTED BY DERMATITIS MAY INCLUDE SYMPTOMS SUCH AS, REDNESS, ITCHING, RASH, SCALING, AND CRACKING. IRRITANT DERMATITIS IS CAUSED BY THE PHYSICAL PROPERTIES OF CEMENT INCLUDING ALKALINITY AND ABRASION. ALLERGIC CONTACT DERMATITIS IS CAUSED BY SENSITIZATION TO HEXAVALENT CHROMIUM (CHROMATE) PRESENT IN CEMENT. THE REACTION CAN RANGE FROM A MILD RASH TO SEVERE SKIN ULCERS. PERSONS ALREADY SENSITIZED MAY REACT TO THE FIRST CONTACT WITH CEMENT. OTHERS MAY DEVELOP ALLERGIC DERMATITIS AFTER YEARS OF REPEATED CONTACT WITH CEMENT.

SYMPTOMS/INJURIES AFTER EYE CONTACT AIRBORNE DUST MAY CAUSE IMMEDIATE OR DELAYED IRRITATION OR INFLAMMATION. EYE CONTACT WITH LARGE AMOUNTS OF CLINKER DUST, DRY CEMENT POWDER OR WITH WET CEMENT CAN CAUSE MODERATE EYE IRRITATION, CHEMICAL BURNS AND BLINDNESS. EYE EXPOSURES REQUIRE IMMEDIATE FIRST AID AND MEDICAL ATTENTION TO PREVENT SIGNIFICANT DAMAGE TO THE EYE.

SYMPTOMS/INJURIES AFTER INGESTION MAY CAUSE BURNS OR IRRITATION OF THE LININGS OF THE MOUTH, THROAT, AND GASTROINTESTINAL TRACT.

CHRONIC SYMPTOMS

MAY CAUSE CANCER.

SECTION 5: FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

USE WATER FOG, FOAM, DRY CHEMICAL, OR CARBON DIOXIDE (CO₂) EXTINGUISHING MEDIA. AVOID DIRECT APPLICATION OF WATER TO HOT SURFACES OR SOLUTION.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE**FIRE HAZARD**

PRODUCT IS NOT FLAMMABLE

EXPLOSION HAZARD

PRODUCT IS NOT EXPLOSIVE

REACTIVITY

WET CEMENT IS ALKALINE AND IS INCOMPATIBLE WITH ACIDS, AMMONIUM SALTS AND ALUMINUM METAL. CEMENT DISSOLVES IN HYDROFLUORIC ACID, PRODUCING CORROSIVE SILICON TETRAFLUORIDE GAS. CEMENT REACTS WITH WATER TO FORM SILICATES AND CALCIUM HYDROXIDE. SILICATES REACT WITH POWERFUL OXIDIZERS SUCH AS FLUORINE, BORON TRIFLUORIDE, CHLORINE TRIFLUORIDE, MANGANESE TRIFLUORIDE, AND OXYGEN DIFLUORIDE.

ADVICE FOR FIREFIGHTERS**PRECAUTIONARY MEASURES FIRE**

EXERCISE CAUTION WHEN FIGHTING ANY CHEMICAL FIRE.

FIREFIGHTING INSTRUCTIONS

USE WATER SPRAY OR FOG FOR COOLING EXPOSED CONTAINERS. DO NOT GET WATER INSIDE CONTAINERS. DO NOT APPLY WATER STREAM DIRECTLY AT SOURCE OF LEAK.

PROTECTION DURING FIREFIGHTING

DO NOT ENTER FIRE AREA WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING RESPIRATORY PROTECTION.
HAZARDOUS COMBUSTION PRODUCTS: NONE.

SECTION 6: ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (PPE) INCLUDING GLOVES, GOGGLES, AND RESPIRATORY PROTECTION. USE ABSORBENT MATERIALS TO CONTAIN AND CLEAN UP SPILLS. AVOID INHALATION OF VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. DO NOT BREATHE DUST. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

ENVIRONMENTAL PRECAUTIONS

PREVENT ENTRY INTO WATERWAYS, SEWERS, OR SOIL. NOTIFY AUTHORITIES IF SPILL ENTERS WATERWAYS OR CONTAMINATES SOIL.

SECTION 7: HANDLING & STORAGE**HANDLING**

AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. USE IN WELL-VENTILATED AREAS. AVOID INHALATION OF VAPORS OR MISTS. WASH HANDS THOROUGHLY AFTER HANDLING. KEEP BULK AND BAGGED CEMENT DRY UNTIL USED. STACK BAGGED MATERIAL IN A SECURE MANNER TO PREVENT FALLING. BAGGED CEMENT IS HEAVY AND POSES RISKS SUCH AS SPRAINS AND STRAINS TO THE BACK, ARMS, SHOULDERS AND LEGS DURING LIFTING AND MIXING. HANDLE WITH CARE AND USE APPROPRIATE CONTROL MEASURES. ENGULFMENT HAZARD. TO PREVENT BURIAL OR SUFFOCATION, DO NOT ENTER A CONFINED SPACE, SUCH AS A SILO, BIN, BULK TRUCK, OR OTHER STORAGE CONTAINER OR VESSEL THAT STORES OR CONTAINS CEMENT. CEMENT CAN BUILDUP OR ADHERE TO THE WALLS OF A CONFINED SPACE. THE CEMENT CAN RELEASE, COLLAPSE OR FALL UNEXPECTEDLY. PROPERLY GROUND ALL PNEUMATIC CONVEYANCE SYSTEMS. THE POTENTIAL EXISTS FOR STATIC BUILD-UP AND STATIC DISCHARGE WHEN MOVING CEMENT POWDERS THROUGH A PLASTIC, NON-CONDUCTIVE, OR NON-GROUNDED PNEUMATIC CONVEYANCE SYSTEM. THE STATIC DISCHARGE MAY RESULT IN DAMAGE TO EQUIPMENT AND INJURY TO WORKERS. CUTTING, CRUSHING OR GRINDING HARDENED CEMENT, CONCRETE OR OTHER CRYSTALLINE SILICA-BEARING MATERIALS WILL RELEASE RESPIRABLE CRYSTALLINE SILICA. USE ALL APPROPRIATE MEASURES OF DUST CONTROL OR SUPPRESSION, AND PERSONAL PROTECTIVE EQUIPMENT (PPE) DESCRIBED IN SECTION 8 BELOW.

PRECAUTIONS FOR SAFE HANDLING: DO NOT BREATHE DUST. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. WASH HANDS AND OTHER EXPOSED AREAS WITH MILD SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING AND WHEN LEAVING WORK. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. HANDLE EMPTY CONTAINERS WITH CARE BECAUSE THEY MAY STILL PRESENT A HAZARD. OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. CUTTING, CRUSHING OR GRINDING HARDENED CEMENT, CONCRETE OR OTHER CRYSTALLINE SILICA-BEARING MATERIALS WILL RELEASE RESPIRABLE CRYSTALLINE SILICA. USE ALL APPROPRIATE

MEASURES OF DUST CONTROL OR SUPPRESSION, AND PERSONAL PROTECTIVE

STORAGE

STORE IN A COOL, DRY, WELL-VENTILATED AREA AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.

INCOMPATIBLE MATERIALS

ACIDS. AMMONIUM SALTS. ALUMINUM. WATER. OXIDIZERS.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS

FOR SUBSTANCES LISTED IN SECTION 3 THAT ARE NOT LISTED HERE, THERE ARE NO ESTABLISHED EXPOSURE LIMITS FROM THE MANUFACTURER, SUPPLIER, IMPORTER, OR THE APPROPRIATE ADVISORY AGENCY INCLUDING: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OR OSHA (PEL).

RESPIRATORY PROTECTION

USE NIOSH-APPROVED RESPIRATORY PROTECTION IF VENTILATION IS INADEQUATE OR EXPOSURE LIMITS ARE EXCEEDED.

EYE PROTECTION

WEAR SAFETY GOGGLES OR GLASSES WITH SIDE SHIELDS TO PREVENT EYE CONTACT.

SKIN PROTECTION

WEAR CHEMICAL-RESISTANT GLOVES, CLOTHING, AND FOOTWEAR TO PREVENT SKIN CONTACT.

ENGINEERING CONTROLS

USE LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW EXPOSURE LIMITS.

ENVIRONMENTAL CONSIDERATIONS

MODIFIED CEMENT PRODUCTION INVOLVES THE RELEASE OF CARBON DIOXIDE (CO₂) EMISSIONS, PRIMARILY FROM THE CALCINATION OF LIMESTONE AND COMBUSTION OF FOSSIL FUELS. USE CEMENTITIOUS MATERIALS JUDICIOUSLY TO LOWER ENVIRONMENTAL IMPACT WHEN FEASIBLE. LIKE NU HELPS IN IMPLEMENTING SUSTAINABLE PRACTICES SUCH AS OPTIMIZING MIX DESIGNS, MAXIMIZING THE USE OF SUPPLEMENTARY CEMENTITIOUS MATERIALS, AND LIMITING CONCRETE WASTE REMOVAL.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	LIQUID/GREY POWDER
ODOR	VARIABLE
PH	VARIABLE
MELTING POINT	NOT APPLICABLE
BOILING POINT	VARIABLE
FLASH POINT	NOT APPLICABLE
FLAMMABILITY	NON-FLAMMABLE
SOLUBILITY IN WATER	SOLUBLE
SPECIFIC GRAVITY	VARIABLE
VAPOR PRESSURE (MM HG)	VARIABLE
% OF VOLATILE BY WEIGHT	VARIABLE
VAPOR DENSITY	VARIABLE
EVAPORATION RATE	VARIABLE
MELTING POINT	NOT APPLICABLE
% OF WATER VOLUME	N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY	STABLE UNDER NORMAL CONDITIONS OF USE AND STORAGE.
REACTIVITY	WET CEMENT IS ALKALINE AND IS INCOMPATIBLE WITH ACIDS, AMMONIUM SALTS AND ALUMINUM METAL. CEMENT DISSOLVES IN HYDROFLUORIC ACID, PRODUCING CORROSIVE SILICON TETRAFLUORIDE GAS. CEMENT REACTS WITH WATER TO FORM SILICATES AND CALCIUM HYDROXIDE. SILICATES REACT WITH POWERFUL OXIDIZERS SUCH AS FLUORINE, BORON TRIFLUORIDE, CHLORINE TRIFLUORIDE, MANGANESE TRIFLUORIDE, AND OXYGEN DIFLUORIDE. MAY REACT WITH INCOMPATIBLE MATERIALS. AVOID CONTACT WITH ACIDS, BASES, OXIDIZING AGENTS, AND REDUCING AGENTS.
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED HANDLING AND STORAGE CONDITIONS
POSSIBILITY OF HAZARDOUS REACTIONS	HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
CONDITIONS TO AVOID	PROTECT FROM MOISTURE. INCOMPATIBLE MATERIALS.
INCOMPATIBLE MATERIALS	ACIDS. AMMONIUM SALTS. ALUMINUM. WATER. OXIDIZERS.
HAZARDOUS DECOMPOSITION PRODUCTS	NONE

SECTION 11: TOXICOLOGICAL INFORMATION

STABILITY	STABLE UNDER NORMAL CONDITIONS OF USE AND STORAGE.
REACTIVITY	WET CEMENT IS ALKALINE AND IS INCOMPATIBLE WITH ACIDS, AMMONIUM SALTS AND ALUMINUM METAL. CEMENT DISSOLVES IN HYDROFLUORIC ACID, PRODUCING CORROSIVE SILICON TETRAFLUORIDE GAS. CEMENT REACTS WITH WATER TO FORM SILICATES AND CALCIUM HYDROXIDE. SILICATES REACT WITH POWERFUL OXIDIZERS SUCH AS FLUORINE, BORON TRIFLUORIDE, CHLORINE TRIFLUORIDE, MANGANESE TRIFLUORIDE, AND OXYGEN DIFLUORIDE. MAY REACT WITH INCOMPATIBLE MATERIALS. AVOID CONTACT WITH ACIDS, BASES, OXIDIZING AGENTS, AND REDUCING AGENTS.
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED HANDLING AND STORAGE CONDITIONS
POSSIBILITY OF HAZARDOUS REACTIONS	HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
CONDITIONS TO AVOID	PROTECT FROM MOISTURE. INCOMPATIBLE MATERIALS.
INCOMPATIBLE MATERIALS	ACIDS. AMMONIUM SALTS. ALUMINUM. WATER. OXIDIZERS.
HAZARDOUS DECOMPOSITION PRODUCTS	NONE

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY	ECOLOGY-GENERAL: NOT CLASSIFIED
PERSISTENCE AND DEGRABILITY	NOT ESTABLISHED
BIOACCUMULATIVE POTENTIAL	NOT ESTABLISHED
MOBILITY IN SOIL	NO ADDITIONAL INFORMATION AVAILABLE
OTHER INFORMATION	LIKE NU MANUFACTURING ACRYLIC SEALER BINDER MAY HAVE ADVERSE EFFECTS ON AQUATIC ORGANISMS IF RELEASED INTO WATER BODIES. AVOID DISCHARGE INTO WATERWAYS OR SEWERS.

SECTION 13: DISPOSAL CONSIDERATION**WASTE DISPOSAL RECOMMENDATIONS**

DISPOSE OF LIKE NU MANUFACTURING ACRYLIC SEALER BINDER IN ACCORDANCE WITH LOCAL REGULATIONS. DO NOT DISPOSE OF SOLUTION IN WATERWAYS OR SEWERS.

ADDITIONAL INFORMATION

CONTAINER MAY REMAIN HAZARDOUS WHEN EMPTY. CONTINUE TO OBSERVE ALL PRECAUTIONS.

WASTE MATERIALS

AVOID RELEASE TO THE ENVIRONMENT.

SECTION 14: TRANSPORT INFORMATION

LIKE NU MANUFACTURING ACRYLIC SEALER BINDER IS NOT REGULATED AS A HAZARDOUS MATERIAL FOR TRANSPORTATION UNDER DOT REGULATIONS.

SECTION 15: MANUFACTURING AND OTHER INFORMATION**MANUFACTURER
ADDRESS**

LIKE NU MANUFACTURING
26945 CABOT ROAD
SUITE 108

**CONTACT
WEBSITE**

LAGUNA HILLS, CA 92653
INFO@LIKENUMATERIALS.COM
WWW.LIKENUCONCRETE.COM

DISCLAIMER

THE INFORMATION PROVIDED IN THIS DATA SHEET IS FOR GENERAL GUIDANCE ONLY AND DOES NOT CONSTITUTE PROFESSIONAL ADVICE. USERS SHOULD CONDUCT THEIR OWN TESTING AND EVALUATION TO DETERMINE THE SUITABILITY OF LIKE NU FOR THEIR SPECIFIC APPLICATIONS. THE MANUFACTURER ASSUMES NO LIABILITY FOR THE USE OR MISUSE OF THIS PRODUCT. ALWAYS REFER TO THE PRODUCT'S TECHNICAL DATA SHEET AND SAFETY INFORMATION BEFORE USE. THIS SDS IS PROVIDED FOR INFORMATIONAL PURPOSES ONLY AND DOES NOT CONSTITUTE A WARRANTY OR GUARANTEE OF PRODUCT PERFORMANCE OR SAFETY.