Henry

Page 1 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING

#### 1. Product And Company Identification

<u>Supplier</u>

**HENRY COMPANY** 

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716

Company Contact: Technical Services Telephone Number: (800) 486-1278

Web Site: www.henry.com www.bakor.com

**Supplier Emergency Contacts & Phone Number** 

CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666 **Manufacturer** 

**HENRY COMPANY** 

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716

Company Contact: Technical Services Telephone Number: (800) 486-1278

Web Site: www.henry.com www.bakor.com

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666

Issue Date: 12/29/2011

Product Name: HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING

**Product Code: HE587** 

#### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
acrylic polymer blend	not avail.	10 - 20
aluminum trihydrate	21645-51-2	15 - 30
calcium carbonate	1317-65-3	10 - 20
chlorothalonil	1897-45-6	0.1 - 0.5
ethylene glycol	107-21-1	1 - 5
titanium dioxide	13463-67-7	5 - 10
water	7732-18-5	25 - 50

#### **EMERGENCY OVERVIEW**

CAUTION! Direct skin and eye contact may cause irritation. Ingestion may cause gastric distress. Inhalation may cause irritation to the respiratory tract.

Appearance/Odor: Creamy, white liquid, paint-like odor.

#### 3. Hazards Identification

#### Primary Routes(s) Of Entry

Inhalation

## **Eye Hazards**

May cause eye irritation (burning, tearing, redness or swelling).

#### **Skin Hazards**

None expected, however, prolonged contact may cause irritation.

#### **Ingestion Hazards**

May cause liver and kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.

Henry

Page 2 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING

#### 3. Hazards Identification - Continued

#### **Inhalation Hazards**

None expected, however, certain individuals may experience minor nausea or headaches.

## **Chronic/Carcinogenicity** Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

#### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

#### Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.

#### **Inhalation**

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Contact a physician if symptoms develop.

#### 5. Fire Fighting Measures

Flash Point: >212 °F

Flash Point Method: Setaflash Lower Explosive Limit: not available Upper Explosive Limit: not available

#### Fire And Explosion Hazards

Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen, oxygen, aluminium and zinc, including carbon monoxide.

#### **Extinguishing Media**

Carbon dioxide, water, water fog, dry chemical, chemical foam.

#### **Fire Fighting Instructions**

Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Firefighters should wear self-contained breathing apparatus and full protective gear.

#### 6. Accidental Release Measures

Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations. Avoid runoff to waterways and sewers.

#### 7. Handling And Storage

#### **Handling And Storage Precautions**

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from physical damage. Protect from extreme temperatures. Keep out of reach of children.

#### 8. Exposure Controls/Personal Protection

#### **Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Henry

Page 3 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING

#### 8. Exposure Controls/Personal Protection - Continued

#### **Eye/Face Protection**

Safety glasses with side shields or goggles recommended.

## **Skin Protection**

Use with chemical-protective gloves to prevent skin contact.

#### **Respiratory Protection**

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator. Respirator use may be required due to secondary operations such as mixing, spraying, sanding, buffing, etc.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

## Ingredient(s) - Exposure Limits

aluminum trihydrate

ACGIH TLV-TWA: 10 mg/m3 (as aluminum metal)

OSHA PEL-TWA: 15 mg/m3 (as aluminum metal) (total dust)
OSHA PEL-TWA: 5 mg/m3 (as aluminum metal) (respirable dust)

ethylene glycol

ACGIH TLV-CEILING 100 mg/m3

titanium dioxide

ACGIH TLV-TWA 10 mg/m3 (respirable) OSHA PEL-TWA 15 mg/m3 (total dust)

#### 9. Physical And Chemical Properties

#### **Appearance**

Creamy, white liquid

#### <u>Odor</u>

Paint-like odor

Chemical Type: Mixture
Physical State: Liquid
Boiling Point: 212 °F
Specific Gravity: 1.48

Vapor Pressure: 760@ 212°F Vapor Density: >1 pH Factor: 9.0-9.5

pH Factor: 9.0-9.5 Solubility: dispersible Evaporation Rate: <1

#### 10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

#### **Conditions To Avoid (Stability)**

Extreme temperatures

Henry

Page 4 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING

### 10. Stability And Reactivity - Continued

#### **Incompatible Materials**

Strong oxidzers, strong acids

## **Hazardous Decomposition Products**

Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, aluminum and zinc fumes and smoke may be produced.

### **Conditions To Avoid (Polymerization)**

none

#### 11. Toxicological Information

#### **Chronic/Carcinogenicity**

IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): titanium dioxide, chlorothalonil

Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

### **Miscellaneous Toxicological Information**

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

#### Ingredient(s) - Carcinogenicity

chlorothalonil

Listed In The IARC Monographs

#### Ingredient(s) - Toxicological Data

calcium carbonate

LD50 (oral-rat) : 6450 mg/kg

chlorothalonil

LD50 (oral-rat) - 4200 mg/kg

LD50 (dermal-rabbit) - >20,000 mg/kg

ethylene glycol

LD50 (oral, rat): 5.89 g/kg LD50 (dermal, rabbit): 9.5 g/kg

#### 12. Ecological Information

Do not allow into any sewer, on the ground, or into any body of water.

#### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

#### 14. Transport Information

Ground Not Restricted

IMDG Not Restricted

IATA Not Restricted

#### 15. Regulatory Information

### **SARA Hazard Classes**

Acute Health Hazard

Henry

Page 5 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF

### 15. Regulatory Information - Continued

#### Ingredient(s) - U.S. Regulatory Information

chlorothalonil

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical ethylene glycol

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

#### **State Regulations**

Warning: This product contains substances known to the state of California to cause cancer.

#### Ingredient(s) - State Regulations

calcium carbonate

Pennsylvania - Workplace Hazard

chlorothalonil

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

ethylene glycol

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

titanium dioxide

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

New York City - Hazardous Substance

## Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: D2A - Very Toxic

### Ingredient(s) - Canadian Regulatory Information

ethylene glycol

WHMIS - Ingredient Disclosure List


#### WHMIS - Canada (Pictograms)





Page 6 of 6

# HE587 - DURA-BRITE WHITE ELASTOMERIC ROOF COATING



16. Other Information

**Revision/Preparer Information** 

This MSDS Supersedes A Previous MSDS Dated: 01/07/2010

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### **HENRY COMPANY**

Printed Using MSDS Generator™ 2000