Safety Data Sheet



According to HCS-2012 APPENDIX D TO §1910.1200

Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

1. Identification	
(a) Product identifier	
Product name:	LITHIUM BATTERY
(b) Other means of ident	ification
Product description:	Model: CR2032
	Nominal Voltage: 3.0V
	Typical Capacity: 210mAh
	Lithium content: 0.063g
(c) Recommended use of	the chemical and restrictions on use
Recommended use:	No information available.
Restriction on use:	No information available.
(d) Details of the supplier	r of the product
Applicant's name:	SHENZHEN PKCELL BATTERY CO., LTD.
Applicant's address:	7th Floor, block B, Yicheng Huanzhi center, Renmin Road, Longhua District, Shenzhen,
	China.
Manufacturer's name:	SHENZHEN PKCELL BATTERY CO., LTD.
Manufacturer's address:	7th Floor, block B, Yicheng Huanzhi center, Renmin Road, Longhua District, Shenzhen,
	China.
E-mail:	2355701539@qq.com
Telephone:	+86-755-86670643
(e) Emergency phone number	
+86-755-86670643 🕕	

2. Hazard(s) identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

(b) GHS Label elements, including precautionary statements

Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

	Emergency Overview	
Signal word	Danger	
Hazard Statements		
Harmful if swallowed		
Harmful in contact with skin		
Causes severe skin burns and	d eye damage	
Suspected of causing cancer		
Causes damage to organs th	rough prolonged or repeated exposure	
This product is an article w	hich contains a chemical substance. Safety	information is given for exposure to t
	use of the product should not result in expos	
battery. In case of rupture:		
		6
A		
Appearance Silver Precautionary Statements -	Physical State Solid Prevention	Odor Odorless
Precautionary Statements - Obtain special instructions b Do not handle until all safety Use personal protective equi Wash face, hands and any ex Do not eat, drink or smoke w Do not breathe dust/fume/g Precautionary Statements - Immediately call a POISON C	Prevention efore use y precautions have been read and understood ipment as required kposed skin thoroughly after handling when using this product gas/mist/vapors/spray Response	Odor Odorless

Call a POISON CENTER or doctor/physician if you feel unwell Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation



Version: 2.0/EN

Product name: LITHIUM BATTERY

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician

Safety Data Sheet According to HCS-2012 APPENDIX D TO §1910.1200

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

(c) Hazards not otherwise classified (HNOC)

Not applicable

(d) Unknown Toxicity

14.4 % of the mixture consists of ingredient(s) of unknown toxicity

(e) Other information

Very toxic to aquatic life with long lasting effects

(f) Interactions with Other Chemicals

No information available.

3. Composition/information on ingredients

(a) Mixtures information

Chemical name	CAS No.	Concentration%
Lithium	7439-93-2	2.5
Manganese Dioxide	1313-13-9	36
Graphite	7782-42-5	3.5
Perchloric acid, lithium salt	7791-03-9	1.0
Ethylene glycol dimethy ether	110-71-4	6.0
Propylene carbonate	108-32-7	8.0
Iron	7439-89-6	29
Chromium	7440-47-3	10.5
Molybdenum	7439-98-7	1.0
Polypropylene	9003-07-0	2.5

4. First-aid measures



Issue date: 2021.03.30

nology



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

(a) Description of	first aid measures
General Advice	First aid is upon rupture of sealed battery.
Eye contact:	Show this safety data sheet to the doctor in attendance.
	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep
	eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue
	rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.
Skin contact:	Remove contaminated clothes and rinse the skin with plenty of water. Get medical advice /
	attention if you feel unwell.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained
	personnel should) give oxygen. Get medical advice / attention if you feel unwell.
Ingestion:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an
	unconscious person. Do NOT induce vomiting. Get medical aid.
Self-protection of	Ensure that medical personnel are aware of the material(s) involved, take precautions to
the first aider	protect themselves and prevent spread of contamination.
(h) Adapt in a set of	t summtame (affacts, south, and dalmund

(b) Most important symptoms/effects, acute and delayed

Contact with internal components may cause allergic skin sensitization (rash) and irritate eyes, skin, nose, throat, respiratory system. Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

(c) Immediate medical attention and special treatment

No information available.

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media:Use water or dry sand as appropriate.Unsuitable extinguishing media:No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filter mask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area, dispose the case after the batteries cool and vapors dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors.

(b) Environmental Precautions

Prevent material from contaminating soil and from entering sewers or waterways.

(c) Methods and materials for containment and cleaning up

If the battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

7. Handling and storage

(a) Precautions for safe handling

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries Use recommended charging time and current.

(b) Conditions for safe storage, including any incompatibilities

And recommended at $-5 \degree C \sim 45 \degree C$ for 1 month storage, at $-5 \degree C \sim 35 \degree C$ for 3 months storage. Do not storage the battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children.

8. Exposure controls/personal protection

a)Control parameters	A BASS		
xposure Guidelines			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium	N/A	NI/A	NI/A
7439-93-2	N/A	N/A	N/A



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

ACGIH TLV: American Conference of Governmental Industrial Hygienists -Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines: Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering Measures: 1.Showers 2.Eyewash stations 3.Ventilation systems

(c) Individual protection measures, such as personal protective equipment

Eye/Face Protection:	Not necessary under normal conditions, wear safety glasses if handling an open or
	leaking battery.
Skin and body Protection:	Not necessary under normal conditions, Wear protective gloves and protective
	clothing such as long sleeved clothing, impervious gloves, chemical resistant apron,
	and antistatic boots if handling an open or leaking battery.
Respiratory Protection:	Not necessary under normal conditions. If exposure limits are exceeded or irritation
	is experienced, ventilation and evacuation may be required.
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact
	with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat,
	drink, or smoke in work area. Maintain good housekeeping.

9. Physical and chemical properties

(a) Appearance	Silver Solid
(b) Odor	Odorless
(c) Odor threshold	No data available.
(d) pH	No data available.
(e) Melting point/freezing point	No data available.
(f) Initial boiling point and boiling range	No data available.
(g) Flash point	No data available.
(h) Evaporation rate	No data available.
(i) Flammability	No data available.
(j) Upper/lower flammability or explosive limits	No data available.
(k) Vapor pressure	No data available.
(I) Vapor density	No data available.
(m) Relative density	No data available.
(n) Solubility(ies)	Insoluble in water.
(o) Partition coefficient: n-octanol/water	No data available.
(p) Auto-ignition temperature	No data available.
(q) Decomposition temperature	No data available.
(r) Viscosity	No data available.



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies controlled release of pressure without ignition.

(d) Conditions to avoid

Do not subject the battery to mechanical shock. Keep away from open flames, high temperature.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Inhalation: Ingestion: Skin contact: Eve contact: Inhalation of a large number of vapors or fumes released due to heat may cause respiratory. Ingestion of battery contents may cause mouth, throat and intestinal burns and damage. Contact with battery electrolyte may cause burns and skin irritation.

Contact with battery electrolyte may cause burns. Eye damage is possible.

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity:	No data available.
Skin corrosion/irritation:	The liquid in the battery irritates.
Serious eye damage/irritation:	The liquid in the battery irritates.
Respiratory sensitization:	The liquid in the battery may cause sensitization to some person.
Skin sensitization:	The liquid in the battery may cause sensitization to some person.
Carcinogenicity:	Cobalt and Cobalt compounds are considered to be possible human
	carcinogen(s).
Germ Cell Mutagenicity:	No data available.
Reproductive Toxicity:	No data available.
STOT-Single Exposure:	No data available.
STOT-Repeated Exposure:	No data available.
Aspiration Hazard:	No data available.



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

(c) Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
Sensitization:	No data available.
Mutagenic Effects:	No data available.
Carcinogenicity:	No data available.
Reproductive Toxicity:	No data available.
Chronic Toxicity:	No data available.
Target Organ Effects:	No data available.
Aspiration Hazard:	No data available.

12. Ecological information

(a) Ecotoxicity

Water hazard class 1(Self-assessment): slightly hazardous for water.

(b) Persistence and Degradability

No information available.

(c) Bioaccumulative potential

No information available.

(d) Mobility in soil

No information available.

(e) Other adverse effects

No information available.

13. Disposal considerations

Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Ζυυδ

Local regulations may be more stringent than regional or national requirements.

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

The potential effects on the environment and human health of the substances used in batteries and accumulators; the desirability of not disposing of waste batteries and accumulators as unsorted municipal waste and of participating in their separate collection so as to facilitate treatment and recycling.

14. Transport information

Report No.: NCT21011157S1-1 TRF: SDS-V2



Version: 2.0/EN

Product name: LITHIUM BATTERY

Issue date: 2021.03.30

According to Section II/Section IB of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION 969 \sim 970 of the 2021 IATA Dangerous Goods regulations 62nd Edition and the special provision 188 of IMDG (inc Amdt 39-18). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

(a) UN number

- (b) UN Proper shipping name
- (c) Transport Hazard class(es)
- (d) Packing group (if applicable)
- (e) Marine pollutant (Yes/No)

(f) Transport in bulk (according to Annex II

- of MARPOL 73/78 and the IBC Code)
- (g) Special precautions

3090 or 3091

Lithium metal batteries or Lithium metal batteries contained in equipment or Lithium metal batteries packed with equipment Class 9 (PI968 Section IB) or N/A (PI968~970 Section II) II

No

No information available.

No information available.

15. Regulatory information

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air transport Association (IATA) Dangerous Goods Regulations.
- The International Maritime Dangerous Goods (IMDG) Code.
- The Office of Hazardous Materials Safety within the US Department of Transportation (DOT)
- Research and Special Programs Administration (RSPA)

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: 2015.04.29 Revision summary: The Second New SDS Date of this revision: 2019.01.01

(b) Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances
ENCS	Japanese Existing and New Chemical Substances

Page 9 of 10 Version Date : 2019-01-01



Version: 2.0/EN

Product name: LITHIUM BATTERY

ECL:

IECSC:

Existing Chemicals List, the Korean chemical inventory. Inventory of existing chemical substances in China.

(c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.



Issue date: 2021.03.30