SAFETY DATA SHEET



1. Identification

Product identifier KILZ® 2 All-Purpose Gray Primer

Other means of identification

Product number 2200

Recommended use **Architectural Coating**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Masterchem Industries LLC Supplier

> 3135 Old Highway M Imperial, MO 63052-2834

Telephone 636-942-2510 +1 760 476 3962 **Emergency telephone**

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Store away from incompatible materials. Storage

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Limestone	1317-65-3	10 - 30	
Titanium dioxide	13463-67-7	3 - 7	
Talc	14807-96-6	0.5 - 1.5	
Quartz (Crystalline silica)	14808-60-7	0.1 - 1	

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in **Composition comments**

percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

Communication Standard.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

SDS US 1/7 953554 Version #: 02 Revision date: 19-May-2020 Issue date: 02-April-2020

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Do not use water jet as an extinguisher, as this will spread the fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

.

SDS).

8. Exposure controls/personal protection

953554 Version #: 02 Revision date: 19-May-2020

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	туре	Value	
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

Issue date: 02-April-2020

Components	Туре	Value	Form
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Talc (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
ogical limit values	No biological exposure limits noted for the ingredient(s).		
ropriate engineering	Good general ventilation should be used. Ventilation rates should be matched to conditions. If		

Bio

Appropriate engineering

controls

applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Skin protection

Other Wear appropriate chemical resistant clothing.

If airborne concentrations are above the applicable exposure limits, use NIOSH approved Respiratory protection

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. **Physical state Form** Liquid.

SDS US KILZ® 2 All-Purpose Gray Primer

Color Gray. Odor Slight.

Odor threshold Not available.

7 - 10 рH

Not available. Melting point/freezing point > 99 °F (> 37.2 °C) Initial boiling point and boiling

range

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

50 - 140 KU at 25°C **Viscosity**

Other information

Density 10.78 lbs/gal **Explosive properties** Not explosive. Oxidizing properties Not oxidizing.

VOC 8 g/l (including water) (Material)

23 g/l (excluding water) (Coating)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Fluorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Prolonged skin contact may cause temporary irritation. Skin contact Eye contact Direct contact with eyes may cause temporary irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

KILZ® 2 All-Purpose Gray Primer SDS US 4/7 953554 Version #: 02 Revision date: 19-May-2020 Issue date: 02-April-2020

Components **Test Results Species**

Quartz (Crystalline silica) (CAS 14808-60-7)

Chronic Inhalation

LOEC Human 0.0563 mg/m3

Talc (CAS 14807-96-6)

Acute Oral

LD50 Rat > 5000 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Due to the form of the product, exposure to the potentially carcinogenic components is not Carcinogenicity

expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (Crystalline silica) (CAS 14808-60-7) 1 Carcinogenic to humans.

Talc (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Quartz (Crystalline silica) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Quartz (Crystalline silica) (CAS 14808-60-7) Cancer

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator.

Local disposal regulations Dispose in accordance with all applicable regulations. Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (Crystalline silica) (CAS 14808-60-7)

Cancer lung effects

immune system effects

kidney effects

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Limestone (CAS 1317-65-3)

Quartz (Crystalline silica) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Limestone (CAS 1317-65-3)

KILZ® 2 All-Purpose Gray Primer SDS US 953554 Version #: 02 Revision date: 19-May-2020 6/7 Issue date: 02-April-2020

Quartz (Crystalline silica) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Limestone (CAS 1317-65-3)

Quartz (Crystalline silica) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Limestone (CAS 1317-65-3)

Quartz (Crystalline silica) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 02-April-2020 **Revision date** 19-May-2020

Version # 02

HMIS® is a registered trade and service mark of the ACA. **Further information**

Health: 0 **HMIS®** ratings

Flammability: 0 Physical hazard: 0

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

LOEC: Lowest observable effect concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.

HSDB® - Hazardous Substances Data Bank References

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Masterchem Industries LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

953554 Version #: 02 Revision date: 19-May-2020 7/7 Issue date: 02-April-2020