
DDERN FORMS





PRODUCT DESCRIPTION

With sturdy blades crafted from solid wood- properly treated to weather the outdoors- this smart fan is rugged refinement to the core. Take control of it with our exclusive Modern Forms app-features like Adaptive Learning make life easier every day by suggesting optimized schedules, while a powerful DC motor inside keeps things running smooth, quiet and up to 70% more efficient than traditional AC fans. Choose a bronze housing with dark walnut wood, matte black with distressed koa or graphite with weathered gray.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Optional LED light kit included
- Includes BT wall control
- Optional remote control sold separately
- Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 7690/10546 Weighted-Average/High Energy Use (W): 34/51 **Estimated Yearly Energy Cost (\$):** 10 Weighted-Average/High Efficiency (CFM/W): 227/310 Max RPM: 145

ORDER NUMBER

Model	Hous	sing	Blade	Blade				
FR-W1814-72L	BZ	Bronze	DW	Dark Walnut				
	GH	Graphite	WG	Weathered Gray				
	MB	Matte Black	DK	Distressed Koa				

SPECIFICATIONS

Construction: Aluminum, Balsa Wood 15° Pitch, 72" sweep Blade: 3/4"W X 4.5H Downrod: **Mounting Slope:** Up to 30° 80"

Hanging Weight: 20 lbs **Total Power:** 60W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20

125 x 25 sensorless DC motor **Motor Type:**

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* **Bluetooth Range:** Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source: LED **Light Wattage:** 20W Lumens/Delivered Lumens: 1600/846 Dimming: Integrated CRI:

Color Temperature: 3000K (2700K/3500K options available)

Rated Life: 50,000 hours

Example: FR-W1814-72L-GH/WG

For 2700K add "-27"; for 3500K add "-35" before the finish: FR-W1814-72L27GHWG

*Results may vary based on application and surroundings.

*This fan comes uni-pack - blade select options are not available

The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

72" Ceiling Fan

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	**************************************	F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	0	XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire