

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Waterproofing with PTEF

Product Code: 819XX

Intended Use of the Product

Waterproofing

Name, Address, and Telephone of the Responsible Party

Company

Star brite Inc.

4041 SW 47th Avenue

Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 4 H227

Asp. Tox. 1 H304

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS08

Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H227 - Combustible liquid

H304 - May be fatal if swallowed and enters airways

Precautionary Statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.

P280 - Wear eye protection, protective gloves, protective clothing.

P301+P310 - If swallowed: Immediately call a poison center/doctor.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish.

P403+P235+P405 - Store in a well-ventilated place. Keep cool. Store locked up.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Aquatic Acute 2

Aquatic Chronic 3

H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

Unknown Acute Toxicity (GHS-US) Not available

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8 (EC No) 926-141-6	60 - 100	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Solvent naphtha, petroleum, medium aliphatic	(CAS No) 64742-88-7	3 - 7	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 3, H402 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: May be fatal if swallowed and enters airways.

Inhalation: May cause drowsiness or dizziness.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible liquid.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with (strong) oxidizers: (increased) risk of fire.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Silicon oxides. Nitrogen compounds.

Reference to Other Sections Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid all contact with skin, eyes, or clothing. Do NOT breathe (vapor, mist, gas).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources. Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters. Dangerous due to potential toxicity for the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

Reference to Other Sections See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s) Waterproofing

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures)
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)		
USA ACGIH	TLV	Not applicable
USA OSHA	PEL	Not applicable
USA NIOSH	REL	Not applicable
USA NIOSH	IDLH	Not applicable

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Use explosion-proof equipment. Take precautionary measures against static discharges. Gas detectors should be used when flammable gases/vapours may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Clear to amber liquid

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: Petroleum
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting/Freezing Point	: - 70 °C (- 94 °F)
Boiling Point	: 149 - 204.5 °C (300.2 - 400.1 °F)
Flash Point	: 62.5 °C (144.5 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density/Specific Gravity	: 0.78 (water = 1)
Solubility	: Insoluble in water.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

- Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire.
- Chemical Stability:** Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.
- Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.
- Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.
- Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Nitrogen compounds. Silicon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

- Acute Toxicity:** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Not classified
- Serious Eye Damage/Irritation:** Not classified
- Respiratory or Skin Sensitization:** Not classified
- Germ Cell Mutagenicity:** Not classified
- Teratogenicity:** Not available
- Carcinogenicity:** Not classified
- Specific Target Organ Toxicity (Repeated Exposure):** Not classified
- Reproductive Toxicity:** Not classified
- Specific Target Organ Toxicity (Single Exposure):** Not classified
- Aspiration Hazard:** May be fatal if swallowed and enters airways.
- Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness.
- Symptoms/Injuries After Skin Contact:** May cause skin irritation.
- Symptoms/Injuries After Eye Contact:** May cause eye irritation.
- Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.
- Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC50 Inhalation Rat (mg/l)	> 5.2 mg/l/4h
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat (mg/l)	> 5.28 mg/l/4h
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LC50 Fish 1	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	450 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)

Persistence and Degradability

Waterproofing with PTEF	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Waterproofing with PTEF	
Bioaccumulative Potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
BCF fish 1	(bioaccumulation expected)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number

DOT NA no.	: NA1993
UN-No. (TDG)	: Not regulated
UN-No. (IMDG)	: Not regulated
UN-No. (IATA)	: Not regulated

UN Proper Shipping Name

Proper Shipping Name (DOT)	: COMBUSTIBLE LIQUID, N.O.S. (Petroleum Distillates)
Transport Document Description (DOT)	: NA1993 COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM DISTILLATES), 3, III
Transport Document Description (ADR) (IMDG/IATA)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Petroleum Distillates), 9, III

Transport Hazard Class(es)

Department Of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
DOT Symbols	: D - Proper shipping name for domestic use only, G - Identifies PSN requiring a technical name

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing Group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 Cfr 173.xxx)	: 150
DOT Packaging Non Bulk (49 Cfr 173.xxx)	: 203
DOT Packaging Bulk (49 Cfr 173.xxx)	: 241
TDG Special Provisions	: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".
Explosive Limit And Limited Quantity Index	: 5
Marine Pollutant	: No
<u>Additional Information</u>	
Emergency Response Guide (ERG) Number	: 128
Other Information	: This product meets the limited quantity exceptions as follows:DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the above descriptions apply.

Transport by sea

Dot Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Marine Pollutant	: No

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75)	: 220 L

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Waterproofing with PTEF	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard

Waterproofing with PTEF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Waterproofing with PTEF

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Very toxic material causing other toxic effects
----------------------	---



Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATA ON DATE OF PREPARATION OR LAST REVISION

Revision date : 04/23/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness

Waterproofing with PTEF

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H371	May cause damage to organs
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA Fire Hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS