WHAT GRADE OF QUALITY ARE NORSK-STOR™ MULTI-PURPOSE TILES? Norsk-Stor™ mats are made from the highest quality raw materials available. This includes the use of virgin materials where appropriate and quality control processes not used by any other manufacturers. Our state of the art manufacturing capabilities allow us to maintain tolerances that others cannot duplicate. As a result, Norsk-Stor™ are the highest quality products available in the market today.

WHAT SIZE ARE THE TILES AND HOW MUCH AREA DOES A BOX COVER? Tile Size = 18.3° x 18.3° x .250° = 2.32 sq. ft. Package Sizes -6 pack box = 13.95 sq. ft. -20 pack box = 46.4 sq. ft.

WHAT FLOOR DESIGNS ARE AVAILABLE?

Raised Diamond, Raised Coin, Vented Tile, and Sport Mat with Rhino-tec™ finish.



WHAT COLORS ARE AVAILABLE?

	RAISED DIAMOND	RAISED COIN	VENTED TILE	SPORT MAT
Black	•	•	•	•
Dove Gray	•	•	•	•
Metallic Pewter	•			
Metallic Graphite	•			
Beige		•	•	
White		•		
Blue		•		
Red		•		
Yellow		•		
Green		•		

Actual product color may be different from samples shown on sales material.





MULTI-PURPOSE FLOORING

Warranty Statement:

- 1.Norsk-Stor™ Tile Flooring products are warranted to the original purchaser to be free from defects in material and workmanship for a period of 10 years from the date of the original retail purchase. The word "defect" is defined as imperfections that impair the use of the product. Defects resulting from misuse, abuse or negligence will void this warranty. This warranty does not cover defects due to alteration or accident. This warranty does not cover damage caused by vandalism or "acts of nature" or any other event beyond the control of the manufacturer.
- 2. This warranty is non-transferable and is expressly limited to the repair or replacement of defective products. All defective products are to be returned to the Retailer where they were originally purchased and are to be subjected to that specific Retailer's return merchandise policy and agreement on file with The Parallax Group International., LLC.
- 3.This warranty does not cover scratching, scuffing, tearing, cosmetic damage, or other wear and tear resulting from normal use of the product. In addition, any damage resulting from intentional damage, negligence, or unreasonable use will void this warranty.
- 4.Liability for incidental or consequential damages is excluded to the extent permitted by law. While every attempt is made to embody the highest degree of safety in all products, freedom from injury cannot be guaranteed. The user assumes all risk of injury resulting from the use of this product. The purchaser should pay special attention to all codes, laws, specifications and ratings for products specifically used in play areas, playgrounds, and other recreational uses where the safety of children and others are concerned. The user assumes all risk of injury resulting from the use of this product. All merchandise is sold on this condition, and no representative of the company may waive or change this policy.
- 5.This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability or fitness for use. Neither The Parallax Group International., LLC or any representative assumes any other liability in connection with this product.



MULTI-PURPOSE FLOORING



WHAT APPLICATIONS IS THIS PRODUCT DESIGNED

FOR? Norsk-Stor[™] floor tiles are designed for commercial/residential use in garages, workshops, showrooms, warehouses, retail stores, commercial / home gyms, churches, schools, hospitals, offices, aircraft hangars.



CAN YOU PARK YOUR CAR ON THE TILES? Yes — our Multi-Purpose flooring is specifically designed to support the weight of automobiles and other heavy objects. The structural integrity is derived from our patent pending design.



WHAT TOOLS ARE NEEDED FOR INSTALLATION?

No special tools are required. A soft mallet is recommended to tap the tiles in place. A utility knife makes cutting around objects much easier.



ARE THE FLOOR TILES RESISTANT TO LIQUID SPILLS? Norsk-Stor™ floor tiles are resistant to most solvents and chemicals. Patented AirDry™ design allows trapped moisture to flow from underneath and evaporate.



IS THERE ANY SPECIAL PREP WORK REQUIRED?

Sweeping or mopping floor prior to installation is recommended. Interlocking floor tiles made from Flexible PVC or similar materials typically get harder to install in cold weather conditions. Therefore, it is recommended that both the floor, and floor tile be kept at approximately 60° to 70° F for 24 to 48 hours prior to, and during the installation.

HOW DO YOU FINISH THE EDGES OF THE TILE?

Finished edging is compatible with ALL Norsk-Stor™ Multi-Purpose flooring products. Trim Kits are available in Gray, Black, Blue, Beige and Metallic Graphite. Each Kit includes (4) Corners and (14) connector pieces.



DOES THE FLOOR HAVE ANTI-FATIGUE AND ANTI-SLIP PROPERTIES? Good anti-slip and fatigue relieving properties, improving safety and productivity.

DOES THIS FLOOR PROVIDE INSULATION?

Norsk-Stor™ floor tiles provide excellent thermal and acoustic insulation.

CAN WE REPLACE TILES THAT ARE WORN OR DAMAGED OR TO CHANGE COLOR PATTERNS?

Norsk-Stor™ tiles provide the ultimate flexibility, allowing you to access and replace tiles in any part of the floor without having to pull up a section or the entire floor.



PRODUCT? Clean with a damp mop or cloth using mild soap/detergent and water.

CAN THE TILES BE USED OUTDOORS?

Norsk-Stor™ tiles are not designed for permanent outdoor use. Avoid prolonged sun exposure to prevent color fading. Only tiles with UV inhibitor are designated for outside use.

IS THERE ANY LATEX CONTAINED IN THIS PRODUCT? No there is no latex.

ARE THESE TILES RATED FOR CHILDREN'S PLAY AREAS? The purchaser should pay special attention to all codes, laws, specifications and ratings for products specifically used in play areas, playgrounds, and other recreational uses where the safety of children and others are concerned. This product is not rated for outdoor playground use.

THE FIRE MARSHAL IS REQUIRING ME TO VERIFY THE FIRE RATING FOR THIS PRODUCT - CAN YOU PROVIDE THAT INFORMATION?

The fire ratings are as follows:

TECHNICAL SPECIFICATION	STANDARD	UNIT OF MEASUREMENT	MULTI-PURPOSE FLOORING
Flame Spread	DIN51960	A/NFPA 235 1995 Critical Rad Flux	Class 1
Fire Resistance	NSI/ASTM E648 979	Ohms	Class 1

CAN THIS PRODUCT BE USED UNDER OR AROUND EXERCISE EQUIPMENT? This product is ideal for commercial and home gyms. Added protection is recommended in free weight lifting areas using our thicker Norsk-Sport™ gym flooring.



I'M CONCERNED ABOUT ALLERGIES WITH MY
CHILDREN – WHAT IS THE MULTI-PURPOSE
FLOORING MADE OF? Raw material composition
consists of a proprietary blend of PVC and other
polymers to provide specific performance characteristics.

IS THIS PRODUCT SAFE FOR CHILDREN?

This product has been tested using standard child safety testing for children's toys.

ASTM 963-96a
Title16 CFR part 1500.50
Standard Safety Protection for Children's products.