



CEMENT & CONCRETE PRODUCTS™

CONCRETE REPAIR

PRODUCT NOS. 8620-10, -13

PRODUCT DESCRIPTION

QUIKRETE® Concrete Repair is a superior acrylic latex formulation for crack repair in concrete, including concrete, stucco or masonry walls, sidewalks, patios and driveways.

PRODUCT USE

QUIKRETE® Concrete Repair fills and repairs cracks up to ½" (13 mm) wide in concrete, masonry, stucco, sidewalks, patios and driveways. Benefits include:

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

SIZES

• QUIKRETE® Concrete Repair is available in 5.5-fl.oz. (163 ml) squeeze tubes and 10-fl.oz. (296 ml) standard caulking tubes

YIELD

- 5.5-fl.oz (163 ml) tubes will yield about 12 linear feet (3.7 M) at a ¼" (6 mm) diameter bead
- 10.1-fl.oz (296 ml) tubes will yield about 24 linear feet (7.3 M) at a ¼" (6 mm) diameter bead or 12 linear feet (3.7 M) for a 3/8" (9mm) diameter bead

INSTALLATION

SURFACE PREPARATION

Clean all loose dirt, dust and gravel from the crack. Surfaces to receive Concrete Repair should be dry and free of oil and grease.

APPLICATION

- (1) Cut tip of spout on angle to make a ¼" (6 mm) to 3/8" (9 mm) hole.
- (2) Use cartridge in standard caulking gun. Apply by pushing cartridge tip over surface and forcing bead of Concrete Repair deep into the crack. Apply no thicker than 3/8" (9 mm) at a time. On horizontal surfaces, deep cracks can be partially filled with sand prior to application.
- (3) Concrete Repair can be tooled to smooth the surface.

DIVISION 3

Concrete Materials &
Methods 03 05 00



- (4) Excess Concrete Repair can be wiped off with a damp cloth.
- (5) Wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F (4°C) for proper application.
- (6) Do not apply if rain threatens or is predicted within 12 hours

PRECAUTIONS

Do not use to fill control / expansion joints. Do not use for structural repairs. For horizontal structural repairs, use QUIKRETE Polyurethane Self-Leveling Sealant (#8660-10). For vertical & overhead repairs, use QUIKRETE Polyurethane Non-Sag Sealant (#8660-11). May cause eye, skin and respiratory irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Use only with adequate ventilation. Ingestion may cause irritation. Store between 35 °F (2°C) and 100 °F (38°C). Do not apply where temperatures may reach 140°F (60°C) or higher (fireplaces, electric wires, etc.)

WARRANTY

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing. This limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Rd., NE, Suite 1300, Atlanta, GA 30305
(404) 634-9100 • Fax: (404) 842-1425

* Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications