

FOR EXTERIOR USE ONLY

PLEASE READ ENTIRE LABEL.

HENRY #201 FIBERED BLACK ROOF COATING is a premium cold-applied, brush or spray-grade solvent based asphalt roof coating. It is a penetrating protective coating formulated to provide a tough, durable, weather-resistant film to protect existing roofs in good condition. The solvent system allows working at lower temperatures than with asphalt emulsions, and the coating won't wash off if unexpected drizzle occurs before curing. Complies with ASTM D-4479, Type I.

NOTE: Formulated for low slope surfaces. In hot weather, exposed product may flow on sloped surfaces. May not be used on surfaces that experience ponding water. Ponding water is defined as water remaining on a roof surface 48 hours after rain has stopped.

CLEAN: Surface must be clean and dry, free of moisture both on and beneath the surface. Scrape off and remove gravel to provide a smooth surface. Remove rust and scale from metal by wire brushing. Sweep roof thoroughly to remove all dust and dirt. Carefully inspect area to be coated, including around pipes, chimneys, equipment, roof edges and walls. Repair all cracks, breaks, splits and holes by embedding Henry #195 Polyester Fabric or #183 Roof Repair Fabric between 2 heavy coats of Henry #204® Plastic Roof Cement, #505 FlashMaster™ Flashing Cement or #906 FlashMaster™ Plus Wet or Dry Flashing Cement applied over and at least 2 inches beyond repair. Note: Seal leaks before Henry #201 is applied!

APPLY: Stir coating thoroughly. Do not thin. Apply a single coat over the entire surface with a roofing brush or heavy duty spray equipment. In cold weather, store coating in a warm room overnight before using. **DO NOT HEAT CONTAINER.** Coating should soak into and not flood the surface. Flooding of surface can cause run-off of the coating in hot weather.

COVERAGE: 100 sq. ft. per 1 1/2 to 2 gallons. Do not over-apply.

WARNING! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F (43°C). **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED. If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. In case of accidental injection by power spray equipment, **GET MEDICAL ATTENTION IMMEDIATELY!**

USE ONLY WITH ADEQUATE VENTILATION! Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN.

1. Clean



2. Repair



3. Stir



4. Apply



PRECAUTIONS: Do not apply if there is a threat of rain within 24-48 hours after application. Application over hot applied asphalt may not prevent alligating of underlying asphalt flood or glaze coat. Do not apply over damp or wet surfaces. Coating tends to soften in hot weather. Do not walk on roof after coating in order to avoid tracking. Do not apply on roofs with a slope greater than 2" in 12". When transporting, make sure the pail is secured and the lid is tight to prevent spills. Allow to cure 3 to 4 months before applying a reflective fibered aluminum coating. **DO NOT USE** with saturated felts. **DO NOT USE** with solvent sensitive insulation, wood shingles of any kind or wood flashings. This coating is not recommended over gravel, rubber or PVC sheet roofing, shingles of any kind, or old roofs that are too dry and brittle to withstand the shrinkage stresses that occur after the application of any coating. The usual age limit for roofs to be coated is 7 to 10 years, but this varies with condition of the roofing.

CLEAN-UP: Remove coating from tools, etc., with kerosene, paint thinner or mineral spirits. Clean hands with waterless hand cleaner.

WARNING: This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Obtain a Material Safety Data Sheet (MSDS) from your supplier or Henry.

NOTE: Asphalt-based coatings form a water soluble residue as they weather. In areas without regular rainfall, the roof should be hosed off occasionally to prevent build up and discoloration (removable with soap and water). Areas that pond water may accumulate more asphalt residue.

Useful Tools

