



#### 1. COMPANY AND PRODUCT IDENTIFICATION

**Duncan Enterprises** 5673 East Shields Avenue Fresno, CA 93727 559-291-4444 559-291-9444 (Fax) www.duncan.com

www.mycolorshot.com

**EMERGENCY TELEPHONE NUMBERS** 

**Health Emergencies:** 

559-291-4444 7:00 am - 3:30 pm Pacific Std. Time

Spill and Off-Hour Health Emergencies:

800-424-9300 U.S. and Canada

703-527-3887 Outside U.S. and Canada (Collect)

**Product Name: COLORSHOT® Premium Spray Paint - Clear Sealer** 

**Product Description:** Matte and gloss finishes

**Product Use / Restrictions:** Suitable for wood, metal, plastic, and crafts. Carefully read and

follow all label warnings and all sections of SDS.

#### 2. HAZARDS IDENTIFICATION

Classification (GHS):	Flammable Aerosol 2	
Classification (GHS):		
	Gases Under Pressure – Compressed gas	
Health & Physical Hazard	Flammable Aerosol	
Statement(s):	Contains gas under pressure; may explode if heated.	
Other Hazards not	No additional information available.	
classified:		
Signal Word:	Warning	
Precautionary	Keep away from heat, hot surfaces, open flames, sparks – No smoking.	
Statement(s):	Do not spray on an open flame or other ignition source.	
, ,	Pressurized container: Do not pierce or burn, even after use.	
	Store in a well-ventilated place.	
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Pictogram(s) by GHS:		

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Detailed formulation is submitted by the client and it is proprietary information.

Reportable ingredients (if applicable):

Identity/Synonym	CAS Number:	Percentage/Range*:
n-Butyl acetate	123-86-4	10-20%
Ethyl acetate	141-78-6	5-10%
Acetone	67-64-1	1-5%

<sup>\*</sup>The exact percentage (concentration) of composition is withheld as a trade secret.

#### 4. FIRST AID MEASURES

On Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
On Skin Contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
On Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
On Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel.





	Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.	
Acute/Delayed Symptoms:	Inhalation: May cause respiratory tract irritation.	
	<b>Skin contact:</b> May cause skin irritation. Symptoms may include redness, drying, and cracking of the skin.	
	<b>Eye contact:</b> May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
	<b>Ingestion:</b> May be harmful if swallowed. May cause stomach distress, nausea or vomiting.	
Medical Advice:	Symptoms may not appear immediately. Treat symptomatically.	
Note to Physician:	No additional information available.	

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media		
Suitable extinguishing	Use extinguishing measures appropriate to surrounding material and environment.	
media:		
Unsuitable extinguishing	None known.	
media:		
Protection of Firefighters		
Specific hazards arising	Flammable aerosol. Products of combustion may include, and are not limited to: oxides	
from the chemical:	of carbon. Heat may build pressure, rupturing closed containers, spreading fire and	
	increasing rise of burns and injuries.	
Special procedures/	DO NOT fight fire when fire reaches explosives. Evacuate area. Use water spray or	
equipment for firefighters:	fog for cooling exposed containers. Keep upwind of fire. Wear full firefighting turn-out	
	gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than	
	air and may travel along the ground to a distant ignition source and flash back.	
Hazardous combustion	Products of combustion may include, and are not limited to: oxides of carbon.	
Products:		

#### **6. ACCIDENTAL RELEASE MEASURES**

General measures:	Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.	
Emergency Containment	Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand,	
procedures:	vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter	
-	waterways. Use appropriate Personal Protective Equipment (PPE).	
Environmental Precautions,	No additional information available.	
if any:		
Methods for Cleaning Up:	Scoop up material and place in a disposal container. Provide ventilation.	
Personal Protective	Use personal protection recommend in Section 8.	
Equipment:		

#### 7. HANDLING AND STORAGE

Safe Storage:		
	tightly closed. Do not expose to temperatures exceeding 50°C/ 122°F. Keep in fireproof place. Store away from direct sunlight or other heat sources.	
Safe Handling:		
	flame or other ignition source.	



## COLORSHOT PREMIUM Spray Paint

## **Safety Data Sheet**

Additional hazards when	Hazardous waste due to potential risk of explosion. Pressurized container. Do not
	pierce or burn, even after use.
measures:	Proper grounding procedures to avoid static electricity should be followed.

#### 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

**Occupational Exposure Limits:** 

Chemical name	ACGIH TLV	<u>US IDLH</u>	OSHA PEL	NIOSH REL
n-Butyl acetate	TWA 50 ppm,	1700 ppm (10%	TWA 710 mg/m <sup>3</sup> ,	TWA 710 mg/m <sup>3</sup> , 150 ppm,
	STEL 150 ppm	LEL)	150 ppm	STEL 950 mg/m <sup>3</sup> , 200 ppm
Ethyl acetate	TWA 400 ppm	2000 ppm (10%	TWA 1400 mg/m <sup>3</sup> ,	TWA 1400 mg/m <sup>3</sup> , 400 ppm
·		LEL)	400 ppm	-
Acetone	TWA 250 ppm, STEL 500	2500 ppm (10%	TWA 2400 mg/m <sup>3</sup> ,	TWA 590 mg/m <sup>3</sup> , 250 pppm
	ppm	LEL)	1000 ppm	

<u>Appropriate Engineering Controls:</u> Individual Protection measures, such as PPE (Personal Protective Equipment): Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protection Equipment:	
Respiratory Protection:	In case of insufficient ventilation, wear suitable respiratory equipment. Respirator section must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eye Protection:	Safety glasses or goggles are recommended when using the product.
Hand Protection:	Wear suitable gloves.
Skin Protection:	Wear suitable protective clothing.
General Safety and Hygiene	Do not eat, smoke or drink where material is handled, processed or stored. Wash
Measures:	hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State/Appearance:	Liquid
Color:	Clear
Odor:	Aerosol
Odor Threshold:	No data available.
pH:	No data available.
Boiling Point/Range:	75-110°C / 167-230°F
Melting Point/Range:	No data available.
Flash Point:	> 90°C / 194°F
Evaporation Rate:	No data available.
Vapor Density:	No data available.
Solubility(ies):	No data available.
Vapor Pressure:	No data available.
Relative Density:	No data available.
Specific Gravity (Water=1):	0.8
Viscosity:	No data available.
Partition Coefficient	No data available.
(n-octanol/water), if	
applicable:	
Explosive Properties:	No data available.
Flammability: (Solid, gas)	Flammable aerosol.
Flammability Limit in Air:	No data available.





Upper/Lower	
Autoignition temperature:	No data available.
Decomposition temperature:	No data available.

#### 10. STABILITY AND REACTIVITY

Chemical Stability:	No dangerous reaction known under conditions of normal use.  Stable under normal storage conditions. Flammable aerosol. Contents under pressure.  Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.	
Conditions to Avoid:	Heat. Sparks. Open flame. Direct sunlight.	
Incompatible Materials:	Oxidizing agents.	
Hazardous Decomposition	May include, and are not limited to: oxides of carbon.	
Products:		
Possibility of Hazardous	No dangerous reaction known under conditions of normal use.	
Reactions/Polymerization:		

#### 11. TOXICOLOGICAL INFORMATION

Information on	likely routes	of exposure:
----------------	---------------	--------------

0.1	N		
Skin corrosion/irritation:	Not classified.		
Serious eye	Not classified.		
damage/irritation:			
Respiratory or skin	Not classified.		
sensitization:			
Symptoms of exposure:	Likely routes of exposu	ure: ingestion, inhalation,	skin and eye.
	Inhalation: May cause	respiratory tract irritation.	
	Skin contact: May caus	se skin irritation. Symptom	ns may include redness, drying,
	defatting and cracking of	f the skin.	,
	Eye contact: May caus	e eye irritation. Symptoms	may include discomfort or pain,
		production, with possible	
	Ingestion: May be harn	nful if swallowed. May cau	se stomach distress, nausea or
	vomiting.	·	
Information on toxicological	No additional information available.		
effects:			
Germ Cell Mutagenicity:	Not classified.		
Carcinogenicity:	Not classified.		
Specific target organ toxicity	Not classified.		
(single exposure):			
Specific target organ toxicity	Not classified.		
(repeated exposure):			
Chemicals listed on NTP,	No listed chemicals.		
IARC or OSHA as a			
Carcinogen:			
Chemical Name:	Oral LD50	Dermal LD50.	Inhalation LC50
n-Butyl acetate	10768 mg/kg rat	> 17600 mg/kg rabbit	390 ppm/4h rat
Ethyl acetate	5620 mg/kg rat	> 18000 mg/kg	-
Acetone	5800 mg/kg rat	> 15700 mg/kg rabbit	50100 mg/m <sup>3</sup> (exposure time: 8 h) rat

<sup>\*</sup>Estimates for product may be based on additional component data not shown.

#### 12. ECOLOGICAL INFORMATION (NON-MANDATORY)

Ecology-general: May cause long-term adverse effects in the aquatic environment.



# COLORSHOT. PREMIUM Spray Paint

## **Safety Data Sheet**

Chemical Name:	LC50 fish 1	LC50 fish 2	EC50 Daphnia 1	EC50 Daphnia 2
n-Butyl acetate	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	-	-
Ethyl acetate	220 - 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	-
Acetone	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	12600 - 12700 mg/l (Exposure time: 48 h Species: Daphnia magna)

Persistence and degradability: Not established

Bioaccumulative potential:

Chemical Name:	Partition coefficient n-octanol/water	BCF fish 1	
n-Butyl acetate	1.81 (at 23°C)	-	
Ethyl acetate	0.6	30	
Acetone	-0.24	0.69	
Maria 1994 A. D. Maria dell'Original Cofensional Communication (Communication)			

Mobility in soil: No additional information available.

Other adverse effects: No additional known effects from this product.

#### 13. DISPOSAL CONSIDERATIONS (NON-MANDATORY)

Disposal instructions:	This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible. Container under pressure. Do not drill or burn even after use
Local disposal regulations:	See above.
EPA waste code(s):	No data.
Additional information:	Flammable vapors may accumulate in the container.

#### 14. TRANSPORTATION INFORMATION (NON-MANDATORY)

	<u>DOT</u>	IMD	G	<u>IATA</u>
UN/ID number:	UN 1950	-		-
Proper shipping name:	Aerosols	-		-
Transport hazard class:	2.1	-		-
Packing group (if applicable):	No applicable.	-		-
Environmental Provisions:	No data.	-		-
Special Precautions in transport:	data availab	le.		
Transport in bulk according to Annex II of MARPOL		No data.		
73/78 and IBC Code				
Emergency Response Guide Number: No data.		EmS-No:	No data.	

Pictograms

<u>US:</u>	<u>IATA; IMDG:</u>	Marine Pollutant:
	-	-
FLAMMABLE LIQUID		
3		





#### 15. REGULATORY INFORMATION (NON-MANDATORY)

US Federal Regulations:		
TSCA Section 12(b) Export	All components of this product are listed, or excluded from listing, on the United	
Notification (40 CFR 707,	States Environmental Protection Agency Toxic Substances Control Act (TSCA)	
Subpt. D):	inventory according to the Hazard Communication Standard (DFR29 1910.1200)	
• •	HazCom 2012.	
CERCLA (Superfund)	n-Butyl acetate: 5000 lb., listed under Butyl acetate.	
reportable quantity (lbs.) (40	Ethyl acetate: 5000 lb.	
CFR 302.4)	Acetone: 5000 lb.	
Toxicological Review:	Our products certified by a nationally recognized toxicologist to contain no materials in	
	sufficient quantities to be toxic, cause injury, acute or chronic health problems to	
	humans. Products are labeled in accordance with all applicable state and federal	
	regulations including, but not limited to consumer product safety standards.	
	State Regulations	
California Proposition 65	This product contains the following chemicals that are known to the State of California	
Warning:	to cause cancer, birth defects, or other reproductive harm: Contains a trace amount of	
	titanium dioxide; does not require product labeling under the provisions of CA Prop 65.	
Right to Know Listings		
n-Butvl acetate		

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. -Pennsylvania - RTK (Right to Know) List

#### **Ethyl acetate**

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. -Pennsylvania - RTK (Right to Know) List

#### **Acetone**

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. -Pennsylvania - RTK (Right to Know) List

Unless a concentration is specified in Section 2 of the SDS, the above chemicals(s) are present in trace amounts.





#### 16. OTHER INFORMATION

The recommendations and information contained in this SDS are compiled from sources believed to represent the most current information available when the SDS was prepared. However, the manufacturer / distributor of this product does not provide any warranty, guaranty of representation as to the correctness or sufficiency of this information. If this material is used in large amounts and/or an unusual manner, the user is obliged to determine what safety measures are appropriate, including the applicable and relevant workplace and environmental

Table of Abbreviations				
ACGIH:	American Conference of Governmental Industrial Hygienists	LD:	Lethal Dose	
ANSI:	American National Standards Institute	MARPOL:	Marine Pollution	
ASTM:	American Society for Testing Materials	mg / kg:	Milligram per Kilogram	
°C:	Degrees Centigrade	mm:	Millimeter	
CAA:	Clean Air Act	MSHA:	Mine Safety and Health Administration	
CAS:	Chemical Abstract Service	N/A:	Not Applicable	
CERCLA:	Comprehensive Environmental Response, Compensation & Liability Act	NFPA:	National Fire Protections Association	
CFR:	Code of Federal Regulations	NIOSH:	National Institute for Occupational Safety and Health	
CPR:	Controlled Products Regulations	NTP	National Toxicology Program	
DEA:	Drug Enforcement Act	OEL:	Over Exposure Limit	
DOT:	Department of Transportation	OSHA:	Occupational Safety and Health Administration	
DSL:	Canadian Domestic Substances List	PEL:	Permissible Exposure Limits	
EmS:	Emergency Medical Goods Services	ppm	Parts Per Million	
EPA:	Environmental Protection Agency	SARA	Superfund Amendment and Reauthorization Act	
°F:	Degrees Fahrenheit	STEL	Short-Term Exposure Limit	
FDA:	Food & Drug Administration	SDS:	Safety Data Sheet	
g/l:	Grams per Liter	SDWA:	Safe Drinking Water Act	
HAPs:	Hazardous Air Pollutants	TLV:	Threshold Limit Value	
Hg:	Mercury	TRI:	Toxics Release Inventory	
HMIS:	Hazardous Materials Identification System	TSCA	Toxic Substances Control Act	
HNOC:	Hazard(s) Not otherwise classified	TWA	Time – Weighted Average	
IARC:	International Agency for Research on Cancer	U.N.	United Nations	
IATA:	International Air Transport Association	WHMIS	Workplace Hazardous Materials Information System	
ID:	Identification / Identity	>	Greater Than	
IDLH:	Immediate Danger to Life or Health	<	Less Than	
IMDG:	International Maritime Dangerous Goods	73/78:	1973 & 1978	
LC:	Lethal Concentration			

regulations pertaining to handling, use and disposal.

Version:	Date:
1	Created: 2/21/2017
2	3/13/2018 - sp
3	1/10/2019 - sp
4	9/9/2021 - sp

**END SAFETY DATA SHEET**