

Version 2.0 Revision Date 04/24/2017

Print Date 09/17/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	ZEP INSTANT SPOT RMVR ZUS
Material number	:	ZUSPOT19
Manufacturer or supplier's o	leta	nils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Carpet Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification Gases under pressure : Liquefied gas Eye irritation Category 2A ÷ Reproductive toxicity Category 1B 2 **GHS** label elements Hazard pictograms Signal word Danger 1 Hazard statements H280 Contains gas under pressure; may explode if heated. 2 H319 Causes serious eye irritation. H360 May damage fertility or the unborn child.

1 / 13



ZEP INSTANT SPOT RMVR ZUS

Version 2.0	Revision Date 04/24/2017	Print Date 09/17/2018
Precautionary statements	 Prevention: P201 Obtain special instructions P202 Do not handle until all safe and understood. P264 Wash skin thoroughly after P280 Wear protective gloves/ pro protection/ face protection. Response: P305 + P351 + P338 IF IN EYES for several minutes. Remove con easy to do. Continue rinsing. P308 + P313 IF exposed or cond attention. P337 + P313 If eye irritation pers attention. P337 + P313 If eye irritation pers attention. P410 + P403 Protect from sunlig place. Disposal: Dispose of contents/container in regulation. 	ty precautions have been read handling. otective clothing/ eye S: Rinse cautiously with water ntact lenses, if present and cerned: Get medical advice/ sists: Get medical advice/ ht. Store in a well-ventilated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 10
butane	106-97-8	>= 1 - < 5
acetone	67-64-1	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
sodium borate, decahydrate	1303-96-4	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	 If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.



ersion 2.0	Revision Date 04/24/2017	Print Date 09/17/2018
	Protect unharmed eye.	
	Keep eye wide open while rinsing.	
	If eye irritation persists, consult a	
If swallowed	: Keep respiratory tract clear.	
	Never give anything by mouth to a	
	If symptoms persist, call a physicia	
	DO NOT induce vomiting unless d	
	physician or poison control center.	
	Take victim immediately to hospita	al.
Most important symptoms and effects, both acute and	: Effects are dependent on exposur contact time).	e (dose, concentration,
delayed	Effects are immediate and delayed	d.
,	Chronic effects are delayed and s	
	observed during an exposure.	
	Causes serious eye irritation.	
	May damage fertility or the unborn	
	Review section 2 of SDS to see al	l potential hazards.
Notes to physician	: Treat symptomatically. Symptoms	s may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	:	Use personal protective equipment.
protective equipment and		Evaporates.



Version 2.0	Revision Date 04/24/2017	Print Date 09/17/2018
emergency procedures	Evacuate personnel to safe areas. Remove all sources of ignition. Beware of vapours accumulating t concentrations. Vapours can accu	o form explosive
Environmental precautions	: Prevent product from entering drait Prevent further leakage or spillage If the product contaminates rivers respective authorities.	e if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent mate acid binder, universal binder, sawo Sweep up or vacuum up spillage a container for disposal.	dust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm	OSHA P0



Version 2.0

Revision Date 04/24/2017

Print Date 09/17/2018

	1	1		1
			120 mg/m3	
		PEL	20 ppm 97 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
sodium borate, decahydrate	1303-96-4	TWA	5 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
		PEL	5 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI
		acid (BAA)		shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas



ZEP INSTANT SPOT RMVR ZUS Revision Date 04/24/2017

sion 2.0	Revision Date 04/24/2017	Print Date 09/17/2018	
Personal protective equipr	nent		
Respiratory protection	ventilation is provided or exposu	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.	
Hand protection Material Remarks	Protective glovesThe suitability for a specific work with the producers of the protect	•	
Eye protection	: Safety glasses Eye wash bottle with pure water		
Skin and body protection	: Impervious clothing Choose body protection accordir concentration of the dangerous s	-	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and a	at the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
рН	: 9-10
Melting point/freezing point	: No data available
Boiling point	: 100 °C
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: The product is not flammable.
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: No data available
Density	: 0.9922 g/cm3
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined

SAFETY DATA SHEET



ZEP INSTANT SPOT RMVR ZUS

Version 2.0	Revision Date 04/24/2017	Print Date 09/17/2018
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: 7.7 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Chronic effects are delayed and symptoms may not be observed during an exposure.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	Confirmed animal carcinogen with unknown relevance to humans
00114	2-butoxyethanol 111-76-2
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Version 2.0

Revision Date 04/24/2017

Print Date 09/17/2018

ZepInc

Acute toxicity	
Product:	
Acute oral toxicity	: Acute toxicity estimate : 4,556 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 15.02 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:	
butane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h
	LC50 Rat: 1,355 mg/l
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h
	LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg
	LD50 Rabbit: > 7,426 mg/kg
propane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h
	LC50 Rat: 658 mg/l Exposure time: 4 h
	LC50 Rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation



Version 2.0

Revision Date 04/24/2017

Print Date 09/17/2018

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

2-butoxyethanol: butane: acetone: propane: sodium borate, decahydrate:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n-	: Remarks: No data available
octanol/water	
Components:	
butane :	
Partition coefficient: n-	: Pow: 2.89



Version 2.0	Revision Date 04/24/2017	Print Date 09/17/2018
octanol/water		
Mobility in soil		
No data available		
Other adverse effects		
No data available Product:		
Regulation	40 CFR Protection of Environm Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, n with a Class I or Class II ODS a Clean Air Act Section 602 (40 0 + B).	as defined by the U.S.
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity



Version 2.0

Revision Date 04/24/2017

Print Date 09/17/2018

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.		Calculated product RQ
		(lbs)	(lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	Acute Health Hazard Sudden Release of Pressure Hazard Chronic Health Hazard	
SARA 302	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.	
The companents of this product are reported in the following inventories:		

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)




Version 2.0

Revision Date 04/24/2017

Print Date 09/17/2018

SECTION 16. OTHER INFORMATION



OSHA - GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	: Contains gas under pressure; may explode if heated. Causes serious eye irritation. May damage fertility or the unborn child.
Precautionary statements	:
	 Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Storage: Protect from sunlight. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	04/24/2017
Print Date:	09/17/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.

Version 2.0

Revision Date 04/24/2017



Print Date 09/17/2018