



# 1. Identification

Product identifier	BEHR® PRO i300 Interior Dead Flat - White Base
Other means of identification	
Product number	PR310
Recommended use	Architectural Coating
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/	Distributor information
Supplier	Behr Process Corp.
	1801 E. St. Andrew Place
	Santa Ana, CA 92705
Telephone	714-545-7101
Emergency telephone	+1 760 476 3962
	+1 866 519 4752
Access code	335213
2. Hazard(s) identification	
Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	10 - 30
Cristobalite	14464-46-1	1 - 5
Flux Calcined Diatomaceous Earth (DE)	68855-54-9	0.5 - 1.5
Quartz (Crystalline silica)	14808-60-7	0.1 - 1
Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Ga	as concentrations

e in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

# 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Observe good industrial hygiene practices.

Precautions for safe handlingObserve good industrial hygiene practices.Conditions for safe storage,<br/>including any incompatibilitiesStore in tightly closed container. Store away from incompatible materials (see Section 10 of the<br/>SDS).

# 8. Exposure controls/personal protection

# **Occupational exposure limits**

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Туре	Value	
Flux Calcined Diatomaceous Earth (DE) (CAS 68855-54-9)	TWA	0.05 mg/m3	
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	

Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF			_
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limi Components	t Values Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide t			_
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Quartz (Crystalline silica) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted fo	r the ingredient(s).	
propriate engineering trols	Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels	ocal exhaust ventilation, or othe mended exposure limits. If expo	er engineering controls to
vidual protection measures Eye/face protection	, such as personal protective equipme Wear safety glasses with side shields		
Skin protection Hand protection	Wear appropriate chemical resistant g	gloves.	
Skin protection			
Other	Wear suitable protective clothing.		
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for a uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
neral hygiene siderations	Always observe good personal hygier and before eating, drinking, and/or sm		

# 9. Physical and chemical properties

5. Filysical and chemical p	bioperites
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	White.
Odor	Slight.
Odor threshold	Not available.
рН	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 99 °F (> 37.2 °C)
Flash point	Not applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.52
Solubility(ies)	
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 140 KU (25 °C)
Other information	
Density	12.69 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	0 g/l (excluding water) (Coating) 0 g/l (including water) (Material)
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

reactionsConditions to avoidContact with incompatible materials.Incompatible materialsStrong oxidizing agents.Hazardous decomposition<br/>productsNo hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effe			
Components	Species Test Results		
Quartz (Crystalline silica) (CAS 14	808-60-7)		
<u>Chronic</u>			
Inhalation			
LOEC	Human	0.0563 mg/m3	
Titanium dioxide (CAS 13463-67-7	7)		
<u>Acute</u>			
Inhalation			
LC50	Rat	3.43 mg/l, 4 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
Skin corrosion/irritation	Prolonged skin contact r	nay cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes	may cause temporary irritation.	
Respiratory or skin sensitization	ı		
<b>Respiratory sensitization</b>	Not a respiratory sensitiz	zer.	
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Due to the form of the pr expected.	roduct, exposure to the potentially carcinogenic components is not	
IARC Monographs. Overall	Evaluation of Carcinoger	nicity	
Cristobalite (CAS 14464-		1 Carcinogenic to humans.	
Quartz (Crystalline silica)		1 Carcinogenic to humans.	
Titanium dioxide (CAS 13 NTP Report on Carcinogens		2B Possibly carcinogenic to humans.	
Cristobalite (CAS 14464-		Known To Be Human Carcinogen.	
		Reasonably Anticipated to be a Human Carcinogen.	
Quartz (Crystalline silica)		Known To Be Human Carcinogen.	
OSHA Specifically Regulate			
Cristobalite (CAS 14464- Flux Calcined Diatomace		Cancer Cancer	
(CAS 68855-54-9)	ous Earth (DE)	Cancer	
Quartz (Crystalline silica)	(CAS 14808-60-7)	Cancer	
Reproductive toxicity	This product is not expe	cted to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard	I.	
Chronic effects	Prolonged inhalation ma	y be harmful.	
12. Ecological information			
		fied as onvironmentally bazardous	

# 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
44 Transport information	

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### ΙΑΤΑ

Not regulated as dangerous goods.

## IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

# 15. Regulatory information

**US** federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

# SARA 304 Emergency release notification

Flux Calcined Diatomaceous Earth (DE)

Quartz (Crystalline silica) (CAS 14808-60-7)

Quartz (Crystalline silica) (CAS 14808-60-7)

Quartz (Crystalline silica) (CAS 14808-60-7)

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1)

Cristobalite (CAS 14464-46-1)

Cristobalite (CAS 14464-46-1)

Cristobalite (CAS 14464-46-1)

(CAS 68855-54-9)

(CAS 68855-54-9)

(CAS 68855-54-9)

(CAS 68855-54-9)

Cancer Cancer

Cancer lung effects lung effects

> lung effects immune system effects immune system effects

immune system effects kidney effects kidney effects

kidney effects

## **Toxic Substances Control Act (TSCA)**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Quartz (Crystalline silica) (CAS 14808-60-7)

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

#### SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

## **US state regulations**

# US. Massachusetts RTK - Substance List

Cristobalite (CAS 14464-46-1) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

# US. New Jersey Worker and Community Right-to-Know Act

Cristobalite (CAS 14464-46-1) Mildewcide (CAS 55406-53-6) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

Cristobalite (CAS 14464-46-1) Flux Calcined Diatomaceous Earth (DE) (CAS 68855-54-9) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

#### US. Rhode Island RTK

Cristobalite (CAS 14464-46-1) Quartz (Crystalline silica) (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

# 16. Other information, including date of preparation or last revision

Issue date	26-December-2019
Revision date	16-June-2020
Version #	03
Further information	HMIS® is a registered trade and service mark of the ACA. B - Safety Glasses, Gloves
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0 Personal protection: B
List of abbreviations	DOT: Department of Transportation (49 CFR 172.101). IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG Code: International Maritime Dangerous Goods Code. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. LOEC: Lowest observable effect concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PEL: Permissible Exposure Limit. TWA: Time Weighted Average Value.
References	HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity
Disclaimer	Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.